

Copyright © 1976, 1977, 1978, 1979, 1980, 1981, 1983 Intel Corporation Intel Corporation, 3065 Bowers Avenue, Santa Clara, California 95051



. . . ق م 2.10 · · · · "HOLDING" Ser Y.

Additional copies of this manual or other Intel literature may be obtained from:

Literature Department Intel Corporation 3065 Bowers Avenue Santa Clara, CA 95051

.

The information in this document is subject to change without notice.

Intel Corporation makes no warranty of any kind with regard to this material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Intel Corporation assumes no responsibility for any errors that may appear in this document. Intel Corporation makes no commitment to update nor to keep current the information contained in this document.

Intel Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in an Intel product. No other circuit patent licenses are implied.

Intel software products are copyrighted by and shall remain the property of Intel Corporation. Use, duplication or disclosure is subject to restrictions stated in Intel's software license, or as defined in ASPR 7-104.9(a)(9).

No part of this document may be copied or reproduced in any form or by any means without the prior written consent of Intel Corporation.

The following are trademarks of Intel Corporation and its affiliates and may be used to identify Intel products:

AEDIT	IMMX
BXP	Insite
CREDIT	int _e l
1	IntelBOS
1 ² ICE	Intelevision
ICE	int ligent Identifier
1CS	int ligent Programming
DBP	Intellec
DIS	Intellink
+LBX	IOSP
'm	

(PDS RMX ISBC ISBX SDM 1SXM Library Manager MCS Megachassis MICROMAINFRAME

MULTIBUS MULTICHANNEL MULTIMODULE Plug-A-Bubble PROMPT Ripplemode RMX/80 RUPI System 2000 UPL

REV.	REVISION HISTORY	DATE
-01	Original issue.	76
-02		77
-03		78
-04		79
-05		9/79
-06		5/81
-07	Adds information to support ISIS V4.2; corrects techni- cal and typographical errors.	11/81
-08	Combines Change Package with manual.	1/83
		l I
	}]



, ,

du - ...

,

·

· - -

•

1

ļ

ſ

PREFACE

ĉ



.

and the state of t

This manual describes, and defines the use of, the Intel Systems Implementation Supervisor (ISIS-II). ISIS-II is the operating system for the Intellec and Intellec Series II microcomputer development systems.

The information in this manual supports the system designer who is using a microprocessor or related Intel products in a program-controlled system.

This manual contains seven chapters and five appendices:

- "Chapter 1. Introduction," which describes the general capabilities of ISIS-II.
- "Chapter 2. Getting Started with ISIS-II," which describes some of the programs of ISIS-II and the step-by-step procedures for loading and executing ISIS-II on the Intellec development systems.
- "Chapter 3. File Creation and Management," which describes and shows examples of the ISIS-II commands for entering, storing, and managing program and data files.
- "Chapter 4. Working with Program Modules," which describes and shows examples of the ISIS-II commands for storing, identifying, and manipulating user-written program modules.
- "Chapter 5. Use of ISIS-II and the Monitor by other Programs," which describes and shows examples of ISIS-II system calls that can be included in user-written programs to use ISIS-II and Monitor capabilities without direct intervention by the user from the system console.
- "Chapter 6. The Intellec Monitor," which describes and shows examples of the Monitor commands for program debugging.
- "Chapter 7. Interrupt Processing," which describes and shows examples of using the Intellec interrupt functions.
- "Appendix A. Hexadecimal Paper Tape Format," which describes the paper tape format used by the Monitor.
- "Appendix B. Hexadecimal-Decimal Conversion," which is an aid for doing hexadecimal to decimal and decimal to hexadecimal conversions.
- "Appendix C. Error Messages," which is a listing of the error messages issued by ISIS-II and the ISIS-II commands.
- "Appendix D. ISIS-II Sample Programs—TYPE," which lists two versions of TYPE, in PL/M and in 8080/8085 Assembly Language.
- "Appendix E. ASCII Codes," which shows ASCII codes, their meanings, and their values.

All a subscription of posterior of

ł

â

۱V

Related Publications

For more information on the Intellec Series II microcomputer development system see the following manuals:

- A Guide to Intellec Microcomputer Development Systems, 9800558, which introduces microcomputer development systems in general and the Intellec systems in particular. It presents an overview of the purpose and use of development systems.
- Intellec Series II Installation Manual, 9800559, which contains the installation information for all models.

AR

- Intellec Series II Hardware Interface Manual, 9800555, which describes the use of peripheral I/O devices with the Intellec Series II.
- Intellec Series II Schematic Drawing, 9800554, which contains the schematic diagrams for Intellec Series II Microcomputer Development Systems.

For more information on the Intellec Microcomputer Development System see the following manuals:

- MDS-DOS Hardware Reference Manual, 9800212, and the Intellec Double Density Diskette Operating System Hardware Reference Manual, 9800422, which describes the physical installation of the flexible disk drives supported by ISIS-II for the Intellec Microcomputer Development System.
- MDS-740 Hard Disk Subsystem Operating and Checkout, 9800943, which describes the day-to-day operation procedures for the hard disk drive.

For information on the text editor which runs on the Series II, see the following manual:

• ISIS-II CREDIT (CRT-Based Text Editor) User's Guide, 9800902.

For the most complete and up-to-date list of software and hardware documentation, refer to the current Literature Guide, 802800. This publication provides references to such publications as PL/M80 and PL/M-86 manuals, ASM80 and ASM86 manuals, PASCAL-80 and PASCAL-86 manuals, and FORTRAN-80 and FORTRAN-86 manuals.

	1) 'iftr	· 1 김리	н 5-	7	17.12	
Notational Conventions	1 A 4	, 5⊀	9	f	11 - 11	5
	11.5%	1 A	េះ ជំរ	, ·	NH 58	
						,

The following conventions are used to show syntax in this manual:

UPPERCASE	Information in uppercase must be entered as shown. It can be entered in uppercase or lowercase.
<lowercase></lowercase>	Fields in lowercase indicate variable information. They are enclosed in angle brackets $(< >)$ to show field limitation because some formats do not need a delimiting space or punc-
fi '	tuation. The angle brackets should not be entered.
[]	Brackets indicate optional fields.
•••• ••5 ,	Ellipses indicate that a field may be repeated.
()	Braces indicate a choice. One of the items within the braces must be picked unless the field is also surrounded by brackets, in which case it is optional.
I	A vertical bar indicates choice of syntactic elements on either side.
punctuation	Punctuation other than ellipses, braces and brackets must be entered as shown. For example, the punctuation shown in the following command must be entered: $\frac{1}{2} + \frac{1}{2} + \frac{1}{2} + \frac{1}{2} = \frac{1}{2}$
276 RF 11 11 11	SUBMIT PLM80(PROGA,SRC,'9 SEPT 78')
el97	14 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
2	en fort en state de la service

intel

۰.

CONTENTS (Cont'd.)

PAGE

READ - Transfer Data from File to Memory	5-9
WRITE - Transfer Data from Memory to File	5-10
SEEK - Position Disk File Marker	5-12
RESCAN - Position Marker to Beginning of	
Line	5-14
CLOSE - Terminate Input/Output Operations	
on a File	5-15
SPATH - Obtain File Information	5-16
Disk Directory Maintenance	5-18
DELETE - Delete a File from the Disk	
Directory	5-18
RENAME - Change Disk Filename	5-19
ATTRIB - Change the Attribute	
of a Disk File	5-20
GETATT - Obtain Attribute Information	5-22
GETD - Obtain File Device Directory	5-23
Console Reassignment and Error Message Output.	5-25
CONSOL - Change Console Device	5-25
WHOCON - Determine File Assigned as	
System Console	5-26
ERROR - Output Error Message on System	
Console	5-27
Program Execution	5-28
LOAD - Load a File of Executable Code and	
Transfer Control	5-28
EXIT - Terminate Program and Return	
to ISIS-II	5-30
Monitor I/O Interface Routines	5-30
CI - Console Input Routine	5-31
CO - Console Output Routine	5-32
RI - Reader Input Routine	5-33
PO - Punch Output Routine	5-34
LO - List Output Routine	5-35
UI - Universal PROM Programmer Input	
Routine	5-36
UO - Universal PROM Programmer Output	
Routine	5-38
System Status Routines	5-40
CSTS - Console Input Status Routine	5-40
UPPS - Universal PROM Programmer Status	
Routine	5-41
IOCHK - Check System I/O Configuration	
Routine	5-42
IOSET - Set System I/O Configuration Routine.	5-44
MEMCHK - Check RAM Size Routine	5-44

,

CHAPTER 6

د

THE INTELLEC MONITOR

Command Entry	6-1
Entry Errors	6-2
Command Categories	6-3
Monitor I/O Configuration Commands	6-3

PAGE

A - Assign Command	6-4
Q - Query Command	6-5
Memory Control Commands	6-6
D - Display Command	6-6
F - Fill Command	6-7
M - Move Command	6-7
S - Substitute Command	6-8
Register Command	6-9
X - Register Command (Display Form)	6-9
X - Register Command (Modify Form)	6-10
Paper Tape I/O Commands	6-11
R - Read Command	6-11
W - Write Command	6-12
E - End-of-File Command	6-12
N - Null Command	6-13
Execute Command	6-14
G - Execute Command	6-14
Utility Command	6-16
H - Hexadecimal Command	6-16

CHAPTER 7

INTERRUPT PROCESSING

Priority of Interrupts	7-1
The Interrupt Mask Register	7-1
Interrupt Mask Register Initialization	7-2
Interrupt Acceptance	7-2
Interrupt Removal	7-2

APPENDIX A

JRMAT
JRMA T

APPENDIX B HEXADECIMAL-DECIMAL CONVERSION

APPENDIX C ERROR MESSAGES

Numbered ISIS-II Error Messages	C-1
Link Error Messages	C-4
Fatal Error Messages	C-4
Non-Fatal Error Messages	C-5
Locate Error Messages.	C-5
Fatal Error Messages	C-5
Non-Fatal Error Messages.	C-7
Lib Error Messages	C-7
Editor Error Messages	C-9

APPENDIX D

ISIS-II SAMPLE PROGRAMS[®]TYPE

APPENDIX E ASCII CODES

INDEX

.

CONTENTS (Cont'd.)



ъ	۰.	~ 1	
г.	A١	UI	E.

I. Jusset Commond	2 47
	3-47
I Command Examples	3-47
S - Substitute Text Command	3-48
S Command Examples	3-49
D - Delete Command	3-49
D Command Examples	3-49
K - Kill Line Command	3-49
K Command Examples	3-50
Typing a File	3-50
T - Type Command	3-50
T Command Examples	3-51
Terminating a Session and Saving Your File	3-51
E - Exit Command	3-51
E Command Example	3-52
Q - Quit Command	3-52
Q Command Example	3-52
W - Write Command	3-52
W Command Example	3-52
Reading Data from Disk.	3-53
A - Append Command	3-53
A Command Examples	3-53
Determining Memory Space Available	3-53
M - Memory Command	3-53
M Command Examples	3-54
Command String Iterations	3-54

CHAPTER 4 WORKING WITH PROGRAM MODULES

Microprocessor Memory Allocation	4-1
Program Segments	4-2
Code Segment	4-2
Data Segment.	4-2
Stack Segment	4-3
Memory Segment	4-3
Common Segments	4-3
Absolute Information	4-3
Modular Program Development	4-3
Faster Program Development	4-4
Use of Different Source Language	4-4
Shared Subprograms	4-4
Easier Debugging and Program Modification	4-4
Mechanics of Relocation and Linkage	4-4
Relative Addressing	4-4
Intrasegment References	4-5
Intersegment References	4-5
External References and Public Symbols	4-5
Use of Libraries	4-6

101 - 10 9 1 1
LINK Command 4-7
Link Map 4-8
Order of Modules in the Output File 4-9
LOCATE Command
LOCATE Control Descriptions
MAP 4-11
COLUMNS (number) 4-12
PRINT (file) 4-12
SYMBOLS 4-12
LINES 4-13
PUBLICS 4-13
PURGE 4-13
ORDER(segment sequence) 4-13
NAME(name) 4-14
RESTART0 4-14
START(address) 4-15
STACKSIZE(value) 4-15
How LOCATE Locates Segments 4-15
Locating with the Default Order 4-15
Locating with the Default and ORDER Control 4-16
Locating with the Default, ORDER Control, and
Specific Addresses4-16
LIB Command 4-17
Continuation Lines 4-18
CREATE - Create a Library File 4-18
ADD - Add Modules to a Library File 4-18
DELETE - Delete Modules from a Library File 4-18
LIST - List Library Modules and Their Public
Symbols 4-19
EXIT - Return to ISIS-II 4-19
Program Overlays and Linked Loading 4-20
Memory Pages and the H and L Registers 4-21

CHAPTER 5 USE OF ISIS-II BY OTHER PROGRAMS

31.

AND WELL

ç

*

Memory Organization and Allocation	5-1
Line-Edited Input Files	5-3
Terminating a Line	5-3
Reading from the Line-Edit Buffer	5-3
Editing Characters	5-4
Reading a Command Line	5-4
Summary of System Calls	5-5
System Call Syntax and Usage	5-5
PL/M Calls	5-6
Assembler Language Calls	5-6
File Input/Output Calls	5-7
System Calls Cautions	5-7
OPEN - Initialize File for Input/Output	
• Operations	5-8



This chapter is for the user who has little or no prior programming and computer system experience. However, the information is beneficial to anyone who wishes to familiarize herself or himself with the terms and concepts pertinent to ISIS-II.

The Intellec Systems

ISIS-II is an operating system for the Intellec development systems:

- Intellec Series II Microcomputer Development Systems
- Intellec Microcomputer Development System

ISIS-II supports all models of Intellec systems with one or more single- or doubledensity disk drives and at least 32K of RAM.

The Intellec systems support both software and hardware program development. In conjunction with ISIS-II, they provide the environment for software development, testing and debugging. You can execute your assembly language code on the development system during the logic debugging phase (simulating any specialized I/O used in your product).

When you add the appropriate In-Circuit Emulator you can execute and debug your code for all In-Circuit Emulator supported processor families.

ISIS-II supports the following peripheral devices:

- Universal PROM programmer
- Line printer
- Paper tape reader
- Paper tape punch
- TTY
- CRT terminals
- Flexible disk drives
- Hard disk drives

The ISIS-II Disk Operating System

An operating system is a group of programs that manages the resources of a system and frees you to concentrate on other tasks. It provides a simple command language that allows you to state what you want done and what device or file you want it done to. For example, a disk drive and a line printer have very little in common. The disk drive is a random access input/output device and the line printer is a sequential output-only device. The operating system lets you copy data to either one with the same command.

The computer has to execute thousands of instructions to carry out each command. It has to read the command, determine what it means, get the data from one location, copy it to another, and tell you that it is done. All you have to specify is what you want done; in this case, copying a file. You don't have to worry about the details.



TABLE

2-1 C-1

3	TITLE	PAGE	TABLE	E TITLE	PAGE
ISIS-II S	upported Configurations	2-1	C-2	Fatal Errors Issued by System Calls	C-3
Nonfata	Error Numbers Returned	by	E-1	ASCII Code List	E-1
Systen	n Calls	C-3	E-2	ASCII Code Definition	E-2

۶r

ILLUSTRATIONS

TABLES

an the state of th

ş

6 . 9 - 1 9 - 1 9 - 1 8 - 1 8 - 1 9

intel

A-1 Paper Tape Record Format A-	PAGE	TITLE	FIGURE
	A-1	aper Tape Record Format	A-1 F
	к к к		
ن ، به بر بر ب	،		
	· · · · · · · · · · · · · · · · · · ·	,	
・ (ディスペン) - 「読・・・ - 「読・・・	* * . *	J	
	、 スマパン ア - 注。 ママ・注。	••, , , ,	

. ;

Any disk used by ISIS-II must be formatted by ISIS-II. Once this is done you can select or create files on the disk. There are four basic types of files:

- Format files that contain information about the disk itself. The directory is a format file. ISIS-II rejects disks that do not have the required format files.
- System files that contain the basic ISIS-II system programs and command programs. A disk that contains the minimum files essential for ISIS-II operation is called a system disk. A disk that does not have these files is called a non-system disk.
- User-written program files
- Data files that are used by your programs or by ISIS-II

Modular Programming

A modular approach to program design with ISIS-II is similar to a modular approach to designing a multifunction hardware system. In either case, you can determine the functions required and draw a block-diagram of the proposed system. Each block or module would then be handled as a discrete element whose inputs and outputs are fully defined in a specification.

For example, to produce a program for a traffic light controller, you might want a module to count vehicles approaching from a given direction, another module to determine the time of day; another for the time of year; one or two more modules to control the frequency and duration of the red, yellow, and green lights; and a final module to detect and allow passage of emergency vehicles.

Each of these modules can be written, tested, debugged, and modified independently with ISIS-II. You can also write different modules in different programming languages. For example, you might write the routines that do the calculations in FORTRAN because of its mathematical capabilities, input and output routines in PL/M because of the ease with which it handles port input and output, and assembly language for supervisor routines that handle the bit manipulation that may be required.

Finally, when all the modules are tested and debugged, you can combine them into a system with the ISIS-II LINK command. This LINK capability, combined with the other ISIS-II functions, makes modular programming possible. You don't have to write a single large program that is difficult to test and debug. You write small program segments and combine them into a complete program after they are individually debugged.

While the hardware portion of the system is being designed, you may not know what RAM and ROM addresses you will have for your code. You can write code that can be assigned fixed addresses at a later time, using the relocatable assemblers and compilers. The ISIS-II LOCATE command provides this facility. If testing of the final product finds problems that require the programs and data to be moved, you can do it with the LOCATE command rather than making extensive code changes.

The ISIS-II LIB command lets you create and change libraries of commonly used programs and subroutines. You can then include these programs and subroutines in your programs just by specifying their names. When you LINK your programs, you specify the library along with your programs. Only those programs that you use are included with your code.

During the development you can use the appropriate Intel In-Circuit Emulators to test your programs and hardware and simulate hardware configurations.

The Intellec system also interfaces to your Universal PROM Programmer to load your program in PROMs (Programmable Read Only Memory) or EPROMs (Erasable Programmable Read Only Memory).

- t)

ł

The Intellec development systems contain a Monitor in ROM (Read Only Memory), which provides basic system control facilities in the form of commands (that you enter at the console) and system calls (that you code in your programs) to access memory and I/O devices.

The ISIS-II operating system uses the Monitor also, rather than duplicate functions that already exist there. In fact, all input and output operations, except for disk operations, are handled by the Monitor.

ISIS-II Functions

Marine Contraction and the second

ISIS-II provides the functions to manage your programs and data and assemble your assembly language code. You can add the PL/M and FORTRAN compilers and other assemblers to ISIS-II.

To manage your programs and data ISIS-II provides:

- A text editor to create and change files. The text editor automatically keeps a copy of the unchanged version of a file when you make changes. The editor has commands to handle single characters and large numbers of lines.
- A function to delete whole files that are no longer needed
- Functions to convert program object code to and from hexadecimal formats
- A function to copy files
- A function to change the name of files
- A function to work with file attributes
- Functions to combine program parts into complete functional systems
- A feature to list all files, their length, and their attributes
- A feature to invoke system calls under pseudo-batch operation

Disk Files

The programs that make up ISIS-II are contained in disk files, on hard disk drives or flexible disk drives. When the system is reset with an ISIS-II system disk in the appropriate drive the operating system initializes and takes control of the system. Unless your flexible or hard disk has been formatted previously, you must format it for ISIS-II before it may be used.

Only the essential ISIS-II files are loaded. Programs to perform specific functions remain on disk until you enter a command that calls them. Then the required program or programs are loaded into memory and executed. This technique gives you the full capabilities of the operating system and lets you reserve the majority of memory space for your work. After the command program has completed its functions, the memory it was using is again available.

Your programs and data are also stored on disks. Each file on a disk has a name. ISIS-II program files come with names assigned; you name each file you create. ISIS-II keeps a directory of all the files on a disk. To access a file, you don't have to know its position on the disk, only its name. If you forget the name, there is a directory command (DIR) that lists the names of all files on a specified disk.

1-2

Editing

Editing in the ISIS-II system is entering and modifying data. You can name a disk file, enter program source code, and save it for future use. After the data is entered and saved on disk, you can use it as input to the assemblers or compilers. If the program has errors, you can correct them and assemble or compile again.

Editing in ISIS-II is done with the Text Editor described in Chapter 3, or the optional editor CREDIT described in the *ISIS-II CREDIT* (CRT-Based Text Editor) *User's Guide*.

Code Format Translations

ISIS-II can convert object module format programs to or from the hexadecimal object format. This capability is provided primarily for users of earlier versions of ISIS.

Module Management

Under ISIS-II, management of software modules or routines that comprise your program is module management. ISIS-II assigns absolute addresses to relocatable modules, combines independently developed modules, and creates a library of modules that are used by more than one program.

I/O Device Management

A primary function of ISIS-II is managing I/O devices. ISIS-II provides a number of aids that greatly simplify your management tasks. The ISIS-II aids are:

- A simple but uniform method of identifying each device and each disk file.
- Preestablished names for devices.
- Specifying a device or file for a series of subsequent operations.

Device/File Name Format

ISIS-II identifies each possible I/O device by means of a unique name. With disks, the name is expanded to identify the file that is to receive or provide data. The file name may be further expanded to allow for those instances when the file is to exist in several forms. For example, you may wish to retain a file in both its original and modified forms. You may also wish to use the same basic name for a program after it has been assembled.

The general format for naming devices and files is:





:device: is a two character designation for a device. The valid device designations are listed in the next section. The device designation is always enclosed in colons. *:device:* is used alone when an actual device is referenced instead of a file that resides on a device.

र**40**5 कर सकती है। जारीकी जारहरूर प्रजास सम्बद्ध प्रतीर होते कर जारी कर समित के दिन के स्वित के **स्वरूप से के** अब्दी से देखा कर कि जाता स्वरूपकों जीवन का प्रतीन के लिया से साम कि जाता के जाता है।

e entres das l'encendants de la composition de la composition de la composition de la composition de la compos Al emmitidades das de la composition de la composition entres compositions de la composition de la composition d

- Second Mexic Music Sector Report Construction of the second system of the second se Second sec
 - ल्यां विकार स्थान स्थान स्थान होते । ल
 - to be a proved a set of the barrier has a shift the terms

painsonpors naturos

(c) Hereitetter Bergeneretten en einen eine Sterkeneren einen einen einen einen einen einen einen einen eine Bergeneren einen Hereiten Bergeneren im Bergeneren einen Bergeneren Bergeneren Bergeneren Bergeneren Bergeneren einen Bergeneren einen Bergeneren einen Bergeneren einen Bergeneren Bergeneren einen Bergeneren Bergene Bergeneren Berg Bergeneren Ber

(a) The energy has been string and string and a string to the late of the string and an and a string and an an an arbitrary and the string and energy has been and an arbitrary and the string and energy has been and an arbitrary and arbitrary an arbitrary and arbitrary and arbitrary arbitrary arbitrary and arbitrary and arbitrary and arbitrary and arbitrary arbitrary and arbitrary arbitrary arbitrary arbitrary arbitrary arbitrary arbitrary and arbitrary arbitr Arbitrary arbi

Start in the control of the set of the test of the start of the set of the

2. Approved a fill of particular energy and exemption of the contract of th

Were the stated way or such at the quark of the group design and the mathematical sector with the A Strend ROM have some all of the instal for group deductions or the sector way and the successioned instally a disease when a continue, wine that the two the sector way and the sector way the subscription of the States and the simple state that the two the sector way and the sector way the subscription of the States and the sector wine the sector way and the sector way the sector of the States and the sector wine the sector way and the sector way and the sector way the sector of the States and the sector wine the sector way and the sector way and the sector way and the sector product the sector of the sector wine the sector way and the sector way and the sector of the sec

[13] M. L. M. L. M. LARDER, M. LER, M. LER,

Brießer eine einerstellte sonderen isterieten interention in och ett om en binner einen er en einen er en einen 1998 Merin betre ortenette bind bind bindet in Merine Perins och eine einen einen einen einen einen einen einen

ીપેલ કારકાર્ય આવ્યા પ્રકાર કારણા **મારાવાં શા**ય આવ્યું છે. તે પ્રાપ્ત આવ્યું કે મુખ્ય પ્રાપ્ત આવ્યું આ પ્રાપ્ત આવ્યું આવ્યું છે. આ ગામ પ્રાપ્ત અને બેંગ્સાંટ **પ્રો**પ્ત શાય બનાવાં કે કે સ્ટાર્ગ બેંગ્સાટ પ્રાપ્ત આવ્યું છે. આ ગામ સ્ટાપ્ત બેંધો સાથે સ્ટાપ્ત અને પ્રાપ્ત અને પ્રાપ્ત અને પ્રાપ્ત અને પ્રાપ્ત અને પ્રાપ્ત અને પ્રાપ્ત અને પ્

. .

ISIS-II also assigns the following device name to a nonexistent device:

(BB: Byte bucket

The byte bucket is nonexistent, but is treated as a real device by ISIS-II commands. The byte bucket receives data that you wish discarded.

Device/File Accessing

The assignment of names to devices and files saves time, since you gain access to these system resources without concern over the addresses that would otherwise be required. The system maintains a record of the device addresses established when the system is configured and of the file addresses established when files are created. Names are converted to true addresses during processing sequences.

Creating a file puts information about the file into system tables. When a file is deleted, its entries are deleted from the system tables.

When a file is accessed by ISIS-II in response to a console command such as COPY, ISIS-II opens and closes the file. When a file is accessed by a program, it must use the OPEN and CLOSE system calls.

Important points to remember are:

- ISIS-II commands are concerned with data transfers to or from a device.
- Accessing any device, file, or program involves a common I/O process.
- The name of the device, file, or program is included as a parameter of the current command or a parameter of a previous command.

System Start-Up

The step-by-step procedure used to load the ISIS-II program from the system disk is simple. However, before proceeding with this start-up procedure, you should be aware of several factors that will affect your use of disks.

Flexible Disk Care

Flexible disks are a cost-effective and convenient medium for the storage of bulk data. However, proper care of the flexible disks is required to ensure continued trouble-free reading and writing of flexible disk files.

Physical handling of a flexible disk requires care to avoid damage to the recording surface and to prevent flexible disk deformation. Specific precautions include:

- Return the flexible disk to its envelope when not in use.
- Do not touch the recording surface.
- Do not smoke when handling the flexible disk.
- Do not clean the recording surface.
- Do not bend the flexible disk or deform its edges by using paper clips or other mechanical devices.
- Do not use pencil or ball point pen on the flexible disk label: use felt tip pen.

. 2 2

· · · ·

ISIS-II Flexible Disks 🌅 🐳

The flexible disks used by ISIS-II contain 77 tracks each. A single-density flexible disk has 26 sectors per track, and a double-density flexible disk has 52 sectors per track, each sector containing 128 bytes. Once a flexible disk has been formatted for one density, it must be reformatted to be used in a drive of another density.

ISIS-II Hard Disk Platters

The hard disk platters used by ISIS-II contain 400 tracks on each of two surfaces. Each track has 36 sectors of 128 bytes. This data format is translated into 200 logical tracks, with 144 logical sectors per logical track. There are two platters per hard disk drive, one fixed, and one removable. The fixed hard disk platter resides in drive 0; the removable hard disk cartridge resides in drive 1.

1, 1. .

Memory

ISIS-II requires a minimum of 32K of random access memory (RAM). The first 12K (starting at location 0) is reserved for use by the portion of ISIS-II that must remain in memory during operation. An additional 320 bytes at the top of contiguous RAM is reserved for the Monitor. The remaining RAM is shared by the program being developed, ISIS-II programs loaded from disk, and data you use or generate during program development.

The Monitor

The Monitor handles the initiation of the system when you first start up. (The startup procedure is described at the end of this chapter.)

In a system without hard disk drives, the Monitor checks drive :F0: to see if power is on and if a system flexible disk is loaded. If ISIS-II is on the flexible disk, it is loaded into memory and control is passed from the Monitor to ISIS-II. If there is no drive :F0:, or if it isn't ready, or if ISIS-II isn't on the disk, control is retained by the Monitor.

If you have a hard disk drive attached, the Monitor seeks a system flexible disk in drive :F4:.

After ISIS-II is loaded, you can access the Monitor functions through the DEBUG command (described in Chapter 3).

I/O Interface

The I/O interface to all standard peripheral devices except disk drives (console, printer, paper-tape reader and punch) is handled by the Monitor. When an input or output operation to these devices is needed, ISIS-II calls the appropriate Monitor routine. When the operation is completed, the Monitor routine returns control to ISIS-II.

ISIS-II handles the disk I/O itself. The routines in the Monitor are for the slower devices that accept or send data on a byte-by-byte basis.

the Intellec Mid two systems dif tions the same i	un on the Intel crocomputer De fer because of I n both systems.	lec Series II Microco evelopment Systems hardware difference	omputer Development 5. The start-up procedu es, but the operating sy	Systems of res for the stem fund
			Katt i t	-
		CAUTION	-1	7
; ,			· A. C. M.	•
The follow	ing can damage	or modify the conte	ents of a disk:	
Removal c engaged.	or application of	of power with the	disk installed and the	e drive
Pressing th ing a disk I	e top of the BO /O operation.	OOT switch (selectin	g the Monitor bootstra	p) dur-
Removal o put is a hyp	f a disk while n hen).	ot at the ISIS-II con	nmand level (last conso	le out-
Failing to v ing the both	vait for INTER com of the BOO	RUPT 2 light to go T switch during sta	on and then off before rt-up.	press-
	فر	NOTE	<u> </u>	* 216
		at the Monitor is in	control after the ISIS-I	l start-
If the consupport of the consumption of the constant of the co	are, check for sk, or disconned	a non-system disk cted drive.	in drive :F0:, an inco	rrectly
If the cons up proceduinstalled di	are, check for sk, or disconned	a non-system disk cted drive.	in drive :F0:, an inco	orrectly
If the cons up proced installed di	ole indicates that are, check for sk, or disconned	a non-system disk cted drive.	in drive :F0:, an inco	•rrectly
If the cons up proced installed di	ole indicates that are, check for sk, or disconned	a non-system disk cted drive.	in drive :F0:, an inco	rrectly
If the consup proceed installed di	sk Start-Up	a non-system disk cted drive.	in drive :F0:, an inco	•rrectly
If the consup proceed installed di	sk Start-Up	a non-system disk cted drive.	in drive :F0:, an inco	rrectly

- 1. Apply power to the system and external flexible disk drive unit (if attached).
- 2. Insert the ISIS-II system flexible disk in drive :F0: (write protect slot first). Push the flexible disk into the slot until it latches.

3.	Close the drive door.	the the second
4.	Press the RESET button.	• • • • • •

5. Observe that the following appears on the console screen to indicate the readiness of ISIS-II to accept commands: ISIS-II, Vm.n where Vm.n is the version number.

. ..

.

filename is the one-to six-character name you create for a file. The characters can be alphabetic or numeric. Files can be referenced by the file name alone only if they reside on a disk loaded in drive :F0:. That is, if *:device:* is not specified, :F0: is the default.

.extension is a one-to three-character name you can create for files. An .extension is not required when a file is created. But if .extension is specified, it must always be used when referencing the file. A common use of .extension is to distinguish between different files associated with a single program.

For example:

:F1:PROGA.SRC :F1:PROGA.LST	 for source code for the listing of the assembly 	densit te oma obert
:F1:PROGA.OBJ :F1:PROGA.LNK :F1:PROGA	 for the object code for the linked object code for the code located at absolute 	and south the state of the stat

Note that all these files have the same *filename* and are distinguished only by .extension.

If the disk that contains these files was moved to drive :F2:, the names would become :F2:PROGA.SRC, :F2:PROGA.LST, etc. No matter where the disk is loaded, *filename* and *.extension* stay the same but *:device:* is dependent on the physical location.

TENSO DEF TRANSCON

1. 2 . .

System Designated Device Names

Filenames and extensions are assigned by you. However, device names are established by the system and include the following:

				,	•,		·	, ·	•	,	
:F0:					,	,					4
through		ſ		×.,			•••	,		•	
:F9:	Disks (refer to Table 2-1 for su	ported co	nfigura	ation	s)						
:TI:	Teletypewriter keyboard					هيد ر	~ (A. S.		a 72 38	54
:TO:	Teletypewriter printer		•	• • •	4.	1 - 7			, , , , ,	1.154	,
:TP:	Teletypewriter punch	,			\$	9734		.,	·. ·.		
:TR.	Teletypewriter reader		. 4-	÷.		* • • •				*)	•
:VI:	Video terminal keyboard		1 2172		аг. - а'						, . , .
:VO:	Video terminal screen			•	· ·	÷ t			,		
:HP:	High-speed paper tape punch		` #					ist Sanata	e.		
:HR:	High speed paper tape reader			ſ	~	<u>,</u> ,			•		
:LP:	Line printer						•••	,			•

In addition to the preceding, ISIS-II also assigns the following device names to certain generic devices that do not exist in their own right. These are device names associated with whatever devices are being used as the system console:

:C1: :C0:	Console input Console output	an the she happened	المحمد	Í ,
		11 C CL		\

System operations are directly tied to the console. You can establish any input device as the console input device and any output device as the console output device. The means for doing this is the CONSOL system call as defined in Chapter 5.

If you are using an Intellec Series II Microcomputer Development System, the keyboard and screen of the terminal are :CI: and :CO: respectively.



This chapter describes how to use ISIS-II to create, revise, and manage files. In most cases the files will be program files generated through the use of an assembler or compiler. However, ISIS-II can also create data or program files through the use of Text Editor commands that are designed to add, delete and replace characters or lines as displayed on the system console.

The chapter begins with an explanation of various aids that are available to the console user. These aids are operating hints or simply descriptions of system characteristics that should be understood before attempting more complex tasks. The chapter then goes on to explain the use of ISIS-II commands that allow you to create, revise, or delete files and/or references to files within a file directory. The final subject matter explains use of the ISIS-II Text Editor. The CREDIT CRT-Based Text Editor is described in the ISIS-II CREDIT (CRT-Based Text Editor) User's Guide, 9800902.

Console User Aids

The explanation of console user aids is essentially an introduction to the use of ISIS-II and its subordinate programs. Many of the items covered are delineated to the extent necessary to fully define their impact on major ISIS-II functions. Other items are introduced at this point and receive further coverage elsewhere.

** 44

L ST & MENTER

Line Editing

12

There is no direct hardware data link between the console's keyboard and CRT; rather, each keyboard input to the computer is echoed back, by software, to the console for display (or printing). This technique assures you that the intended character has been entered without error. The entered (input) characters and the echoed (output) characters are stored in separate buffers until a carriage return is typed or a maximum of 122 characters have been entered. In either case, the input (line editing) buffer content is forwarded to its intended destination via one or more system generated READ commands. Prior to line termination, you can revise or delete the buffer contents by using special non-printable 'editing' characters and character combinations. These 'editing' characters are not normally stored in the line editing buffer but rather provide control over the buffer contents. The editing characters are:

- **RUBOUT** Deletes the preceding character from the line editing buffer. The deleted character also disappears from the CRT. On systems using a teletypewriter, RUBOUT echoes the deleted character to the teletypewriter. Repeated usage is allowed.
- CONTROL/P Used before another editing character (including CONTROL/P) to allow entry of the editing character into the line editing buffer.
- CONTROL/R Causes the display of the current contents of the line editing buffer.
- CONTROL/X Deletes the entire contents of the line editing buffer. Causes the display of a number sign (#) followed by a carriage return and line feed.

The operating and storage environment must be compatible with the materials of the flexible disk. The environment of the flexible disk should meet the following criteria:

- No noticeable dirt, dust, or chemical fumes in the immediate area.
- Temperature between 50 F° (10 C°) and 125 F° (52 C°).
- Relative humidity between 8 and 80 percent.
- Wet bulb temperature of 85 F° (30 C°) maximum.
- No direct sunlight on flexible disk surface for prolonged periods.
- No magnetic field.

Loading a flexible disk into a flexible disk drive and removing it from a drive requires a few precautions to avoid damage and to ensure proper operation. These precautions include:

- Do not insert or remove a flexible disk unless power is applied to both the system and the flexible disk drive.
- Do not open the flexible disk drive door unless the DRIVE light is off (push Intellec RESET switch and hold down, if necessary, to disengage drive).
- Do not attempt loading of single-density flexible disks from double-density drive or vice versa.
- Insert flexible disk with read/write access slot first.
- Close door of the drive after flexible disk insertion.
- Do not remove flexible disk unless the last output to console was a hyphen (ISIS-II is ready to receive a command).
- Do not attempt to write to a flexible disk unless it has been formatted as defined in Chapter 3.

Hard Disk Care

The hard disk drive assembly (that is, the hard disk drive with removable cartridge installed) is *extremely* sensitive to contaminants on the hard disk platter surface. The head does not make contact with the disk platter, but rides about 1.14 microns above it. An average human hair is about 100 microns in diameter, and a typical smoke particle is about 6.35 microns. If either of these objects or such "invisible" contaminants as fingerprints or dust particles comes between the disk drive head and the disk.

Follow these procedures and precautions when using a hard disk drive:

- The operating environment should meet the criteria listed above for flexible disk care, with the following additions.
- Clean any dust or dirt from the cartridge cover and drive chassis. Use a lint-free cloth.
- Allow nothing to touch the disk surface.
- Inspect the disk surfaces periodically. If it is visibly dirty, or scratched, it must be serviced. Contact your Intel service representative.
- Keep liquids away from the hard disk drive.
- Do not smoke in the hard disk drive area.
- Before using a disk cartridge that has just been brought into a new operating environment, allow at least one hour to let the cartridge temperature stabilize.

For further information, refer to the MDS-740 Hard Disk Subsystem Operation and Checkout Manual, 9800943. (In that manual the Intellec Microcomputer Development System is referred to as the Intellec 800.)

Disk Recording Characteristics

The CONTRACT SP

The following paragraphs contain information you need to properly use ISIS-II commands and understand the prompts and error messages.

, , ,· ,· ,· ,

File Character Coding

Although all data in files is some sequence of binary zeros and ones, these bits are interpreted in different ways according to the type of file. The editor creates files of ASCII-coded text. The data in source programs is interpreted as ASCII-coded text by ASM80, PLM80, or FORT80. When ASM80, PLM80, and FORT80 translate source programs, they produce object programs containing the actual machine instructions and auxiliary information used by the linker, locater, and loader.

The kind of data in a file determines what can be done with the file. An ASCII file can be sent to the line printer; others will print, but the output won't be intelligible. Object programs cannot be executed unless they have absolute addresses assigned by the locater. Even then they may not execute properly if they refer to external locations not present in the object program (see Chapter 4).

It is important to know the kind of data in a file so you can know what can be done with the file. You can use the extension of the filename to reflect the type of data in the file. For example, source programs could have the extension .SRC (or .ASM, .PLM, or .FOR to reflect the language used). The object code produced by the translators could have the extension .OBJ; in fact, if you do not supply a name for the output file, the translators use the name of the input file with the extension .OBJ.

Many ISIS-II programs in addition to the translators assign a specific extension on the input file if you do not supply it. One program, SUBMIT, assumes the extension .CSD on the input file if you do not supply it. This saves you time entering commands but can lead to misunderstandings if you are not aware of what the program does. Other ISIS-II programs create temporary working files with the extension TMP. Some examples of these are EDIT.TMP, LOCATE.TMP, LINK.TMP, and LIB.TMP.

1 . 1. 1

Disk Organization

Flexible disks contain 77 tracks. Tracks of single density flexible disks contain 26 blocks of 128 bytes each. Tracks of double density flexible disks contain 52 blocks of 128 bytes each. Hard disks have 800 tracks, each track having 36 sectors of 128 bytes each. Disks can be either system or non-system.

A system disk contains ISIS-II software necessary for operating the system. A nonsystem disk contains only the information necessary for maintaining the directory of files on that disk, leaving more space for data than on a system disk. Disks must be formatted before they can be used in the system. See the FORMAT and IDISK commands described later in this chapter.

ISIS-II treats a file as a string of bytes. Space is allocated to a file in complete blocks even though the last block in the file may be only partially used. In other words, a block is not shared by two files. When a file is deleted, the blocks it occupied are released for reassignment by ISIS-II.

. 1

1. 9

Intellec Microcomputer Development System

The following procedure defines system start-up from power application through loading and execution for the Intellec Microcomputer Development System.

- 1. Apply power to system, disk drive, and console.
- 2. Insert ISIS-II system disk in drive :F0: (write protect slot first).
- 3. Close drive door.
- 4. Press top of Intellec BOOT switch.
- 5. Press top of RESET switch.
- 6. Observe that INTERRUPT 2 light goes on to indicate loading of ISIS-II.



)), 11 v via treatif

· . . 1

Be sure INTERRUPT 2 is on before proceeding.

ĕ

- 7. Press space bar of video terminal or teletypewriter to select console.
- 8. Observe that INTERRUPT 2 light goes off to indicate receipt of space bar entry.
- 9. Press bottom of BOOT switch to execute ISIS-II.
- 10. Observe that the following appears at the selected console to indicate readiness of ISIS-II to accept commands: ISIS-II, Vm.n where Vm.n is version number.

·

Hard Disk with Flexible Disk Start-Up

Hard Disk Startup

When you start up a system that includes a hard disk, or when you press the RESET switch on an Intellec Series II Microcomputer Development System that includes a hard disk, ISIS-II is loaded from a flexible disk in drive :F4:.

After the system is initialized with ISIS-II system files from :F4:, a fatal error, software reboot, or interrupt 1 will cause the Intellec Series II Microcomputer Development System to refer to the hard disk platter in drive :F0: for ISIS-II system files. If the RESET switch is pressed, the processor refers to the system flexible disk in :F4:. Therefore, after the system is initialized, you can remove the system disk from :F4: until RESET is again pressed.

With a System Disk in :F0:

In an environment with both hard disk drives and flexible disk drives, and a system hard disk in drive :F0:, follow these procedures:

- 1. Apply power to Intellec Series II Microcomputer Development System or Intellec Microcomputer Development System.
- 2. Apply power to hard and flexible disk drives :F0: and :F4:, respectively.
- 3. Place a system flexible disk in :F4:.

Press START switch on hard disk drive; wait for READY light to come on.

- 4. Press RESET on an Intellec Series II, or if using an Intellec Microcomputer Development System:
 - a. Set BOOT to ON
 - b. Press RESET
 - c. Press space bar
 - d. Set BOOT to OFF
- 5. The message ISIS-II, Vm.n is displayed, and the system is ready to accept commands.

2-8

When a file is created, all attributes are reset. That is, the file does not possess any of the attributes listed above. This applies to a file created by the COPY command, also. (Attributes can be copied with the COPY command by specifying the C switch.)

to st A divert

۰.

Invisible: Files with the invisible attribute set are not listed by the DIR command unless the I switch is used. Most system files possess the invisible attribute. It is advisable to make invisible files write-protected also.

Write-protect: Files with the write-protect attribute set cannot be opened for update or for output and cannot be deleted or renamed with ISIS-II commands from the console. Write-protected files can be overwritten by the IDISK and FORMAT commands. Write-protected files cannot be opened for output or update with the OPEN system call (see Chapter 5).

Format: What applies to write-protected files also applies to files with the format attribute set. In addition, files with the format attribute are created on a new disk when it is formatted by the FORMAT or IDISK commands. The following files have the format attribute: ISIS.DIR, ISIS.MAP, ISIS-TO, ISIS.LAB, ISIS.BIN, and ISIS.CL1, plus ISIS-BAD if a hard disk. A system disk must have all of these files. A non-system disk must have ISIS.DIR, ISIS.DIR, ISIS.MAP, ISIS.TO, and ISIS.LAB, plus ISIS.BAD if a hard disk. You should not assign the format attribute to any other file, nor remove the format attribute from a file.

System: Files with the system attribute set are copied to the disk being formatted when the S switch is specified with the FORMAT command. When you use the IDISK command, you must copy the files with the COPY command. This gives you the option of choosing the files for the new system disk.

こういうはない された ちょういんこう

Wild Card File Names

ما با ۲۰ د دی می می د

. . .

1 + + + 1

Some ISIS-II commands allow you to specify filenames using a wild card construct. This means you can use an asterisk (*) or a question mark (?) to replace some or all of the characters in a name or extension. These special characters mean match anything when searching a directory for a filename. For example,

name.* - means match any filename with name and any extension or without an extension.

*.extension - means match any filename with extension and any name.

. - means match any filename.

The asterisk can also specify a wild card match for the remainder of the name or

extension but not for initial characters. For example,

AB*.HEX - means match any filename with AB as first two characters of the name and HEX as the extension. This example would match: ABC.HEX, ABXYZ.HEX, AB.HEX.

*B.HEX is illegal, since * must follow initial alphanumeric characters.

*.BAK - means match any filename with a .BAK extension. This example would match: A.BAK, AB.BAK, or ABC.BAK.

难意为 无理主动的 化合理合理合理

- 1. Argeby strong sources (2. 1996 and a solid gravestication of a settion of a solid solid solid solid solid so British Material Solid Solid
- ³ Comparison and the second second state (where second se Second second

 - age of the positive strategy for a surface of the solar strategy of the solar strategy of the solar solar solar Be at the strategy of the solar so
 - - - 1 Margaret
 - - 1.11
 - 化合理 化二乙烯酸化合物医乙酮医乙酮 化化化合物 建铁
 - and the providence of the second s
 - and the second second

ant Antonio de la companya de la companya Antonio de la companya de la companya

िंग प्रभाग से आतुम् भरेग प्रमान से स्थान से भरापता पर पर प्रमार के समय से स्थान से स्थान केल्स्ट्रिक भरा के फ्रांस प्रभाग से मार्ग्स सिंग, सिंग्स्ट के पर्युत्त के सिंग प्रमार के स्थान से स्थान से स्थान केल्स्ट्रिक साथ के स्थान प्रमान के सिंग से स्थान के स्थान से स्थान से स्थान से साथ से स्थान से स्थान से स्थान स सेल्स्ट्रेक साथ के प्रसार के सिंग से स्थान से सींग सी सिंग से स ç

*

ISIS-II console commands perform four basic tasks:

•	Prepare a new disk f	for	use by	the system (i.e.,	format the disk).	. •
•	Execute programs.	•	-	• . 11	, /	·-

- Create, delete, and revise files and directories.
- Convert object file formats.

The ISIS-II console commands associated with each of the preceding tasks is identified in the following list and is described in subsequent paragraphs.

Disk Maintenance

```
ver let simast
```

121 1

IDISK	Format a new disk to a basic system or non-system disk.	
FORMAT	Format a new disk and copy files.	
FIXMAP	Map bad sectors on a hard disk.	

Program Execution

filename	Execute the program named "filename"
DEBUG	Load a program and give control to the Monitor
SUBMIT	Enter the file that contains commands to be executed

• •

and the construction of the states of the st

· an all the second second

File Maintenance

DIR	Output the names of and information about the files listed within the disk directory
COPY	Copy a file from one device to another
HDCOPY	Copy hard disk tracks to another hard disk
DELETE	Remove references to a file from the directory and free disk storage space associated with that file
RENAME	Change the name of a disk file
ATTRIB	Change and/or display the attribute(s) of a disk file
VERS	Display ISIS utility version numbers

Code Conversion

HEXOBJ	Convert a format	a program	from hexadecim	al to object module
OBJHEX	Convert a format	a program	from object mo	dule to hexadecimal
		анд (р. 1971) 1971 - К	s t = € * 5'* i	teres a sur sur sur
File Editing	· 2	ŕ1,	8 / ¹	trans work a start
EDIT	Create a subcomm	and modify	y ISIS-II files. cribed in this chap	The Text Editor

File Creation and Management

1

.

ŷ

1 3 4 5 7

CONTROL/Z

Causes an end-of-file to be input to the system. There is no change to the display. The contents of the line editing buffer are deleted.

NOTE

The following characters are not editing characters, but they affect terminal output:

CONTROL/S Stops terminal output and delays program execution.

CONTROL/Q	Resumes terminal output after the CONTROL/S command is					
	given.	- 34	PLIENGU	•		51020
	۰,	۰,	• សំណ	set br	.1	
	فعو	[.].	.,' EF-'	, .	· .5d ·	

The line-editing facility can be applied to files other than the console input device. There is a fuller description of line-editing in the section called Line-Edited Input Files, in Chapter 5.

1. 108 N 1 1 1 1 1

The System Console

The device used as the console in the bootstrap procedure is known as the 'initial system console.' The console can be changed to another device by a program executing a CONSOL system call (see Chapter 5) or by using the SUBMIT command. The 'current console' is the device currently serving as console, which may or may not be the same as the initial system console.

11 * (* 17 61

The console, whatever device it is assigned to, is always the source of system commands. The SUBMIT command directs ISIS-II to take commands from a disk file. The SUBMIT file can return control to the initial system console by means of a control/E. The console can also use control/E to return control to the SUBMIT file.

When control/E is input to ISIS-II as part of the command line either from the SUBMIT file or the console keyboard, control/E is echoed but is not entered in the input buffer. To enter a control/E into the input buffer and subsequently into a SUBMIT file, the control/E must be preceded by control/P, in which case control/E is entered as a literal.

Under ISIS-II the files :CI: and :CO: are pseudonyms for the devices serving as console input and output. The :CI: file is always the source of system commands. The :CO: file receives console output such as the echo of a command. These two files are always open. However, it is not an error for a program to issue an OPEN system call for either of these files. Neither :CI: or :CO: count as one of the six files allowed open simultaneously by ISIS-II.

After system bootstrap in an Intellec Microcomputer Development System, the files :CI: and :CO: correspond to either :VI: and :VO: or :TI: and :TO:, depending on which device the space bar was typed during the bootstrap procedure. In the Intellec Series II Microcomputer Development System, :CI: and :CO: are automatically assigned to :VI: and :VO: (the integral console devices). The files :CI: and :CO: can be reassigned to other files by programs issuing the CONSOL system call.

When an end-of-file is encountered in :CI:, :CI: and :CO: are closed, ISIS-II is reloaded, and the initial system console is reopened as :CI: and :CO:.

3-2

If any additional files such as command files are to be on the new disk, they must be copied with the COPY command.

1DISK can be used on single drive and multiple drive disk systems. On single drive systems, you are prompted to remove the system disk and insert the blank disk. When the formatting is completed, you are prompted to insert the original system disk. In systems with only 32K of RAM, two swaps of disks are required.

The syntax of the IDISK command is:

لد . بلغ ار 144

IDISK <device> <label> [<switches>]

where

<device> is the name of the drive containing the disk to be formatted. If you specify :F0:, and no FROM switch, the system assumes a single disk system and prompts for disk swaps as needed. Disk swapping is not required if any drive other than :F0: is specified. A hard disk in :F0: must be formatted as a system disk.

label> is the name to be given to the disk. The syntax of label is the same as for filename with up to six characters for name and three for extension.

<device><label> must be entered with no intervening space or comma, as in :F1:MYDISK. At least one space must be entered before and after <device> <label>.

<switches> are one or more of the following:

S specifies that the new disk is formatted as a basic system disk. If S is not specified, the disk is formatted as a basic non-system disk.

P specifies that IDISK operates in single drive mode and prompts for output and system disks, pausing to display the prompt messages and to allow changing of disks.

FROM n specifies the disk drive containing the disk files needed for formatting. n is an integer 0-9, specifying drives :F0: through :F9:. If the FROM n switch is not specified, the default is to :F0:. If n is not a valid integer 0-9, the following error message appears on the :CO: device:

UNRECOGNIZED SWITCH

When used with a hard disk, IDISK verifies each sector. If IDISK cannot read a sector reserved for an ISIS-II file, the message

FATAL BAD SPOT AT LOGICAL ADDRESS (ttt, sss), STATUS = nnn

appears on the console, and ISIS.CLI is reloaded. ttt is the logical track address (in decimal); sss is the logical sector address (in decimal); and nnnn is the hard disk error status (in hexadecimal). If the unreadable sector does not correspond to an ISIS- II file, then the message

BAD SPOT AT LOGICAL ADDRESS (ttt, sss), STATUS = nnnn

is displayed. Since ISIS-II allocates hard disk sectors serially, if no mechanism existed to "skip over" bad hard disk sectors, the remaining sectors would remain unallocated and unusable. Instead, ISIS-II checks hard disk sectors for irregularities during FORMAT and IDISK operations. If a bad sector is encountered, it is allocated to ISIS.BAD and hard disk formatting continues.

12. (1

\$...

1.1

2

2

When error 24 occurs, the disk surface may be damaged, in which case you may wish to retain as much of the disk data as possible. This may be done by copying the files to a good disk with the COPY command. •• 191 . 12 ,

The action taken in response to fatal errors depends on the setting of an internal system switch called the debug toggle. That switch indicates whether control is to return to ISIS-II (debug=0) or the Monitor (debug=1) when an error occurs.

Any of the following actions sets the debug toggle to one and transfers control to the Monitor:

Pressing interrupt switch 0 while a program is running. ٠

	Executing a DEBUG command	,		•	н. с	c, 1	
-	Executing a DEDOG command.		1	1	11-1-		

Executing a LOAD system call with a transfer value of 2.

Any of the following actions sets the debug toggle to zero, performs the operation listed, then transfers control to ISIS-II:

- Pressing interrupt switch 1 while a program is running. This action terminates processing.
- Executing an EXIT system call. This action terminates a program.
- Executing a LOAD system call with a transfer value of 1. This action loads an absolute object file.
- Executing a Monitor G8 command. This action exits the Monitor.

If the debug toggle is zero when a fatal error occurs, the following occur:

All open files are closed in their current state, including :CI: and :CO:.

- The initial system console device is opened as :CI: and :CO:.
- A fresh copy of ISIS-II is read in from the disk, and ISIS-II prompts for a command with a hyphen (-).

3.6 × . maipen in this 3

If the debug toggle is set when a fatal error occurs, the following occur:

- 1. · 1 . · · · 1. 1. 1. ۰. All open files are left open. .
- 2101 • Control passes to the Monitor.
- server in a Monitor prompts for a command with a period (.).

. .

At this point Monitor commands can be used to examine registers and memory to try to determine the cause of the error. However, the program should not be restarted with a simple Monitor G command, because the ISIS-II restart address has not been saved. DO NOT RESET THE SYSTEM AT THIS POINT. A G8 command should be used instead so all files are closed. Rebooting does not close files.

•

NOTE

Although programs cannot be loaded in the ISIS-II area, the ISIS-II area is not protected from a running program. If a program should happen to destroy parts of ISIS-II, subsequent system calls may not operate correctly and input/output may destroy areas on your disk. This would happen mainly when an undebugged program is running. ISIS-II can always be restored by bootstrapping from a good system disk. - **1** 1

÷

1.14

35 .

The syntax of the FORMAT command is:

FORMAT <device><label>[<switches>]

where

<device> is the name of the drive containing the disk to be formatted. If you specify :F0: and no FROM switch, or if you specify :F0: and FROM 0, then an error will result. A hard disk in :F0: must be formatted as a system disk.

5 * + 1 H - 5

' . &

۶,

2 4 4

NOTE

In the previous versions of ISIS-II, <device> defaulted to :F1: in the FORMAT command. This default has been removed. If you have SUB-MIT files that use this default, you must change them. You will receive an error message if you try to default <device>.

4U.,

** ** .

Ŧ

<a>label> is the name to be given to the disk. The syntax of <label> is the same as for filename with up to six characters for name and three for extension.

<device><label> must be entered with no intervening space or comma, as in :F1:MYDISK. At least one space must be entered before and after <device> <label>.

<switches> are one or more of the following:</switches>	d;
switchess are one of more of the following.	At 1

A copies all files to the specified drive. The new disk contains all the files that were on the source disk. If the source disk is a system disk, the new disk becomes a system disk.

S copies the basic format files and all files with the system attribute set. If the source disk is a system disk, the new disk becomes a system disk. (The S switch functions differently under FORMAT than it does under IDISK.)

FROM n specifies the disk drive containing the disk files needed for formatting. n is an integer 0-9, specifying drives :F0: through :F9:. If the FROM n switch is not specified, the default is to :F0:. If n is not a valid integer 0-9, the following error message appears on the :CO: device:

UNRECOGNIZED SWITCH

When used with a hard disk, FORMAT verifies each sector. If FORMAT cannot read a sector reserved for an ISIS-II file, the message

FATAL BAD SPOT AT LOGICAL ADDRESS (ttt, sss), STATUS = nnnn

appears on the console, and ISIS.CLI is reloaded. ttt is the logical track address (in decimal); sss is the logical sector address (in decimal); and nnnn is the hard disk error status (in hexadecimal). If the unreadable sector does not correspond to an ISIS- II file, then the message

BAD SPOT AT LOGICAL ADDRESS (ttt, sss), STATUS = nnnn

is displayed. Since ISIS-II allocates hard disk sectors serially, if no mechanism exited to "skip over" bad hard disk sectors, the remaining sectors would remain unallocated. Instead, ISIS-II checks hard disk sectors for irregularities during FOR-MAT and IDISK operations. If a bad sector is encountered, it is allocated to ISIS.BAD and hard disk formatting continues.

Disk Directory Content

teiratosaura e abrou as deic

Each flexible disk directory has space for 200 entries. Each hard disk directory has space for 992 entries. This means that a flexible disk can contain 200 files, or a hard disk 992, if the combined size of the files does not exceed the capacity of the disk.

A directory entry contains identifying information about a file. For example, it includes the following items:

· . !

7 .

4, 1 + 1, n¹ +

- Filename
- Number of blocks allocated to the file •
- Number of bytes in the file (length)
- Attributes

ISIS-II provides a DIR command that displays some of the information contained in a disk directory. The DIR command is described later in this chapter.

> . 5 7 "TEO I . .

Filename

Filename within the directory includes .extension. The :device: is not stored in the directory as it only specifies which drive the disk is mounted in during the current ISIS-II execution. a constant a

Blocks

The number of blocks required by a file includes blocks for data and blocks for pointers that are used by the system to specify the location of files. For every 62 blocks of data, another block is required by the system for pointers. The total number of data and pointer blocks required by a file of N bytes can be calculated by the following formula (any result containing a decimal fraction is rounded to the next higher integer value).

[63*]N/128[/62] For example, a file of 9000 bytes requires

[63*]9000/128[/62]= [63*]70.31[/62]= [63*71/62]= [72.15]= 73 blocks required

when the space definition

1 6

2

L. E '

Length

The number of bytes comprising a file is its length. Length increases as a file is written and can be affected by other programs containing the ISIS-II system calls OPEN and SEEK. Refer to Chapter 5 for further information on these system calls.

Attributes

There are four attributes associated with each file that may be set or reset (turned on or off) by the ATTRIB command or the ATTRIB system call. The attributes are:

e .

Invisible . 170 m n · 1. 1.1. 241 and the second s Write-protect . Format System

If you know the name of the file, exit to ISIS-II and delete the file; then use FIXMAP to mark the bad sector. If you do not know the name of the file, follow this procedure:

- 1. Exit to ISIS-II, using either the Quit or the Exit command (described below).
- 2. Give the command

COPY .Fm.* * TO Fn: QC

where "Fm" is the device name of the disk being fixed, and "Fn" is the name of another hard disk. Because of the Q switch, a list of copied files will be generated. (See the description of Copy.)

- **3a.** If the copy is successful, disk :Fn: contains a usable copy of disk :Fm:. Use FIXMAP to get a list of bad sectors on :Fm:; then use IDISK or FORMAT to reformat that disk, and use FIXMAP to mark any bad sectors missed by the formatting command.
- 3b. If an error occurs while the disk is being copied, write down the last filename displayed by Copy, as well as the track and sector numbers appearing in the error message. Use the Delete command to delete the bad file from disk :Fm:; then use FIXMAP to mark the bad sector. If an error occurs and prevents you from deleting the file, repeat step 2. The file you attempted to delete will not be copied to the new disk. Repeat step 3a.

Example 1: The following example illustrates the use of the Mark command.

*MARK 27 83 SECTOR MARKED *MARK 27 83 (27, 83) ALREADY MARKED

Free Command. The Free command changes the known state of a sector from bad to good.

The syntax of the Free command is:

FREE <disk address>

where:

4 144 <disk address> is the track-and-sector address of the sector to be freed for allocation.

1

المرد مر المراجع

to the state

49

If the T switch is present, a group of 36 sectors is freed. You might use this command if you had marked a sector by mistake.

If the sector specified in the Free command is known to be bad, it is freed for allocation. If the T switch is not present, the system displays:

SECTOR FREED

If the T switch is present, no message appears when a single sector is freed; instead, when all 36 sectors have been processed, the system displays the message:

TRACK PROCESSED

0.5

6 1

1 ... 11 ...

The question mark specifies a single character for a wild card match. For example,

A?B.HEX - means match any filename with A and B as the first and third characters of a three-character name and HEX as the extension. This example would match: ACB.HEX, AXB.HEX, AMB.HEX.

A??.* - means match any filename with A as first character of a three-character name and any extension.

:device: cannot include a wild card character.

File Copying

Data can be transferred from one file or device to another by using ISIS-II commands. For instance, if you want to transfer the contents of the high-speed paper tape reader to a file on drive :F0:, you load the paper tape reader and use the COPY command to transfer the contents of the paper tape to the disk file.

ر ،

COPY :HR: TO PROG.SRC

If you want to display a file on the console, use the COPY command in the following way:

COPY FILE.TXT TO :CO:

The HDCOPY command performs a track-by-track copy from one hard disk to another hard disk.

The ISIS-II Text Editor transfers files in a special way. The method employed by the Text Editor is defined later in this chapter.

Using ISIS-II With A Single Drive System

On an Intellec Series II Microcomputer Development System containing a single integrated disk drive, ISIS-II utility programs that have the P (Pause) switch allow you to remove the system disk, insert another disk, and carry out an operation.

Since most programs (such as the ISIS-II Text Editor, BASIC-80, and CREDIT) reload ISIS-II system files when you exit from them, be sure to format all disks used on a single drive system as basic system disks, using the IDISK command with the S switch.

ι.

Using ISIS-II Commands

The file management capabilities of ISIS-II can be controlled in one of three ways:

- Direct entry of ISIS-II commands at a console keyboard. This for the test
- Issuance of ISIS-II system calls by a program.
- Entry of console commands into a file by using the Text Editor. Execution of this file via the SUBMIT command causes ISIS-II to respond as if it were receiving commands directly from you. The advantages are that you need not be present when the submitted job is performed, and the commands do not have to be re-entered each time the job is submitted.

The following text defines only those commands input by you at the console. The definitions include a summary of the preparation of the file created by the command. The use of system calls is described in Chapter 5.

-

Example 3: The following example illustrates the use of the List command. The list is written first to the console, then to a disk file.

*LIST 180, 63 182, 115 182, 116 182, 117 *LIST DISK.FIL LIST WRITTEN

Count Command. The Count command reports the number of known bad sectors on the disk.

The syntax of the Count command is:

COUNT

The command displays the following message on the console:

XXXXX BAD SECTORS

where "xxxxx" is a decimal number, the number of known bad sectors on the disk. A sector that has not been marked, or a sector that has been marked and then freed, is not a known bad sector.

Example 4: The following example illustrates the use of the Count command.

*LIST 180, 63 182, 115 182, 116 182, 117 *COUNT 4 BAD SECTORS

Record Command. The Record command records the changes specified by Mark and Free.

The syntax of the Record command is:

RECORD

When this command is entered, changes specified by Mark and Free are recorded on the disk.

If you intend to use the Exit command to leave the FIXMAP program, the Record command is unnecessary. (Exit is described below.) If you intend to use the Quit command, the Record command is required; otherwise, none of the marking and freeing specified during the work session—or since the last Record command—will actually take effect.

When the recording is complete, the system displays:

CHANGES RECORDED

Program Con	trol in the second
LIB	Create and control program libraries (described in Chapter 4).
LINK	Combine program files and resolve external addressing (described in Chapter 4).
LOCATE	Convert relocatable object to absolute addresses for execution (described in Chapter 4).

Command Syntax

9 onen-thick dain

The general syntax of ISIS-II console commands is:

<command/> <parameters></parameters>	Łā	, he st	211 F	a Catter B	TAMHC
<u>م</u>	r	1 3 80 M	' n	• ,1 *	9AMXF

where

<command> is the name of ISIS-II command program.

<parameters> are one or more data required by the command. When more than one parameter is specified, they are separated by commas or blank spaces unless otherwise noted under the individual commands.

A parameter may consist of one or more switches. Switches may be separated by spaces but not by commas.

In some cases a parameter requires additional information. Such information immediately follows the parameter and is enclosed in parentheses as shown in the following example:

SUBMIT PLM80(PROGA, SRC, '9 SEPT 78')

In ISIS-I some commands required a dollar sign (\$) before each parameter. In ISIS-II those commands accept the dollar sign but treat it as a blank.

Brackets ([]) in the syntax indicate that a parameter is optional. If the option is omitted, default actions are performed by ISIS-II as explained with each command.

In most cases a command is executed when the carriage return is encountered. Any exceptions are noted under the individual commands.

Disk Maintenance Commands

N ST-6403 C.A

1. 2.24

c.

۰, ۰

IDISK - Disk Formatting Command

A blank disk must be formatted before it can be used by ISIS-II. There are two types of ISIS-II disks: system and non-system. The type of disk to be formatted is specified by the presence or absence of a switch with the command.

IDISK copies only the files needed for a basic disk (whether system or non-system). A basic disk contains only the files needed to format the disk: ISIS.DIR, ISIS.MAP ISIS.TO, and ISIS.LAB, plus ISIS.BAD if a hard disk. For a basic system disk, IDISK copies two additional files: ISIS.BIN and ISIS.CLI.

é

FIXMAP Errors

The following errors cause immediate termination of FIXMAP and a return to ISIS-II. If execution terminates as a result of one of these errors, work done since the last Record command is not recorded on the disk.

If no hard disk is present, the system displays:

USE ON HARD DISK SYSTEM ONLY

If no drive number is given in the FIXMAP command, or if an illegal switch is present, the system displays:

INVALID SYNTAX

If this message appears in response to a command within FIXMAP, it means that the command was typed incorrectly, and it does not terminate the session.

If the specified drive number is greater than 3, the system displays:

DRIVE NUMBER OUT OF RANGE

(In the maximum configuration of the system, the hard disk drives are numbered 0 and 1.)

If the disk does not exist in the system, is not on-line, or is not properly connected, the system displays:

ERROR 30 USER PC xxxx

where "xxxx" is a hexadecimal number.

Example 8: The following example illustrates a typical work session with FIXMAP. You invoke the command and begin by getting a list of all bad sectors on the target drive (drive 1, as indicated in the FIXMAP command). The Count command reports that there are eight bad sectors, and the Record command shows that no sectors have been marked or freed during this work session. You free the last 36 sectors on the track containing track 170, sector 113; all sectors except the eight known bad sectors are reported already to be free. You mark track 170, sector 113 as a bad sector, and again list and count the number of bad sectors. This time, the Record command reports that changes have been made. You free the remaining bad sector, list again, and return to ISIS-II.

-FIXMAP 1 ISIS-II MAP FIXER V1.0 *LIST 170, 113		
170, 114	r w ^{ar} fa	Si * 5 *
170, 116		
170, 117	, T	1 90
170, 118		т ⁴ ь
170, 119	, .	
170, 120	•	
*COUNT	, .	
8 BAD SECTORS	t *	r
*RECORD	, , [,] l	
NO CHANGES		L

Example 1: This example formats a new disk in drive :F0: as a basic system disk on a single-drive system. IDISK prompts for the new (output) disk and for the system disk. IDISK gives the disk the name SYS.V1. The COPY command should be used to copy other files on the newly formatted disk. See the COPY command for single drive systems later in this chapter.

IDISK :F0:SYS.V1 S		·	6 8 6	1 .
LOAD OUTPUT DISK, THEN TYPE (CR)	۲	\$ \$ <u>}</u>	ξ.	•y *x † ¦¥ =yee v
-	r		۰ ·	12-14

Example 2: This example formats a new disk in drive :F1: as a basic system disk, and gives the disk the name NSYS.V1. The COPY command copies all other non-format files from the disk in drive :F0: to the disk in drive :F1:.

-IDISK :F1:NSYS.V1 S	1. e	rs fr
SYSTEM DISK		•
-COPY *.* TO :F1. C B		
COPIED :F0:ASM80 TO :F1:ASM80		r
COPIED :F0:ASM80.OV0 TO :F1:ASM80.OV0		
COPIED :F0:ASM80.OV1 TO :F1:ASM80.OV1		
	× بہ '	3
and the second sec		,
·		
COPIED :F0:FPAL.LIB TO :F1 FPAL.LIB		
COPIED :F0:PLM80.LIB TO :F1:PLM80.LIB	1	ar str,
COPIED : F0: SYSTEM.LIB TO : F1: SYSTEM.LIB		
-		trac's
ł		-1050

Example 3: This example formats a hard disk platter in drive :F0: as a basic system disk; the basic files needed to format the disk are copied from a system disk in drive :F4:. The COPY command should then be used to copy other files onto the newly formatted disk, as in the previous example.

-:F4:IDISK :F0:SYSTEM.DSK S FROM 4

FORMAT - Disk Formatting Command

A blank disk must be formatted before it can be used by ISIS-II. FORMAT cannot be used on a single flexible disk drive system. IDISK should be used.

fa"ar

٤,

There are two types of ISIS-II disks: system and non-system. A disk is formatted as a system or non-system disk depending on the type of source disk used and on the switches specified in the FORMAT command.

When a system disk is formatted, FORMAT copies other files in addition to the basic format files. When a non-system disk is formatted, however, FORMAT copies only the basic format files: ISIS.DIR, ISIS.MAP, ISIS.TO, and ISIS.LAB, plus ISIS.BAD if a hard disk. Any other files that are to be on the new disk must be copied with the COPY command.
Filename - Direct Program Execution

As ISIS-II commands except DEBUG are actually the names of disk files containing executable programs. Thus the execution of any other program is accomplished in the same manner—simply by entering the name of the file. You may also include parameters with the filename to provide control over the program to be executed. However, the program must be written to accept these parameters and must read the parameters from the line editing buffer. Refer to Chapter 5 for more information on line editing of command lines.

· · ·

DEBUG - Program Execution Under Monitor

The DEBUG command loads an executable program and passes control to the Monitor, which outputs the contents of the program counter and prompts for a command with a period (.) on the system console. The Monitor G command can then be entered to begin execution of the program. Any errors occurring during execution are handled as described in Chapter 6 of this manual.

The syntax of the DEBUG command is:

DEBUG[<progname>[<parameters>]]

where

<progname> is any ISIS-II command or in broader terms the file name of an executable program. The program must be an absolute object module. If <progname> is omitted, control transfers to the Monitor, but no program is loaded.

<parameters> are the normal parameters of the program to be executed.

A starting address (entry point address) and up to two breakpoint addresses can be specified in the Monitor's G command (see chapter 6). When execution of your program is suspended at the breakpoint address, you can use Monitor commands to inspect and/or change the contents of memory and/or registers and then continue program execution from the point of suspension with another G command.

If an ISIS-II error occurs after control has been passed to the Monitor, any attempt to resume execution with a G command may cause unpredictable results, possibly overwriting ISIS-II or causing spurious input/output to the disk. It is acceptable to examine memory and/or registers to debug an error, but it is not wise to restart the program until control has been returned to ISIS-II.

You can return to ISIS-II from the debug mode and reset the debug toggle in one of the following ways:

- Enter Monitor command G8.
- Execute an EXIT system call in the program being debugged.
- Press Interrupt 1.

Example 1: This example shows how to execute a program named LIST in debug mode. The source of LIST is not shown, but its load address is 3680H.

```
-DEBUG LIST FILE.TXT
#3680
.G
(The LIST program is executed.)
```

3-23

-FORMAT F	1 IS00AS	SYS S	·	
COPYING SYS	STEM FILE	ES		ł
ISIS TO				
ISIS BIN	rî -	1 - Fi - A	to Other a state	11 '_
ISIS CLI	1	· · ·	NOM W	1 +e e
ASM80	⊭rt	, 11 [,]	it is the br	*
ASM80 OV0				
ASM80 OV1				
ASM80 OV2			LOP	
ASM80 OV3		6		
ASM80 OV4		ښد∨∙ د ځيند. د)2 EFCLE ≥E 25027310 Er = Fr	3
ASXREF		Ю		
ATTRIB	• 1	~ •		
BINOBJ			Provide Contraction and Bessier	و" و ز
COPY				
DELETE				
DIR		ň	ો∋કા, ∗ હતાણ ક્રા	121 121 1
EDIT		ĩ	nt ta a company	1 8.1
FIXMAP				
FORMAT	۰, ۲	1464 11.962	1 Jun of All Solar	acv ce >< >
HDCOPY	1	53 I J S	A ALIENCOPE - L	40.0.014
HEXOBJ				Clatter
IDISK				
LIB			at Tub fa	, i N
	1 ⁶ (1	6.05	الجهاو الأرام المراجع المراجع	A COPICY 11
LOCATE	** •	, <u> </u>	b Jum in in in	•• ••
OBJHEX			* 1,}*	2 UN0143
RENAME				
SURWII	+J	,	for the Part of the second	to a set to
	11	•	and states and the	•
	* 1	ŧ	alle i travent t	*
STRIEM LIB				

Example 1: This example shows the creation of a duplicate system disk excluding any non-system files on that disk.

Example 2: This example formats a basic non-system disk on drive :F1:, giving it the name of LIB.V1. System files are not copied.

-FORMAT F1 LIB V1	sur ob s i i	۱	Q;	ι	171
NON-SYSTEM DISK					
					4 4

Example 3: This example formats a hard disk in drive :F0: as a system disk; the files with the system or format attribute set are copied from a system disk in :F4:.

- F4 FORMAT F0 SYSTEM DSK S FROM 4

1100 × + 4/141

FIXMAP - Map Bad Sectors on Hard Disk

Various hardware and software problems can cause a sector on a disk to become bad, or unreliable The FORMAT and IDISK commands in ISIS-II recognize bad sectors and record the numbers of those sectors to prevent their allocation to files Fatal errors and disk errors arising during the HDCOPY procedure can also show that sectors are bad; either of the following messages reports that track 137, sector 106 on drive 1 is bad:

STATUS=000F D=1 T=137 S=106 DISK ERROR—UNABLE TO WRITE TO DESTINATION DISK ON DRIVE 1 LOGICAL ADDRESS (137, 106), STATUS=000F ¢

1

There are two files that SUBMIT uses. One contains the command sequence definition and is created by you with formal parameters. The other contains the command sequence to be executed and is created by SUBMIT with actual parameters instead of formal parameters. The command sequence file has the same name as the command sequence definition file but with the extension CS. The command sequence file should not be modified by the user.

SUBMIT reassigns the console input device to the command sequence file it has created and returns control to ISIS-II, which then executes the commands in the command sequence file. The last command in the command sequence file is a special SUBMIT command (provided automatically by SUBMIT) that restores the console input device to its former device assignment and deletes the command sequence file.

Formal parameters are specified in the command sequence definition by two characters, %n, where n is a digit from 0 through 9. They may appear anywhere in the command sequence definition. The literal character, control-P (†P), can precede a percent sign (%) that is not to be interpreted as a formal parameter.

Any program that reads its commands from :Cl: can be executed noninteractively. The command sequence definition file can also contain commands to the programs being run. If a SUBMIT command is used in a command sequence definition file, it causes another command sequence file to be created. This 'nesting' of SUBMIT commands can be repeated to any depth.

A control/E in a SUBMIT Switches the console input from the command sequence file to the initial system console, allowing interactive processing. A \uparrow E entered at the initial system console returns control to the command sequence file. If control is not returned to the command sequence file, or if an error occurs after a command sequence has started processing, control returns to ISIS-II and the CS file is not deleted.

Any program running under SUBMIT must allow for one buffer in addition to the open files and buffers required by the program itself. See Chapter 4 for information on how to determine the base address of your program.

Any program running under SUBMIT should not contain a CONSOL system call which changes the name of the console input device.

Example 1: The following examples show a PL/M compilation executed noninteractively on a 4-drive system. The PLM80 command has only three items that change. Using SUBMIT to enter the command automates the process, saving you keystrokes at the console.

The command sequence definition is in the file PLM80.CSD. See the compiler operator's manual listed in the preface for an explanation of the controls in the PLM80 command. The file PLM80.CSD contains the following:

PLM80 :F1:%0 %1 DEBUG XREF PRINT (F3:%0.LST) DATE(%2)

This command sequence definition contains three formal parameters, indicated by %0, %1, and %2. The SUBMIT command used to start the compilation is as follows:

SUBMIT PLM80(PROGA, SRC, '9 SEPT 78')

The command sequence created by SUBMIT and then executed is as follows:

—PLM80 :F1:PROGA.SRC DEBUG XREF PRINT (:F3:PROGA.LST) DATE(9 SEPT 78)

ISIS-II PL/M-80 COMPILER, V3.1

2 y 51 - K

PL/M-80 COMPILATION COMPLETE 0 PROGRAM ERROR(S)

11

-: F0: SUBMIT RESTORE PLM80.CS(:VI:) ۱, 1115 St. 35

102

. ?

If the T switch is present, the <sector> number specifies a group of 36 sectors on <track>:

If <sector> is in the range 1-36, that group of sectors is processed.

If <sector> is in the range 37-72, that group of sectors is processed.

If <sector> is in the range 73-108, that group of sectors is processed.

If <sector> is in the range 109-144, that group of sectors is processed.

Track and sector numbers, and the T switch, if present, should be separated by spaces. The track and sector numbers should be those reported in the error message that identified the bad sector.

Mark Command. The Mark command changes the known state of a sector from good to bad.

The syntax of the Mark command is:

MARK <disk address>

where:

<disk address> is the track-and-sector address of the sector to be marked as bad.

If the T switch is present, a group of 36 sectors is marked as bad. A sector known to be bad is not allocated to any file.

If the sector specified in the Mark command is not associated with an existing file, the sector is marked as bad. If the T switch is not present, the system displays:

SECTOR MARKED

If the T switch is present, no message appears when a single sector is marked; instead, when all 36 sectors have been processed, the system displays the message:

TRACK PROCESSED

If the sector belongs to an existing file, it cannot be marked as bad. Under any of the following conditions, the sector is not marked:

If the sector belongs to one of the required ISIS-II format files, the system displays:

(track, sector) REQUIRED BY ISIS-II

The system will be unreliable when the questionable disk is in use. You should format a new hard disk and copy your program and data files onto it.

If the sector is already known to be bad, marking the sector is redundant. The system displays:

(track, sector) ALREADY MARKED

If the sector belongs to a file other than a required format file, the system displays:

(track, sector) IN USE

. . •

as the

where

F

<file> is the file or group of files (specified with the wild card construction) whose directory entry is to be listed. If FOR <file> is omitted, the entire directory is listed. If <file> is not a wild card name (that is, does not contain * or ?) it is listed even if it has the invisible attribute.

stfile> is the name of the file to contain the directory listing. If TO <listfile> is omitted, the listing is sent to the console output device.

<switch> can be one or more of the following:

 \mathcal{M}

- 0-9 Lists the directory of the disk in :F0:, :F1:, :F2:, ... :F9:. If omitted, the directory of the disk in :F0: is listed. More than one drive number can be specified but only the rightmost one has effect. The drive number also overrides any device specification in FOR <file>.
- I Lists all files, including files with the invisible attribute set. If omitted, only files with invisible attribute not set are listed.
 - Gives fast output, listing only name.ext of files.
- O Prints directory in a single column format. The default is double column format.
- Z Prints the number of sectors presently used on the specified disk as a fraction of the number of available sectors.

P After loading the command, the system pauses with the message:

LOAD SOURCE DISK, TYPE (CR)

After the disk is loaded and CR pressed, the requested directory is output to the console output device. The system will then request that the system disk be replaced:

The DIR default is the directory output in two columns with the following headings:

	DIRECTOR	Y OF name	ext					-	٠	
	NAME	EXT	BLKS	LENGTH	ATTR	NAME	EXT	BLKS	LENGT	H ATTR
	PROGA	HEX	75	9263	w	SUMS		51	6357	
						126				
	936/2002 BI	LOCKS USE	ED		-	't	35 L	2#21+11	J	۰ ۲
						<u>،</u> ،	1.51	r ord	5.15	
wh	ara					4	0.1		. 47) g,
** 111	UI U	L				• 7 1	· i	۰,	. • 4	

name.ext is the label of the disk volume that is assigned by the FORMAT or IDISK command. It has the same syntax as a filename. Each item listed by DIR is explained in the section "Disk Directory Content" in this chapter. The directory listing shows the number of blocks in use and the total number of blocks within the disk (2002, 4004, or 28800).

611822

Under either of the following conditions, the sector is not freed:

If a sector is already free for allocation, freeing the sector is redundant. The system displays:

(track, sector) ALREADY FREE

If the sector is not free because it is in use by a file, the system displays:

(track, sector) NOT A BAD SECTOR

There is no reason to free a good sector that is part of an existing file.

Example 2: The following example illustrates the use of the Free command. Note that 8 5 T and 8 10 T identify the same group of 36 sectors, i.e., sectors 1-36 on track 8.

*FREE 180 51 SECTOR FREED *MARK 8 5 T TRACK PROCESSED *FREE 8 10 SECTOR FREED *FREE 8 10 T (8, 10) ALREADY FREE TRACK PROCESSED

List Command. The List command writes a list of all known bad sectors on the named file.

The syntax of the List command is:

LIST [<filename>]

where:

[<filename>] is an optional parameter specifying the listing file.

The listing file may be either an output device or a disk file. It may not reside on the disk being fixed. If no filename is given, the list is printed on the console.

The format of the output is one sector per line, with track and sector numbers separated by a comma. The list includes all sectors marked by FIXMAP, as well as bad sectors found by IDISK and Format.

If there are no known bad sectors, the system displays:

NO BAD SECTORS

If output is directed to a device other than the console, the following message is displayed after the list is written to the device:

ł

LIST WRITTEN

If the named file resides on the disk being fixed, the system displays:

CANNOT LIST TO TARGET DRIVE

results in prompts to swap disks in drive :F0:. But the commands:

COPY ABC TO .F1 ABC

and

COPY ABC TO DEF

do not result in prompts for disk swapping. You can also copy files between different disks on the same drive by specifying the P (pause) switch in the command.

Ŧ

When you punch a file on paper tape, a string of nulls is added to the file. If the punched file is then read back into the system and compared to the original, the nulls will cause a false compare. These nulls may be stripped from the file with the ISIS-II Text Editor or the CREDIT CRT-Based Text Editor. Object files should be converted to hexadecimal format before punching on paper tape.

The syntax of the COPY command is:

ş *

COPY <infile1>[,<infile2>,...,<infilen>] TO <outfile>[<switches>]

where

<infile> is a file on any device capable of input. The contents of <infile> are not affected by the copy. If more than one <infile> is specified, they are concatenated in the order specified when copied to <outfile>. When concatenating files, you must specify the full name and extension of each file.

Wildcard designations may not be used when concatenating files. The following example gives the error message that will be encountered if this is done.

COPY A, BC.* TO D WILDCARD DELIMITERS DURING CONCATENATE

. *, 1

ر -

When using the concatenate operation, the destination file name cannot be equal to any source file name. The following example indicates the error message which results if this is attempted.

COPY A,B TO B SOURCE FILE EQUALS OUTPUT FILE ERROR

<outfile> is the name of the file to be created or recreated or the name of an
output device. <outfile> is specified in the form :device:name.extension.
:device: is any system device. If :device: is omitted, and a filename is specified,
:device: defaults to :F0:. If :device: is not a disk drive, name and extension are
ignored. If <outfile> is an existing disk file and is not write protected, the
following message appears on the console:

<outfile> FILE ALREADY EXISTS DELETE?

If you respond to the message with 'yes' or just 'y' (followed by a carriage return), COPY deletes the existing file before making the copy. No action is performed if any other response is given.

If <outfile> is write protected, then the following message is output:

<outfile>, WRITE PROTECTED

If no sector has been marked or freed during the work session-or since the last Record command—the system displays:

NO CHANGES

Example 5: The following example illustrates the use of the Record command.

*RECORD CHANGES RECORDED *RECORD NO CHANGES

Quit Command. The Quit command stops the operation of FIXMAP and returns to ISIS-II.

The syntax of the Quit command is:

QUIT

If the Record command has not been given, changes specified by Mark and Free are not recorded on the disk.

Example 6: The following example illustrates the use of the Quit command. Note that the freeing of sector 12, 86 is not recorded on the disk; therefore, upon reentry to FIXMAP, that sector is still known as bad.

*FREE 12 86
SECTOR FREED
*QUIT
-FIXMAP 1
ISIS-II MAP FIXER Vx.y
*LIST
12, 86

,

Exit Command. The Exit command records changes and returns to ISIS-II.

The syntax of the Exit command is:

EXIT

180 3 3 ÷ 4.7

- 2

• • • •

451 . 1

5 -

The Exit command is equivalent to the Record command followed by the Quit command: changes specified by Mark and Free are recorded on the disk, and control returns to ISIS-II.

• • , ti Example 7: The following example illustrates the use of the Exit command. (Compare this example with Example 6, above.)

					· ·	1.3 . M .	(
*FREE 12 86		-					ز
SECTOR FREED	•	*	, t.,	۲			
*EXIT		1 119		•		-	
CHANGES RECORDED						,	,
-FIXMAP 1							
ISIS-II MAP FIXER Vx.y	•		•			ł	
*LIST							
NO BAD SECTORS					~	*415	

P P is the pause switch, which allows files to be copied between two disks on the same drive. The system prompts for disk swaps with the following messages:

> LOAD SOURCE DISK THEN TYPE (CR) LOAD OUTPUT DISK THEN TYPE (CR) LOAD SYSTEM DISK THEN TYPE (CR)

- Q Is the query switch, which causes the system to display the following message before a copy is performed: COPY <infile> TO <outfile>? A yes or y response causes the copy to be performed. Any other response causes the copy not to be performed.
- C C is the attribute switch, which causes <outfile> to be created with the same attributes as <infile> If this switch is not specified, <outfile> is created with all attributes reset (off). This switch does not copy the format (F) attribute.
- B B is the brief switch, which causes an existing file to be deleted without displaying the "ALREADY EXISTS" prompt. The existing file is deleted and recreated with new data unless the U switch is also specified, in which case, the existing file is overwritten. This switch can significantly improve performance, and should be used, even if it is known that the destination file does not exist.

Example 1: This example copies three files to one, overwriting its contents.

-COPY CHAP1 CHAP2, CHAP3 TO BOOK F0 BOOK FILE ALREADY EXISTS DELETE? Y APPENDED F0 CHAP1 TO F0 BOOK APPENDED F0 CHAP2 TO F0 BOOK APPENDED F0 CHAP3 TO F0 BOOK

Example 2: Example 1 could have been done in the following way.

-COPY CHAP1, CHAP2 CHAP3 TO BOOK U APPENDED F0 CHAP1 TO F0 BOOK APPENDED F0 CHAP2 TO F0 BOOK APPENDED F0 CHAP3 TO F0 BOOK

Example 3: This example lists a file on the line printer.

```
-COPY BOOK TO LP
COPIED F0 BOOK TO LP
```

Example 4. This example displays a file on the console output device.

```
--COPY CHAP1 TO CO
(text of CHAP1)
COPIED F0 CHAP1 TO CO
```

Example 5. This example copies a file from the disk in :F0: to the disk in :F1:.

---COPY PROGATO F1 NEWPRG B COPIED F0 PROGATO F1 NEWPRG

Charles I 1

?"

٠'2

(1. 16) 1

*FREE 170 113 T (170, 109) ALREADY FREE (170, 110) ALREADY FREE (170, 111) ALREADY FREE (170, 112) ALREADY FREE (170, 121) ALREADY FREE (170, 122) ALREADY FREE (170, 123) ALREADY FREE (170 124) ALREADY FREE (170 125) ALREADY FREE (170 126) ALREADY FREE (170 127) ALREADY FREE (170 128) ALREADY FREE (170 129) ALREADY FREE (170 130) ALREADY FREE (170, 131) ALREADY FREE (170, 132) ALREADY FREE (170, 133) ALREADY FREE (170, 134) ALREADY FREE (170, 135) ALREADY FREE (170, 136) ALREADY FREE (170, 137) ALREADY FREE (170, 138) ALREADY FREE (170, 139) ALREADY FREE (170, 140) ALREADY FREE (170, 141) ALREADY FREE (170, 142) ALREADY FREE (170 143) ALREADY FREE (170 144) ALREADY FREE TRACK PROCESSED *MARK 170 113 SECTOR MARKED *LIST 170, 113 *COUNT 1 BAD SECTOR *RECORD CHANGES RECORDED *FREE 170 113 SECTOR FREED *LIST NO BAD SECTORS *EXIT CHANGES RECORDED

Program Execution Commands

You can call a program for direct execution in which case you must respond to any queries from the program and to any errors encountered during program execution You can also call for execution of the program under the Monitor in which case the debugging provisions of the Monitor aid you in identifying and locating program errors. A third method is to submit the program as a job to be handled by the system without any interaction on your part. In this latter case you must prepare a file that interacts with the program in the same manner as you would during direct execution of the program.

τ,

If a disk error is detected while reading from the source hard disk, the message

DISK ERROR—UNABLE TO READ FROM SOURCE DISK ON DRIVE M LOGICAL ADDRESS (ttt, sss), STATUS = nnnn

appears on the console device, and a sector of 0FFH is written to the destination disk. If an error is detected when reading from or writing to the destination disk, the message

DISK ERROR—UNABLE TO WRITE TO DESTINATION DISK ON DRIVE N LOGICAL ADDRESS (ttt, sss), STATUS = nnnn

appears on the console device. In both cases, processing continues. You must decide whether or not to use the destination disk or to attempt to make a new copy.

In these error messages, ttt is the logical track address (in decimal); sss is the logical sector address (in decimal); and nnnn is the hard disk error status (in hexadecimal) as described in Appendix C.

As each track is copied to the destination disk, a "T" is printed on the console device. If no errors have been detected during a copy operation, the message

VERIFICATION OK

appears on the console device when the operation concludes. If errors have been detected, the message

BAD SECTORS ENCOUNTERED

appears on the console device.

Example 1: A sample HDCOPY command:

-HDCOPY 1 TO 0

LOAD DISK(S), THEN TYPE (CR)

DRIVE 1 DISK NAME MYDISK.123 COPIED TO DRIVE 0 VERIFICATION OK HARD DISK COPY COMPLETED *Example 2*: This example executes the same program in debug mode, suspends execution at the specified breakpoint address and then returns to ISIS-II with a G8 command instead of letting the program issue an EXIT system call.

—DEBUG LIST FILE TXT #3680	· 1 ·						۰. 	<u>بر</u>
G,-36A0 (Use Monitor command 36A0 is reached.) G8	s to exam	iine register	s and r	nemory	whe	en the l	oreakp	oint
ISIS-II, Vm n —		<u>ج</u> •	-na - { t	. ₹ ₹	•	، د ۲	-) <u>;</u>	۰,

Example 3 : This example allows you to transfer to Monitor control with no program loaded. Return to ISIS-II is by the Monitor G command with no address.

-DEBUG	•	
#0008		ŧ ,

SUBMIT - Non-Interactive Program Execution

The SUBMIT command causes ISIS-II to take its commands from a disk file rather than the console. Before using SUBMIT you create a command sequence definition file with optional formal (or symbolic) parameters. SUBMIT replaces these formal parameters with actual values that you specify in the SUBMIT command. The command sequence definition file thus establishes the order in which the commands are executed, whereas the SUBMIT command determines precisely what command syntax and constants are to be employed.

The syntax of the SUBMIT command is:

SUBMIT <name>[.<extension>][(<parameter0>,<parameter1>,...,<parameter9>)]

where

<name>[.<extension>] specifies the file containing the command sequence definition. If extension is omitted, SUBMIT assumes the file <name>.CSD. The command sequence definition, which must be in a disk file, is the command sequence with formal parameters, that are explained below.

<parametern> specifies the actual values that are to replace the formal parameters in the command sequence definition. The maximum number of parameters is 10. If a parameter is omitted from the SUBMIT list, its position must be indicated by a comma. A parameter is a character string of 31 characters maximum. Any ASCII character from 20H to 7AH is legal, except a comma, space, or right parenthesis. If a parameter contains a comma, space, or right parenthesis, the parameter must be enclosed in quotation marks. To use a quotation mark inside a quoted parameter, use two quotation marks in its place. For example:

'TITLE(''QUOTE ('') SEARCH ROUTINE'')'

a construction of the second sec

< 1,50 × 5 8 + 5

......

· • •

is used in the final command as:

TITLE('QUOTE (') SEARCH ROUTINE')

3-24

Ł

If the file cannot be deleted because it has the write-protect or format attributes set, the following message is sent to the console.

filename, WRITE PROTECTED

Each file name specified in the DELETE command may be followed by a space and a Q in which case the user is asked to confirm the file deletion. This query mode operation is most useful when the wild card construction is employed. You will then receive the following message for each of the files where name conforms to the wild card construct:

filename, DELETE?

Type a Y or y for a positive answer. Any other response causes DELETE to go on to the next file in the group without deleting the specified file.

If you delete files from a disk other than the system disk in a single drive system, you can specify the P (for pause) switch with the command. Before the deletion is performed, the system displays:

LOAD SOURCE DISK, THEN TYPE (CR)

When the deletion is completed, the following message is displayed:

:Fn: <filename>, DELETED LOAD SYSTEM DISK, THEN TYPE (CR)

Example 1: This example deletes three files.

-DELETE CHAP?.* :F0:CHAP1.TXT, DELETED :F0:CHAP2.LST, DELETED :F0:CHAP3.SRC, DELETED

Example 2: This example shows an attempt to delete a write-protected file.

```
-DELETE PROGA.ASM
:F0:PROGA.ASM, WRITE PROTECTED
```

Example 3: This example shows the deletion of a file using the P switch.

-DELETE PROGB.ASM P LOAD SOURCE DISK, THEN TYPE (CR) :F0:PROGB.ASM, DELETED LOAD SYSTEM DISK, THEN TYPE (CR) *Example 2*: This example shows a PL/M compilation, a LINK, and a LOCATE executed from a SUBMIT file on a 2 flexible disk drive system. A \uparrow E is entered in the command sequence definition after the PL/M compilation so the compiler disk can be removed. The operator enters a \uparrow E when the regular system disk (with LINK and LOCATE) is mounted and processing can continue. The text editor does not echo the \uparrow E; however, it is echoed when the SUBMIT file is executed.

The file CMPLNK.CSD in drive 1 contains the following command sequence definition:

PLM80 %0.%1 DEBUG XREF DATE(%2) tE		す。1月16日) 19月2日
LINK %0.OBJ,SYSTEM.LIB TO %0.SAT& PRINT(%0.LNK) MAP	ŕ	t http://www.com/
LOCATE %0.SAT PRINT(%0.LOC) MAP		

The SUBMIT command entered to compile, link, and locate PROGA.SRC follows:

SUBMIT :F1:CMPLNK (:F1:PROGA,SRC, '3 OCT 78')

The command sequence actually executed is shown as it would be echoed on the console output device:



The file control commands are those commands that work directly with files and are not concerned with the type of information within the files. This is in contrast with the other ISIS-II console commands that initialize new disks or deal with program files specifically.

The file control commands provide for copying or deletion of files and revision or display of file directory contents. Familiarization with the file control commands is equivalent to learning a primary function of ISIS-II.

11 0

11 -

DIR - Disk Directory Listing

The DIR command lists one or more directory entries of the disk in a specific drive, sending the list to the console output device or to a list file. The syntax of the DIR command is:

DIR [FOR <file>][TO <listfile>][<switch>]

The positions of these fields are not fixed.

¢.

ATTRIB - Change/Display Disk File Attributes

The ATTRIB command changes and/or displays the specified attributes of a disk file. The syntax of the ATTRIB command is:

ATTRIB <file> [<attriblist>] [Q]

where

<file> is a disk file whose attributes are to be changed. The wild card construction can be used to change and/or display the attributes of a group of files.

<attriblist> is one or more of the following:

- 10 or 11 Reset or set the invisible attribute. When set, the file is not listed by the DIR command unless the 1 switch is specified in the DIR command.
- W0 or W1 Reset or set the write-protect attribute. When set, the file cannot be opened for output or update, and cannot be deleted or renamed.
- F0 or F1 Reset or set the format attribute. When set, the file is copied to the disk being formatted by the IDISK and FOR-MAT commands. Removal of the format attribute from system files will cause improper formatting of new system disks. This attribute is reserved for specific system files and should not be assigned to any other file.
- S0 or S1 Reset or set the system attribute. When set, the file is copied to the disk being formatted by the FORMAT command when the S switch is used. This file is also copied by the COPY command when the S switch and wild card notation are used.

If two values of the same attribute are specified, for example both I0 and I1, the one rightmost in the command takes precedence.

Q requests query mode operation. Before changing the attributes of a file, ATTRIB sends the following message to the console:

filename, MODIFY ATTRIBUTES?

Type a 'yes' or just 'y' if you want the file attributes modified. Any other response causes ATTRIB to leave the attributes unchanged for the specified file and to go on to the next file in the group.

If a nonexistent disk file is specified, ATTRIB responds with a message on the console:

filename, NO SUCH FILE

If a non-disk file is specified, ATTRIB responds with a message on the console:

filename, NON-DISK DEVICE

where filename is that specified in the command. When attributes for a file have been changed, the current attributes for the file are displayed on the console.

Example 1 :

The following example lists two files of a flexible disk on a single density system. The system files, which have the invisible attribute set, are not listed.

—DIR							ş
DIRECTOR	Y OF FO IS	DOAB SYS	3		1.		
NAME	EXT	BLKS	LENGTH	ATTR	NAME	EXT	BLKS LENGTH ATTR
PROGA	HEX	75	9263	W	SUMS		51 6357
					126	È.	
936/2002 BL	OCKS USE	D				٠	

Example 2 : This is the same as Example 1 except a fast listing is requested.

-DIR F DIRECTORY OF 'F0'IS00AB.SYS PROGA HEX SUMS 936/2002 BLOCKS USED

Example 3 : This example requests a directory listing of all format files be sent to the line printer. The format files have the invisible attribute and ISIS.* is a wild card filename, so the I switch must be specified.

-DIR | FOR ISIS * TO LP

Example 4 : A single-column fast directory listing of the double density flexible disk in drive :F1: is requested by the following command.

--DIR 1 F O DIRECTORY OF DISK :F1 ISIS V10 TYPE M80 TYPE HEX TYPE 1337/4004 BLOCKS USED

COPY - Copy a File

The COPY command copies the contents of a file into another file. The source and destination can be disk files or physical devices. The file from which the copy is made must be an input device and file to which the copy is directed must be an output device. For example, you can copy from the reader to the punch but not from the punch to the reader.

When the source or target is a disk file, the filename must be specified or implied. When the source or target is a physical device, only the device designation need be specified.

Wild card characters can be used in disk filenames. However, the wild card characters cannot be used in device designations (you cannot specify :F*:).

The COPY command supports single disk drive systems. You can copy files from one disk to another using only a single drive. The command prompts for the source, output, and system disks as it needs them. If you specify a copy on a drive with no change in file name, the command assumes you want to swap disks and prompts for the swaps. For example, the command:

.

11.1 1

COPY ABC TO ABC

Code Conversion Commands

The code conversion commands exist for two reasons:

• To provide compatibility with systems employing hexadecimal object file format.

2

To convert programs created under previous versions of ISIS.

The programs called by the code conversion commands convert the character coding of these disk files but do not otherwise alter the information of the original programs. The program files of ISIS-I were created on single density disks and must therefore be input via a single density drive.

HEXOBJ - Convert Hexadecimal Code to Absolute Object Code

The HEXOBJ command converts object code in hexadecimal format to an absolute object module compatible with ISIS-II. The hexadecimal format is produced by cross-product translators that run on large machines and by assemblers of earlier versions of ISIS. The format of the HEXOBJ command is:

HEXOBJ <hexfile> TO <absfile>[START(addr)]

where

<hexfile> is a file of machine object code in hexadecimal format.

<absfile> is the output file from HEXOBJ containing the absolute object module that can be loaded for execution under ISIS-II. The module name stored with the object module is the same as the name part of the <absfile> filename. The absolute object module produced by HEXOBJ contains a symbol table if symbols were defined.

START(addr) is used to include a starting address (the address of the first instruction to be executed) in the absolute object module. The address can be specified by a hexadecimal, decimal, octal, or binary number followed by a letter indicating the base. The letter is H for hexadecimal, O or Q for octal, B for binary, D or omitted for decimal. Thus the address 4000 hexadecimal is specified as START(4000H).

If START(addr) is omitted, the starting address is taken from the end-of-file record of the hexadecimal format file, which is determined by the END assembly language statement.

If no starting address is specified in any of the above ways, zero is assumed, which is in the ISIS-II area and causes an error 15 on any attempt to load the file.

Example 1 : In this example a hexadecimal format object file on paper tape is converted to an absolute object file on disk.

-HEXOBJ :HR: TO SUMS

Example 2: This example converts a hex file to absolute object format, recording a starting address in the object module.

-HEXOBJ PRIME.HEX TO PRIME.OBJ START(3200H)

14.

Wildcard designations can be used in <outfile> only to the extent they are used in <infile>. That is, they must follow these rules:

- Every position in the <infile> name that contains an * must have a corresponding * in the <outfile> name.
- Every position in the <infile> name that contains a ? must have corresponding ? or * in the <outfile> name.

The COPY command provides a special case for convenience. When copying disk files to a different disk, you can specify as <outfile> a device designation without a filename. In this case, <outfile> will have the same name as <infile>. For example:

COPY .F1:ABC.XYZ TO F2:	<u>م</u> تر ب		
is the same as specifying:	4812 (* 1. 1. 1. 1. 1. 1868 1. 50 - 1. 1.	, _{1,1}	and the form
COPY :F1:ABC.XYZ TO :F2:ABC.XYZ	121.1	. •	2.211 1109
This form can be used with wildcard de	signations in <infile></infile>	: .	TSPC 12 m 3
COPY 'F1 *.* TO :F2:	۲. ۲	5 K.	17
At the end of the listing of files that wer	e copied the message	;	•

WRITE PROTECTED FILE ENCOUNTERED

If the rules governing wildcard designations are not followed, an error message will be displayed as shown by the example below.

-COPY ABC.* TO D	., •	,	•	e v *	۲Ĥ	′•	15 8 71
FILE MASK ERROR				· or	٠	~	5 <u>1</u>

COPY command switches allow you to limit wild card copies to system files or nonsystem files, copy attributes with the file, suppress messages when a file is to replace an existing file, and to receive a prompt that requires a yes response before a copy is performed.

<switches> are one or more of the following:

12

U U is the update switch, which if used causes the suppression of the "ALREADY EXISTS" message described earlier. <outfile> is opened for update instead of being deleted. The length is not changed unless the copy causes an increase in the size of the file. <outfile> has attributes unchanged unless C is specified, in which case the attributes of <outfile> will be the attributes set before the copy plus the attributes set in the file being copied from. For example, if file XYZ with the I attribute set is copied to the file ABC which has the S attribute set, the final file ABC will have the S and I attributes set.

S is the system switch, which causes only files with the system attribute to be copied. For example, the command:

COPY :F0:*.* TO :F1:*.* S

copies only files with the system attribute from drive :F0: to drive :F1:.

N N is the nonsystem switch and causes only files without the system or format attribute to be copied.

£

The type command lets you display your file on the Console output device.

The memory check command lets you determine how much space you have left in memory to add data.

e 750

Command Entry

When you are using the Editor, an asterisk (*) is displayed at the left margin when the Editor is ready to accept a command. If there is not an asterisk at the left margin either of two conditions exist; 1) you are inserting data with the Insert command in which case your command will be treated as data and entered into the file, or 2) the Editor is still processing the last command you entered.

The commands are all single letter commands and must be followed by two escape (ESC) or alternate mode (ALT MODE) characters, depending on the terminal you are using. In the command syntax statements, these characters are shown as two dollar signs (\$\$). Thus, a simple Editor command will look like:

*B\$\$

(This particular command moves the text pointer to the top of the file.)

Command Parameters

There are two types of parameters that can be included with Editor commands, iteration parameters and data parameters.

Iteration parameters specify how many times the command is to be performed. For example, the Type command (which is t) types one line. To type 10 lines, the command is:

*10T\$\$

The iteration parameter always comes before the command code. If it follows the command, it is ignored or assumed to be part of the following command in a string. (Command strings are described later.)

Data parameters specify the data on which the command is to operate. For example, the Substitute command (which is s) replaces one data string with another. To change the data string "CALL LP1" to "JMP ERRI," the command is:

*SCALL LP1\$JMP ERR1\$\$

The data parameter always comes after the command code. If it precedes the command, the Editor does not know what to do with it and may treat it as a command if the first letter is a valid command code.

The data parameter example also shows another use of the ESC or ALT MODE character, as a separator. It will be used, as shown above, to separate multiple data fields in a command and will be used to separate commands in a command string.

Aborting Commands

A command or command string can be aborted completely, before it is terminated (\$\$) by entering Control/C. Control/C is entered by pressing the letter c (upper or lower case) while the CTRL key is depressed.

Example 6: This example copies system files from one disk to another on drive :F0:

COPY * * TO * * P S					,	
LOAD SOURCE DISK, THEN TYPE (CR)						
LOAD OUTPUT DISK, THEN TYPE (CR)				•		
COPIED F0 ASM80 TO F0 ASM80	3 (t,		
•	* ***	31	-			

LOAD SYSTEM DISK, THEN TYPE (CR)

If the files to be copied are quite large (exceeding the size of the available RAM) the LOAD SOURCE and LOAD OUTPUT messages will be displayed more than once. As each file is copied, a COPIED message is displayed. After the last file is copied, the LOAD SYSTEM message is displayed.

Example 7: This example show valid uses of wildcard names with the COPY command:

COPY	F1 * * TO F2:	(copy all files except those with the FORMAT attribute)
COPY	F1 A??C TO F0 D??E	
COPY	F1 * * TO F3 N	(copy all non-system and non-format files)
COPY	F1 A????? TO F0 B* CPY	

HDCOPY - Copy Hard Disk Tracks

The HDCOPY command copies the contents of one hard disk to another hard disk on a track-by-track basis. The data transformed are verified during reading of the data into memory. HDCOPY formats the destination disk before writing data to it. The BACKUP switch can be used to backup a removable hard disk platter. The syntax of HDCOPY is:

NECODI (dama (S. TO (dama (S. IDAO)(NE		-	_ +i					
HDCOPY <anve 1="">10 <anve2>[BACKUP</anve2></anve>			,	- ^		ŧ		٩
and and the second s	-		3				ŧ	
wnere						*		-,*

<drivel> is the number of the drive containing the source hard disk.

<drive2> is the number of the drive containing the destination hard disk.

The drive numbers must be 0 or 1. The source and destination cannot be the same drive number, or a fatal error results, and an error message is displayed. If either <drive1> or <drive2> is not a hard disk drive, an error message is displayed:

s.t.

SPECIFIED DRIVES NOT HARD DISK

If you specify BACKUP, these actions occur:

- The contents of the disk in drive 1 are copied to the disk in drive 0
- ISIS-II prompts for the backup disk to be placed in drive 1
- The contents of the disk in drive 0 are copied to the disk in drive 1,
- ISIS-II prompts for a system disk to be placed in drive 1
- The contents of the disk in drive 1 are copied to the disk in drive 0

If drives 0 and 1 are not hard disk platters, an error message appears.

ε.

The syntax of the EDIT command is:	•	••		•.•	×r∔ i	bqr s	;
EDIT <filename1>[TO <filename2>]</filename2></filename1>	•	۰. ۱	, 10' <i>'</i>		1	オロシネッ	ŝ,
						1. 1	

where

<filename1> is either the name of a new file to be created and edited or the name of an existing file to be edited.

<filename2> is the name of the device or disk file to which the edited version of <filename1> is written.

If <filename1> is a disk file and <filename2> is not specified, the action taken by the Editor depends on whether <filename1> is a new or existing file. If it is new, it is created for output. If it exists and is not write-protected, it is opened for input. A temporary file, EDIT.TMP, is created for the output. When the session is ended with the Exit (E) command, the files are closed and <filename1> is renamed "name.BAK" and EDIT.TMP is renamed <filename1>.

If <filename1> is not a disk file, it must be an input file and <filename2> must be specified and must be a disk file. For example,

EDIT :HR: TO :F1:ASSY.SRC

reads the text from the high speed paper tape reader into the system in response to the Append (A) command. When the editing is complete, the contents of the file are written to a disk in drive :F1: with the name ASSY.SRC.

You can start entering data with the Insert (I) command or you can read an existing file from disk with the Append (A) command. The commands are described in the next section.

Editor Commands

· · ·

The Editor commands are all single character commands. Many can have iterative and/or data parameters. As you use the commands you will find that you often enter a series of commands one after the other. This takes a lot of extra key strokes (command terminators at the end of each command) and time.

You can enter multiple commands on the same line. When you do this the commands are executed one at a time from left to right, exactly the same way they are executed if you enter each on a separate line.

A single ESC or ALT MODE character can be used at any point between commands as a separator character. When data is included with a command you must separate the data from the next command with an ESC or ALT MODE character. If you don't, the Editor has no way of knowing when the data stops and the next command begins. Without the separator character, everything is considered data. The ESC or ALT MODE character is also used a separator between multiple data fields in a command.

The Text Pointer

The Editor keeps a pointer into the data in a file at all times. The pointer is always pointing between characters. When many of the Editor commands are issued, the action takes place from where the pointer is located. For example, the Type (T) command types the data from the pointer location to the end of a line. The Insert (I) command inserts data into a file at the pointer location.

Example 2: A sample HDCOPY command with the BACKUP switch:

-HDCOPY BACKUP LOAD DISK IN DRIVE 1, THEN TYPE (CR) DRIVE 1 DISK NAME MYDISK.123 IS SOURCE DISK DRIVE 0 DISK WILL BE OVER-WRITTEN OK TO CONTINUE? ۷ **DRIVE 1 DISK NAME MYDISK.123 COPIED TO DRIVE 0** LOAD BACKUP DISK IN DRIVE 1, THEN TYPE (CR) DRIVE 0 DISK NAME MYDISK, 123 IS SOURCE DISK **DRIVE 1 DISK WILL BE OVER-WRITTEN** OK TO CONTINUE? V DRIVE 0 DISK NAME MYDISK.123 COPIED TO DRIVE 1 LOAD SYSTEM DISK IN DRIVE 1, THEN TYPE (CR) DRIVE 1 DISK NAME IS00AT, SYS IS SOURCE DISK DRIVE 0 DISK WILL BE OVER-WRITTEN OK TO CONTINUE? ٧ DRIVE 1 DISK NAME IS00AT SYS COPIED TO DRIVE 0 VERIFICATION OK HARD DISK COPY COMPLETED

DELETE - Delete a Disk File

The DELETE command provides for erasure of specified directory entries. This command effectively removes the specified file or group of files from a disk, making the space it occupied available to ISIS-II for reassignment. A file with the write-protect or format attribute set cannot be deleted. The syntax of the DELETE command is:

DELETE <filename1>[Q][,<filename2>[Q]][,<filename3>[Q]][,...] [P]

where

<filename> is the name of a file to be deleted. The wild card construction can be used to delete a group of files.

If <filename> is a file with neither the write-protect nor format attribute set, the file is deleted and a confirming message is sent to the console.

If <filename> does not exist, the following message is sent to the console where <filename> is that specified in the DELETE command:

filename, NO SUCH FILE

Z Command Examples: To move the pointer to the end of the file:

*Z\$\$

When the pointer is at the end of the file, there is no data following it. If you issue a command such as Type (T), nothing is typed because there is no data to type.

L - Line Command

The L command moves the pointer before the first character of the next line in the file. You can specify an iterative parameter with the L command to move the pointer several lines. The parameter must precede the command code. You can move the pointer backwards, to the beginning of lines by entering a minus parameter. You can move the pointer to the beginning of the current line by entering a parameter of zero. If no parameter is included, 1 is assumed.

The format of the L command is:

[n]L\$\$

where:

n specifies the number of lines the pointer is to be moved. A positive n specifies a forward movement and a negative n specifies a backward movement. O specifies that the pointer be moved to the beginning of the current line. If n is omitted, 1 is assumed.

L is the command code.

L Command Examples: To move the pointer to the beginning of the next line:

*L\$\$

To move the pointer to the beginning of the line five lines back in the file:

*-5L\$\$

To move the pointer to the beginning of the current line:

*0L\$\$

To move the pointer ahead 12 lines:

*12L\$\$

C - Character Command

The C command moves the pointer a specified number of characters forward or backward in the file. You can specify an iterative parameter with the C command. The parameter must precede the command code. A positive number (an unsigned number is assumed to be positive) moves the pointer forward the specified number of characters. A minus number moves the pointer backward. If no parameter is included, 1 is assumed. The parameter can be any number from -65,535 to +65,534. If the beginning or end of the file is encountered before the specified number is reached, the pointer stops at the beginning or end.

RENAME - Rename a Disk File

The RENAME command changes the name of a disk file. Only the directory is affected. The syntax of the RENAME command is:

RENAME <oldname> TO <newname>

where

 <oldname> is the name of the existing file whose write-protect or format attribute is not set. If a nonexistent file is specified, an error occurs.

<newname> is the new name to be assigned to the file with <oldname>. An error occurs if the device part of the filename is not the same as that in <oldname>. If a file with <newname> already exists, this message appears on the console:

newname, ALREADY EXISTS, DELETE?

If you respond to the message with Y or y (followed by a carriage return), RENAME deletes the existing file before renaming. (If the existing file is write-protected, it is not deleted and the file to be renamed is not renamed.) No action is performed and control returns to ISIS-II if a response other than Y or y is given.

RENAME cannot be used on nonsystem disks on a single drive system. To change the name of a nonsystem disk file with only a single drive, use the COPY command to copy the file to a file with the new name, then delete the old file with the DELETE command.

Example 1: The following example changes the name of the file CHAP1.

-RENAME CHAP1 TO CHAP.ONE

-

Example 2: This example shows an attempt to rename a write-protected file.

-RENAME NEWPRG.TXT TO PROGA.TXT

NEWPRG TXT, WRITE PROTECTED

-

N.

Example 3: In this example, the new name is the name of an existent file.

-RENAME TEXT BAK TO TEXT.OLD

TEXT.OLD, ALREADY EXISTS, DELETE? Y

-

\$

1

F Command Examples: To find the character string "LOOP1" starting from the current location of the pointer:

*FLOOP1\$\$

<u>، را ا</u>

÷

To find the same character string but start the search from the beginning of the file:

*BFLOOP1\$\$

To find the same character string starting from the beginning of the file and then move the pointer to the beginning of the line containing the string:

*BFLOOP1\$0L\$\$

In the last example, if the ESC or ALT MODE character after the string had not been entered, the Editor would have searched for the string "LOOP10L" and would not have found it.

Text Commands

The Editor contains commands to enter new text into a file, change existing text, delete an entire line, and delete a single character.

All of these commands affect the pointer. The effect on the pointer is described in each command description.

I - Insert Command

The I command inserts text into the file immediately before the pointer. All data following the I command is inserted into the file until a command terminator is entered. This includes carriage returns and line feeds.

The pointer is always immediately following the inserted data.

٤.

During initial entry of data into a file, the I command normally goes on for many lines, possibly for the entry of an entire program.

The format of the I command is:

Itext\$\$

and the second sec

. .

٠.

٠,

where:

I is the command code.

text is the data to be entered. Any amount of text can be entered, from a single character to an entire file. The Editor keeps accepting data and inserting it into the file until the \$\$ is encountered.

I Command Examples: To enter a single character into the file where the pointer is located:

*IK\$\$

To enter a line to the beginning of the file:

*BIThis is the new line<CR> \$\$ *Example 1* : This example changes the write-protect attribute of a group of files:

-ATTRIB PROGA * W1			
FILE	CURRENT ATTRIBUTES	ι.	
:F0:PROGA SRC	W		
F0 PROGA OBJ	W		

Example 2 : This example sets the system attribute for the TYPE program so it will be transferred onto new system disks (see FORMAT command).

-ATTRIB TYPE S1	
FILE	CURRENT ATTRIBUTES
·F0:TYPE	S
-	« š ,

VERS—Display ISIS Utility Version Numbers

The VERS command displays the version number of user-specified ISIS command programs (e.g., DIR, ATTRIB, COPY, IDISK). The syntax of the VERS command is:

11

VERS [:Fn:]<filename>

where

<filename> is the name of the ISIS file on :Fn: whose version number is to be displayed.

The VERS command should be used to ensure that the version numbers of the ISIS command programs currently on your system are the same as (i.e., compatible with) the version number of the ISIS you signed on under.

Example 1: This example lists the version number of a compatible ISIS command program:

Bern Bry

2 (1) (1) 21

. . . .

· */

3

```
-VERS DELETE
V4.2
```

Example 2: This example lists the version number of an incompatible ISIS command (the basic operating system version number is 4.2):

~

```
---VERS EDIT
V4.1
```

Example 3: This example shows an attempt to list the version number of a non-ISIS file:

```
---VERS MYFILE EXT
FILE DOES NOT CONTAIN A PROGRAM VERSION NUMBER
```

Example 4: This example shows an attempt to list the version number of a file not in the directory of the target device:

-VERS NONFIL ERROR 13 USER PC 375B S Command Examples. To replace the string "JMP" with the string "CALL":

*SJMP\$CALL\$\$

To make the same substitution but start the search from the beginning of the file:

*BSJMP\$CALL\$\$

11. 4

To make the same substitution, searching from the beginning and then typing the entire line in which the change was make:

*BSJMP\$CALL\$0LT\$\$

To delete the first occurance of the string "START" from a file:

*SSTART\$\$

In the above example, no replacement data was supplied with the command. Thus, the command found the string and replaced it with nothing (deleted it).

1 G 🕴

18 -

7...

D - Delete Command

The D command deletes the number of characters, starting at the pointer, specified in the command. If the iterative parameter is positive (or unsigned) the deletions are done from the pointer forward. If the parameter is negative, the deletions are done from the pointer backward. If the deletion is performed in a forward direction in the file, the pointer immediately precedes the first character not deleted. If the deletion is performed in a backward direction, the pointer immediately follows the first character not deleted. In other words, the pointer is between the remaining characters on either side of the deletion.

The format of the D command is:

[n]D\$\$

where:

n specifies the number of characters to be deleted. If n is positive, the deletion is performed in a forward direction and if n is negative the deletion is performed in a backward direction from the pointer. If n is omitted, 1 is assumed.

D is the command code.

D Command Examples. To delete the next 10 characters following the current pointer location:

*10D\$\$

To delete the 10 characters preceding the current pointer location: $\frac{1}{2}$, $\frac{1}{2}$

*-10D\$\$

K - Kill Line Command

The K command deletes all the characters in a line beginning at the current location of the pointer. The characters in the line that precede the pointer are not deleted. The K commands also deletes the carriage return and line feed at the end of the line.

OBJHEX - Convert ISIS-II Absolute Object Code to Hexadecimal

The OBJHEX command converts an ISIS-II absolute object module to hexadecimal format.

The format of the OBJHEX command is:

OBJHEX <absfile> TO <hexfile>

where

<absfile> is the file containing an ISIS-II absolute object module.

<hexfile> is the file to contain the hexadecimal object code converted from the ISIS- 11 format. The starting address (address of first instruction to be executed) is taken from <absfile>. The hexadecimal object code produced by OBJHEX does not contain a symbol table.

Using The Text Editor

The ISIS-II Text Editor enables you to create and update ASCII text files. The Editor can be used to manipulate text on a line or character basis. One or more characters can be inserted in, deleted from, or changed in a line of text. Insertions and deletions can be made that cover one or more lines. The point of insertion or deletion can be freely selected to be at the beginning or end of the file, beginning or end of a line, or at any point within a line.

The ISIS text editor is a contextual editor. That is, it does not use line numbers but uses the context of the file for editing. For example, to insert some text before a line that contains "LXI QQ", you don't need a line number. You can find the line by issuing a Find command specifying the content of the line.

The usual procedure for creating a new text file is to call the editor, enter text from the system console, perform whatever editing functions are desired, and then output the file to a disk for storage. To edit an existing file, call the editor, input the file from a disk, edit the file, and output the modified version to the disk.

The Editor Functions

The Editor has 16 commands that allow full control over your text file. The commands are divided into the following categories:

- Commands to input and output data and terminate a session
- Commands to manipulate the text pointer
- Commands to modify the text
- Command to type the text
- Command to check available memory

The input, output, and session commands let you access a disk file, make changes, and save the results. You can also terminate a session without saving the work.

The text pointer manipulation commands let you move around in the file to make changes or insertions at the desired place. The text pointer is always pointing to some location in the file. Before you can make a change or insertion, you must move the pointer to where you want it. The text pointer is described in more detail later.

The text modification commands let you insert data, delete data, and change data.

Þ

where:

n specifies the number of lines to be displayed. If n is positive the display starts at the line pointer and proceeds forward in the file. If n is negative, the display starts n lines before the pointer and displays to the pointer. If n is zero, the display starts from the beginning of the current line and proceeds to the pointer. If n is omitted, 1 is assumed.

T is the command code.

T Command Examples. To display a line from the pointer through the end of the line:

	·1	st 💭	C
To display from the beginning of a line to the location of the pointer:	8876	• •	Į I
Received the studies of the studies	1.		5.1

*0T\$\$

*T\$\$

To display the entire line no matter where the pointer is located within the line:

*0TT\$\$

In the preceding example, the "0T" displays from the beginning of the line to the pointer and the second "T" displays from the pointer to the end of the line.

To move the pointer to the beginning of a line and then display the line:

busmais. J

*0LT\$\$

To display the previous line and move the pointer to the beginning of that line:

```
*-1LT$$ or just *-LT$$
```

MARCH N N

To display your entire file but you don't know how many lines are in it but know it can't be more than 500:

*B500T\$\$ When the end of the file is reached the command stops.

Terminating a Session and Saving Your File

There are two commands to exit the Editor and return to ISIS-II. One command saves your work from the editing session on disk and the other doesn't.

۰.	,	, es	,	,	-	,	×	- 11	4
			فہ	يد ا	2		r		tačija i k
A								710	u /1

+ ,

£....

E - Exit Command

The E command saves the entire contents of the file in memory on disk. If the file being edited is not completly read in from the disk, the E command saves the contents of the file in memory and then reads the remainder of the file from the disk and immediately writes it back to the disk. When the entire file is saved, the Editor returns control to ISIS-II. Control/C can also be used to stop execution of a command in progress. For example, if you entered a command to type 100 lines of the file when you meant to type 10 lines, you can stop the typing by entering Control/C. The typing will stop immediately, and the Editor will prompt for the next command.

Correcting Typing Errors

You can correct typing errors in command strings or text by pressing the RUBOUT key once for each character to be deleted and then retype the correct characters. As you press the RUBOUT key, the character that is deleted is displayed on the screen. You can only make corrections of this kind in commands before entering the command terminator (\$\$).

A line with several corrections made with the RUBOUT key is unreadable. You can type the line as really exists by entering Control/R. Control/R causes the system to type the whole line with the corrections made. For example:

Tilhoois aais a kkluuindde.

• (1

15 -

+ •

Control/R

This is a line.

When a line has so many errors that you want to start over, you can enter Control/X which cancels that entire line. When Control/X is entered, the system types a cross-hatch character (#) and starts at the beginning of the next line.

Formatting Characters

To make your source code listings usable, carriage returns and line feeds are essential and horizonal TABs are helpful.

Carriage Return and Line Feed Characters

When entering data at the system console device, it is not necessary to insert line feed characters. Each time the carriage return key is pressed, the system generates a line feed character and stores it in memory following the carriage return character.

When you use the RUBOUT key to delete a carriage return, you must rubout the carriage return and the line feed. That is, you must press the RUBOUT key twice.

TAB Characters

TAB characters make it easy to line up the columns of a source code listing. You can enter a TAB with Control/I. The TABs defined in the system are every eight character positions, 8, 16, 24, etc. When Control/I is entered the carriage advances to the next TAB position.

(If you are coding in PL/M, please note that PL/M interprets a TAB character as four spaces, not the eight shown on the screen during entry with the Editor.)

Activating The Editor

The Editor is activated with the ISIS-II EDIT command. The EDIT command cannot be executed from a SUBMIT file.

ت

Reading Data from Disk

The Editor provides a single command to read data from disk into memory.

131

A - Append Command

The A command reads a maximum of 50 lines of text from disk into memory. The text is appended to the bottom of the data already in memory (data that was read in with the A command or entered via the Editor commands).

2

The A command reads 50 lines of text or until:

- The end of the file is reached.
- An end-of-file character (Control/Z) is read. The Control/Z is not read into memory.
- The memory assigned to the Editor is full.
- A form feed character (Control/L) is read. The Control/L is read into memory.

If you have a large file to read into memory, you can issue repeated A comands. An iterative parameter is ignored for the A command.

The format of the A command is:

A\$\$

where:

A is the command code.

A Command Examples. To read 50 lines of text from disk into memory:

*A\$\$

To read 500 lines of text from disk into memory:

*AAAAAAAAAA\$\$

Please note that the command "10a" will only read 50 lines of text. The iterative parameter is ignored. (See the section "Command String Iterations" later in this chapter for an alternative way to specify multiple A commands.)

. E.

. t.

Determining Memory Space Available

The Editor has a command to determine how much memory space is still available for text entry.

· · · · · ·

1 1, " ..

त्र भ

M - Memory Command

The M command computes and displays on the system Console output device, the number of bytes of memory still available. The information is supplied in the following message:

nnnn-CHARACTER(S) AVAILABLE IN WORKSPACE

where nnnn is a decimal integer.

To update a file you must be able to move the pointer in the file. The Editor has five pointer manipulation commands:

- Beginning of Text (B) which moves the pointer before the first character in the file.
- End of Text (Z) which moves the pointer after the last character in the file.
- Line (L) which moves the pointer before the first character in a line.
- Character (C) which moves the pointer one character in the file.
- Find (F) which moves the pointer after the last character of a data string supplied in the command.

B - Beginning of Text Command

The B command moves the pointer before the first character in the file. When you read a file, the pointer starts at this position.

The B command is useful to:

- Move the pointer to the beginning to type a whole file.
- Establish a starting point when searching a whole file to find a certain character string.
- Inserting text before the existing text.

The format of the B command is:

B\$\$

where:

B is the command code.

B Command Examples: To move the pointer to the beginning of a file:

*B\$\$

If you want to type the first line, you can add the Type (T) command (described later) to the B command:

*BT\$\$

The pointer is moved to the beginning and the first line is typed on the Console output device.

Z - End of Text Command

The Z command moves the pointer immediately following the last character in the file. The Z command is useful to add text to the end of a file.

The format of the Z command is:

しかかい キャン・マント

Z\$\$

where:

Z is the command code.

Þ

ځ

Command string iterations can be nested. For example, the command:

*100<3C2>5CD<L>\$\$

will go through a 100 line file. On each line it will advance the pointer 3 characters and then, twice, it will advance five more characters and delete a character. The inner string advances the pointer five characters and deletes the sixth character. The outer string advances the pointer three characters before executing the inner command string and then advances the pointer to the next line.

Iteration command strings can be nested eight deep. If more than eight strings are nested, the following error message is issued and the command is not executed:

•

ITERATION STACK FAULT *BREAK*

19 1 1 2

12

1 1 1

1 - 51 5

17.

......

A not the name

The format of the C command is:

[n]C\$\$

where:

n specifies the number of characters the pointer is to be moved. A positive n specifies a forward movement and a negative n specifies a backward movement. If n is omitted, 1 is assumed.

C is the command code.

C Command Examples: To move the pointer to the next character in the file:

*C\$\$

To move the pointer ahead 10 characters:

*10C\$\$

To move the pointer backward 100 characters:

*-100C\$\$

F - Find Command

t

The F command searches the file for a character string specified in the command. The search begins at the current location of the pointer and continues until the string is found or the end of the file is encountered.

If the character string is found, the pointer is moved immediately following the last character of the string.

If the character string is not found, the pointer is not moved from its current location and following message is typed:

CANNOT FIND ''text''
BREAK

Where text is the character string specified in the command.

All characters must match for a match, including printing and non-printing characters (such as carriage return and line feed).

If the F command is included in a command string, an ESC or ALT MODE character must be used to terminate the character string or the following command will be used as part of the search argument.

The format of the F command is:

Ftext\$\$

where:

F is the command code.

text is the character string being searched for. The Editor only uses the first 16 characters in the string. Any characters beyond 16 are ignored.



CHAPTER 4 WORKING WITH PROGRAM MODULES

The creation of a program module is a fairly straightforward process once you have fully defined the module interfaces. However, the existence of modules would be of little value if you did not have the software tools necessary for manipulation of the modules to build your entire program. Three basic tools are required:

- A linking program that combines many modules into a single module.
- A locating program that assigns absolute memory addresses to a relocatable module.
- A library management program that permits you to add modules to a library whose contents may be accessed when linking.

These capabilities are provided by three commands LINK, LOCATE, and LIB; a standard object code format; two resident compilers, PLM80 and FORT80; and a resident assembler, ASM80.

NOTE

The location and linkage features defined in this chapter are not applicable to the object code of the 8048 microprocessor. For information about MCS-86 object module management, see 8086 Family Utilities User's Guide for 8080/8085-Based Development Systems, 9800639.

The object code format supported by ISIS-II is a relocatable format produced by PLM80, FORT80, and ASM80. ISIS-I formats must be converted to the new format for use with ISIS-II. See the HEXOBJ and BINOBJ command descriptions in Chapter 3.

The LINK program combines files containing object modules of a program into one module in one object file, adjusting the relative addresses in the process. When the modules to be combined reference each other, you must identify these references as public symbols and external symbols thus allowing LINK to satisfy the external references of each module.

The relative addresses assigned to relocatable modules are converted to absolute addresses by the LOCATE program, which produces an absolute object file (or module that can be loaded by ISIS-II for execution, debugging, or memory mapping).

The LIB program creates and maintains libraries of object modules that can be used as building blocks to create new programs via LINK.

The many reasons for relocating a program and for writing programs in modules are discussed in the following text.

Microprocessor Memory Allocation

The microprocessor memory for any given application is generally not of uniform composition. The memory is usually tailored, with RAM (read-write memory) installed for variable data and ROM (read only memory) or PROM (programmable read only memory) installed for program code. Memory chips can be installed in such a way that some addresses have no corresponding physical memory.

To enter extensive text at the end of an existing file:

```
*ZIThis is the start of the text<CR>
More text<CR>
•
•
•
Last line of text.<CR>
$
```

S - Substitute Text Command

The S command finds a character string and substitutes another character string for it. The substitution is made only if the search results in an exact match.

After a successful match, the pointer is located immediately following the inserted data.

· ·

The S command starts its search from the current location of the pointer and continues through the file until an exact match is found or until the end of the file is encountered.

If a match is not found in the search, the following message is displayed:

```
CANNOT FIND "text"
*BREAK*
```

Where text is the search argument.

There is no limit to the amount of data that can be inserted with the S command. However, the search argument is limited to 16 characters. If more characters are entered for the search argument, only the first 16 are used and only the first 16 are replaced with the new text.

When using the S command, remember that it searches to the end of the file. If you make a typing error in the search argument and that exact string exists in the file, it will be changed by the S command. It is a good idea to type the line just changed until you become experienced with the command.

The format of the S command is:

Sold-text[\$new-text]\$\$

where:

S is the command code.

old-text is the character string to be searched for and to be replaced if found. Only the first 16 characters of old-text is used.

new-text is the character string that is to replace old-text. If new-text is omitted, the character string specified by old-text is deleted.
. 1

Þ

Stack Segment

111

* x , , , * * 184 c

The stack segment is for the program stack and must be in RAM. Usually only a module that contains a main routine has a reference to a stack segment. Its length is determined by the compiler for PL/M programs and by the STKLN statement in assembly language. You can also specify the length when the program is made absolute by LOCATE. References to the stack segment are made with STACK (a reserved word in assembly language) and STACKPTR (an identifier in PL/M).

Memory Segment

The memory segment is assigned to RAM memory that is not allocated to code, data, common, or stack segments. References to the memory segment are made with MEMORY (a reserved word in assembly language and an identifier in PL/M). Although the language translators create a memory segment for each relocatable object module, its length is unknown until an absolute module is produced by LOCATE, which uses the Monitor MEMCK routine and the base address of the memory segment to calculate the length of available RAM.

Common Segments

The common segments are used for FORT80 named COMMON areas and the BLANK COMMON area. Common segments usually contain variables, and therefore, are usually placed in RAM.

Absolute Information

In addition to the relocatable code, data, stack, common, and memory segments, an object module can contain information with absolute addresses already assigned. There are three ways this can happen. The ASEG statement in assembly language causes statements following it (until a CSEG or DSEG is encountered) to have absolute addresses. Absolute modules produced by LOCATE can be linked with relocatable modules. PL/M variables declared with the AT attribute produce absolute references.

It is possible to write a self-contained program in assembly language using the ASEG statement. This results in an absolute module that can be executed directly after assembling because the assembler output is a memory image. This approach is possible only in cases where relocation is not needed.

Modular Program Development

Most programs are too lengthy or too complex to code as a straightline program. You can make the job simpler by designing first a main routine that calls separate functions in subprograms. The exchange of parameters with these subprograms can be determined during the design of the main routine. However, the actual coding of the subprograms can be left until later. The final complete program is built from the main routine and the subprograms by the LINK program. The advantages of this approach to program design are summarized in the following paragraphs. An iterative parameter can be specified with the command. If the parameter is positive (or unsigned) the command deletes the remaining portion of the line containing the pointer and and the following lines until the command parameter is met or the end of the file is encountered. If the parameter is negative, the command starts at the pointer and deletes backward for the number of lines specified.

The format of the K command is:

[n]K\$\$ ·

where:

n specifies the number of lines to be deleted. If n is positive the deletion is performed in a forward direction, and if it is negative the deletion is performed in a backward direction. If n is omitted, 1 is assumed.

K is the command code.

•

K Command Examples. To delete an entire line, you must make sure the pointer is at the beginning of the line:

*0LK\$\$

To delete all the characters in a line from the pointer through the carriage return and line feed characters:

*K\$\$

...+

To delete the entire line in which the pointer is located and the following three lines:

*0L4K\$\$

· 41

3.4

2 .

Typing a File

You can display your file with the Type command. If you have a teletypewriter terminal, the command types the text.

N 181 ·

T - Type Command

The T command displays a line on the Console output device. You can include an iterative parameter to display multiple lines. The parameter can be positive or negative. If the parameter is positive, the Editor starts displaying at the pointer and continues for the specified number of lines. If the parameter is negative, the Editor displays the required number of lines that precede the pointer. A parameter of zero displays from the beginning of a line to the pointer location. The T command without a parameter displays from the pointer through the carriage return and the line feed.

The T command does not move the pointer.

The format of the T command is:

[n]T\$\$

Relative Addressing

The relative addresses of instructions and data in the code and data segments are assigned by ASM80 and PLM80 when a source module is translated. The addresses are determined by a location counter starting with zero at the beginning and incremented by the number of bytes in each instruction. The addresses are "relative" to the beginning of the segment.

LINK combines input modules to form one output module by combining all code segments into one code segment and all data segments into one data segment. The relative addresses of the first segment remain unchanged, but LINK changes the relative addresses of the segments that follow to reflect their relationship to the beginning of the new segment. In general this means adding the length of the first segment to the relative addresses of the second, adding the combined length of the first two segments to the relative addresses of the third segment, and so on.

LOCATE produces an absolute module from a relocatable one by adding the base address of each segment to each relative address in that segment to get the absolute address. The base address of each segment can be specified in the LOCATE command or left for LOCATE to assign.

Intrasegment References

In addition to relocating load addresses, relative addresses contained in instructions or data items must be adjusted. If the address refers to a location in the same segment, it is called an intrasegment reference. A jump instruction that refers back several instructions to the beginning of a loop is this kind of reference. The value put in the address field by the translator is simply the relative or absolute address of the location referred to. If it is a relative address, it is adjusted by LINK when segments are combined and finalized by LOCATE by adding the base address of the segment.

Intersegment References

When an address in an instruction refers to a location in another segment of the same module, it is called an intersegment reference. An example is an instruction in the code segment that refers to a variable in the data segment.

When LINK combines segments to produce a new object module, intersegment references are changed to reflect the new relative addresses of the locations in the other segments.

LOCATE converts the relative address of an intersegment reference to an absolute address by adding it to the base address of the segment to which reference is made.

External References and Public Symbols

When an address field in an instruction refers to a location not contained in the same module, it is called an external reference. This reference differs from those above because the translator knows nothing about the relative location of this symbol. Therefore, you must declare these symbols external. They then become known as external symbols, which means they are defined in other modules. The instructions that refer to them are external references.

110

The format of the E command is:

E\$\$ where: E is the command code.

E Command Example. To save the contents of the text file on disk and exit the Editor:

*E\$\$

Q - Quit Command

The Q command causes an exit from the Editor and returns control to ISIS-II without saving the data in memory.

The format of the Q command is:

Q\$\$

where:

Q is the command code.

Q Command Example. To exit the Editor and return to ISIS-II:

*Q\$\$

W - Write Command

The W command takes n lines from the beginning of the memory buffer and writes them onto the disk. The lines that are output are deleted from memory. This prevents the duplication of these lines when an E command is issued.

118

A common usage of the W command is to store part of a very large program while still entering the end portions. Once data has been written out to disk using the W command, it can only be brought back into memory by issuing an EXIT command and then an EDIT command for the file.

The format of the W command is:

n specifies the number of lines to be output and deleted from memory. If n exceeds the number of lines in the file, the entire file is output. If n is omitted, 1 is assumed.

W is the command code.

W Command Example. To save the first 25 lines of the file in memory on disk:

*25W\$\$

The library manager program can give you a list of the modules in a library file, including the public symbols in each module. You may want to keep all the object modules for one program in a library, or you may want to keep modules relating to a specific function in one library file. For example, a system library supplied with ISIS-II is called SYSTEM.LIB and contains the object modules for linking programs to ISIS-II system routines.

Link Command

The ISIS-II program LINK allows you to combine object modules from several input files into one object module in one output file. In the process of combining modules LINK adjusts all addresses so they are relative to the beginning of the segments in the output module. LINK also searches libraries for modules that resolve external references in the modules being combined and includes them in the output module. If any unresolved external references remain in the output module, LINK puts a message in the map that describes the structure of the new module.

The output module must be processed by LOCATE before it can be executed. The LOCATE program assigns absolute memory locations to the object module. The output module can also be used as input to LINK to be combined with other modules into a new and expanded output module.

The LINK program is called into operation by the LINK command. The syntax of the LINK command is:

LINK <inputlist> TO <outputfile> [<controls>]

where

<inputlist> can be either or both of the following two items:

<filename>[(<modname1>,<modname2>,...,<modnamen>)]

PUBLICS(<filename>,<filename2>,...,<filenamen>)

In the first item <filename> specifies a file containing object modules or a file containing a library of object modules. If <filename> is not a library file, it is included in the output module. If <filename> is a library file and <modnames> are specified, then only the specified modules are linked into the output module. If <modnames> are omitted and <filename> is a library, only those library modules that satisfy external references in modules already named in the <inputlist> or already included from the library are linked into the output module. In other words, when <modnames> is omitted, only those library modules that satisfy an existing unresolved reference are included.

The second item PUBLICS specifies modules whose absolute public declarations only are to be included in the output module. This allows for linking modules without combining them in the output file so they can be loaded separately. See the section on overlays in this chapter for a description of this capability.

<outputfile> specifies the file to contain the object module resulting from linking the input modules. This file must not also be specified in the input list.

<controls> are one or more keywords that control the operation of LINK. The controls are:

MAP

This control requests that a link map be produced. The link map is sent to the console output device (:CO:) or to the file specified in the PRINT control. The content of the link map is described later in this chapter. If you are entering a large amount of data, you can check on the amount of storage available and, if it runs short, save the first part of the file on diskette with the W command.

The format of the M command is:

M\$\$			1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	# +1 szters +
1	,	•	الأقفادة ا	1 1 1 1 A
where:		4	14C 10 1	· ** ·
	• 1	\$ j	+ 1947 - 1	ffich a la
M is the command of	code.		1 -	

M Command Examples. To check on the amount of storage available:

*M\$\$

Command String Iterations

You can repeat a command string or a single command any number of times by enclosing the command string in angle brackets (< >), preceded by a number that specifies the number of times the command string is to be performed.

A typical use of this capability is to meet the need to change a character string that exists throughout the file. For example, if you have a program that uses a data field named "X1" and you want to change all occurances of the name to something more meaningful to anyone else reading the code. To change "X1" to "LOOPCNT" through out the file you can use the following:

*B100<SX1\$LOOPCNT\$>\$\$

In this example, note that a B command was used first to move the pointer to the top of the file. Also note that an ESC or ALT MODE character was used to separate LOOPCNT from the final angle bracket. This prevents the Editor from using the angle bracket as part of LOOPCNT.

In the description of the A command it was pointed out that an iterative parameter cannot be used with A command. In an example there, we used a string of 10 A commands to read 500 lines from paper tape. Using this facility, the 10 A commands can be entered as follows:

• * FIM BOUGH MULL - ME INGING - FOR

This is equivalent to:

*10<A>\$\$

*AAAAAAAAAA\$\$

while:

*10A\$\$

is only equivalent to:

* A\$\$

्राद्य सन्द्र हें के र _____र्ग र र

ð

the strate of

В

Ρ

I

Α

The REL column in the LINK map specifies the segment relocation type. The following abbreviations are used in the REL column: · · · 1 1 . . byte relocatable page relocatable in-page relocatable וAt absolute or non-relocatable 111 ISIS-II OBJECT LINKER Vx y INVOKED BY: -LINK FILNAM EXT.PROG.LIB(TRIG),PROG.LIB.& **PUBLICS(TANSTA.AFL) TO SHIP WRK NAME(CELESTIGATION) MAP (Non-fatal error messages appear here.) LINK MAP OF MODULE CELESTIGATION WRITTEN TO FILE : F0.SHIP.WRK MODULE IS NOT A MAIN MODULE ٩. SEGMENT INFORMATION: START STOP LENGTH REL NAME 2345H Ρ CODE *GAP* CODE 10BCH **10FFH** 44H 22FEH CODE *GAP* 22FFH 2H 107H в DATA 75H В /FRED/ 10F2H в H ABSOLUTE 0000H 0002H 3H Α А ABSOLUTE 0040H 0711H 6D2H 0700H 07FFH 100H А ABSOLUTE *OVERLAP* FD00H FD00H A ABSOLUTE 1HINPUT MODULES INCLUDED :F0:FILNAM.EXT (NAVPACK) :F0:PROG .LIB (TRIG) :F0:PROG .LIB (EXP) \$, :F0:TANSTA.AFL (MCBRIDE) (PUBLICS) UNRESOLVED EXTERNAL NAMES: COSIGN-REFERENCED IN .F0:FILNAM.EXT(NAVPACK) (Other errors appear here.)

Order of Modules in the Output File

LINK combines modules from the input list by combining all the code segments from the input modules into one code segment, all the data segments into one data segment, and all the stack segments into one stack segment. The length of the memory segment is computed by LOCATE. Any absolute information in the input modules is transferred to the output module with absolute addresses unchanged. If absolute information is in conflict for the same location, a message to that effect is put in the link map.

` / • ¥. 9 ١ I **%**ŧ

•

<controls> specifies one or more keywords that control the operation of LOCATE. The controls and their default values are explained in the following descriptions. The LOCATE controls are:

MAP	1	1			
COLUMNS(number)		1			
PRINT(file)		1			۰. e ¹
SYMBOLS	2	1	÷ 1		· `,
LINES					
PUBLICS				۰ ۰۰	¥
PURGE			ધ		(
ORDER(segment sequence)					÷ +.
CODE(address)			,	\$6.7 I	
DATA(address)					
STACK(address)		11-	,	1 37 1	
MEMORY(address)					
/common name/(address)					
//(address)		8			
NAME(name)		1			
RESTART0		I			-1 1
START(address)					• " r
STACKSIZE(value)				•	11

If a LOCATE command is longer than one line on your console, (which must not be greater than 122 characters), you can continue it by entering an ampersand (&) as the last non-blank character before the carriage return. The ampersand cannot appear within a filename or control keyword. It can be placed between a keyword and the associated parameter list, for example:



LOCATE uses a temporary file named LOCATE.TMP on the disk to which the output is directed. If you have a file by this name on the output disk it will be destroyed.

"Appendix C: Error Messages" lists the LOCATE error messages.

LOCATE Control Descriptions

MAP

The MAP control specifies that a memory map be printed on the list device. Normally, the printing of the map is suppressed. The map lists the start address for the module, the start and stop addresses for each segment along with their length, and relocation type.

The REL column specifies the relocation type. The following abbreviations are used in the REL column:

B P	byte relocatable	- + - 	- 1 ⁹	,	
Î A	in-page relocatable ⁵ absolute or non-relocatable	1	\$ • 1 . _	f	

-

This diversity in memory design (as well as programming considerations explained later) requires you to tailor your program, specifying absolute addresses for the actual ROM and RAM locations used for code and data. However, you may not know the absolute addresses of the ROM or RAM in your final application at the time you start to develop the program. At an early stage of development when you are testing your program in the system, your only concern with locating the program is that it doesn't overlap the resident routines of ISIS-II. The system memory is simply a sequence of RAM locations from 0 to 32K, 48K, or 64K. However, as your program development continues and debugging becomes a prime concern, address requirements are much more specific. Code may be in PROM starting at location 0; variable data may begin in the first location of a block of RAM.

The program that had a base address of 4000H for compatibility with ISIS-II resident software and had variable data immediately following code, may need new addresses to meet the requirements of the memory in the final application. In a system that deals only with absolute code, you would have to change the source program to specify new addresses and translate again to get object code with correct addresses. In the relocation and linkage system of ISIS-II, you simply produce a new absolute memory image from the relocatable object modules by using the LOCATE program. LOCATE assigns addresses to place code in ROM or PROM, variable data in RAM, and the stack in another area of RAM.

Program Segments

The LOCATE program allows the user to preassign areas of memory because of the way the language translators (PLM80, FORT80, and ASM80) divide a relocatable object module into segments. The segments are:

- Code
- Data
- Stack
- Memory
- Named and unnamed common segments (FORT80 only)

Each segment starts with a relative address of zero. A base address can be specified for each segment when it is being LOCATEd. The base address is the actual address of the first memory location the segment will occupy. LOCATE adds the base address to each relative address and adjusts address references accordingly.

Code Segment

The code segment is that part of the program destined for ROM because it contains machine instructions and program constants that are never modified during execution. This segment can also be placed in RAM. In assembly language it consists of statements following a CSEG directive.

and the second s

Data Segment

The data segment is that part of the program that usually requires RAM. It contains variable data and storage for I/O buffers. In assembly language it consists of statements following a DSEG directive.

The following is a sample symbol table:

SYMBOL TABLE OF MODULE TRIG READ FROM FILE TRIG REL WRITTEN TO FILE TRIG

VALUE	TYPE	SYMBOL	ſ	
			j č	
	MOD	TRIG		
3011H	PUB	SIN	es tor a	•
3015H	SYM	SIO		F
3027H	SYM	SI1	2 4 3 12	n
3040H	SYM	TRIGEX	j j	1 242 6
3063H	PUB	COS	i f	
3102H	PUB	TAN	• , •	۴
3230H	SYM	TAN0		*3
3340H	LIN	272		
				۰ <u>۲</u>
				4, ¹ 4

۶

LINES

The LINES control specifies that a list of the line numbers and input module names from the program is to be included in the symbol table in the list file. Line numbers have the type LIN and module names have the type MOD. The VALUE field is blank for module names in the symbol table. Normally, the printing of the symbol table is suppressed.

PUBLICS

```
्रसार
स्टिये प्रदे ,
```

The PUBLICS control specifies that a list of symbols declared public is to be included in the symbol table. Public symbols have the type PUB. Normally, the printing of the symbol table is suppressed

PURGE

X

The PURGE control specifies that line numbers, local symbols, module names, and public symbols be removed from the output module Public symbols could be used, if present, to link the absolute module with other modules Line numbers, local symbols, and module names could be used for debugging The PURGE control condenses the size of a module that is completely debugged This results in saving disk space and decreasing load time

ORDER(segment sequence)

The ORDER control defines the order in which the various segments are assigned memory locations. The list of segments in the segment sequence parameter must be separated with spaces.

CHERTER MES

If ORDER is not specified, the segments are located in the following order:

CODE	
STACK	
/commons/ (named and unnamed commons in an arbitrary order)	
DATA	1221234
MEMORY	- • ·

This default order can be changed with the ORDER control. LOCATE determines the addresses at which the segments reside but it is done in the order specified by the control.

Faster Program Development

Your program can be developed faster if the modular approach is used because small modules are easier to understand and simpler to program. Breaking a program up into functional modules makes it possible to assign the pieces to a team of developers. With the specific tasks well defined, you can concentrate on programming and testing a specific module. You can supply the input required by the module and verify it by examining the output. As the modules are debugged, they can be put in a library file using the LIB program. When all modules are ready, the LINK program is used to combine the modules into one complete module, which can then be assigned absolute memory addresses by LOCATE.

Use of Different Source Languages

The modules that make up the final program need not be translated from the same language. PL/M, FORTRAN, or assembly language can be used, whichever suits the task best. Relocatable modules produced by the compiler, the assembler, or both can be input to LINK to build a program.

Shared Subprograms

When modules of one program have been tested they can be used by other programs. This means that part of the job of future programming is already done. Because the module has relocatable addresses, it can be combined with different programs, having different address requirements each time.

Easier Debugging and Program Modification

It is easier to narrow down the location of a bug when a program is divided into modules. When you have identified the module containing the error, you can concentrate on debugging that module. When a program must be modified, it may mean that only one or two modules must be changed or added. When the new or changed modules have been translated and debugged, a new absolute memory image can be created simply by using LINK and LOCATE rather than retranslating the entire source program.

Mechanics Of Relocation And Linkage

LINK is able to combine modules, adjusting relative addresses, and LOCATE is able to convert relative addresses to absolute addresses because of information put in the object modules by the translators, ASM80, PLM80, and FORT80. The following types of information in the object module are used by LINK and LOCATE:

- Relative addresses of instructions and data.
- A list of address fields in instructions or data that refer to a location in the same segment (intra-segment references).
- A list of address fields in instructions or data that refer to locations in other segments in the same module (inter-segment references).
- A list of address fields in instructions or data that refer to locations not contained in the same module (external references).
- A list of symbols in the module that are declared public or external in the source code.

You should understand external references and declaring symbols public and external to successfully use LINK and LOCATE. However, an understanding of the other topics in this section is not as important. It is provided here to give a complete picture of the mechanics of relocation and linkage. preparing an absolute module for execution in your prototype system, either the standalone system or the system being emulated with the in-circuit emulator. When the RESET signal is input to the CPU, the program counter is set to 0 and execution begins with the jump to the beginning of your program. An absolute module prepared with the RESTARTO control is not compatible with ISIS-II, which does not allow user code to be loaded in locations 0, 1, or 2. The RESTARTO control is ignored if the input module is not a main module. •

START(address)

The START control specifies the address of the first instruction in the code segment to be executed. This address overrides the address in the input module. If START is omitted, the address is taken from the input module. The START control is ignored if the input module is not a main module. .

STACKSIZE(value)

The STACKSIZE control specifies a value (in bytes) for the size of the stack segment. This value overrides any calculated stack size encountered in the input module.

When debugging a program in an Intellec microcomputer development system, 12 additional bytes of user stack are required beyond that computed by the language translator or LINK. LOCATE adds these 12 bytes if the STACKSIZE parameter is not specified.

1 11 111

a second second

How LOCATE Locates Segments

Module segments are normally located sequentially in memory in the order:

CODE segment STACK segment /commons/ segments (in an arbitrary order) MEMORY segment

You can change the order with an ORDER control and with the CODE, STACK, /common/, //, DATA, and MEMORY controls. You can change the order by using the default order in conjunction with the ORDER control and the segment controls specifying an exact address. 1. 1

· - - -

Locating With The Default Order

When you use the default order, the CODE segment is located 680H bytes above the top of ISIS-II and the rest of the segments immediately follow in order. Gaps are generated only when required by the relocation type of the segment.

- Byte relocatable (BR) segments are located at the first available byte.
- Page relocatable (PR) segments are located at the first available byte that lies on • a page boundry (a multiple of 256 (100H) bytes).
- In-page relocatable (IP) segments are located at the first available byte such that the segment is totally contained within a page. · , " '

The module containing an external reference is said to be an "unsatisfied" module or is said to contain an "unsatisfied" external reference. LINK combines this module with the module that contains the proper "connector". This connector is a public symbol that matches the external symbol. A public symbol is a symbol declared to be public in the source module and put in the object code with its address by the translator.

When LINK "connects" two modules by matching an external symbol to a public symbol, the value of the public symbol (its relative or absolute address) goes in the address field of the instruction that refers to it. Then LINK removes the external references. It is replaced with an intersegment or intrasegment reference if the public symbol has a relative address. If the public symbol has an absolute address, nothing replaces the external reference because no further address adjustment is required.

If the module that LINK produces contains unsatisfied external names, LINK issues a warning message about each one. This module must be linked again with modules containing the matching public symbols in order to produce a satisfied module. The unsatisfied external name messages from LINK do not indicate that an error exists. In intermediate steps of development before all modules of the program are complete, you can expect LINK to produce these messages. Also, if you have declared a name external but never make a reference to it in your program, LINK produces an unsatisfied external name message even though no unsatisfied external reference exists.

This points up the fact that you should have some way of identifying the state of the object code in a file. Saving the memory maps from a LINK and LOCATE is one way of keeping track; using an extension in the filename that reflects the type of contents is another way.

When a module contains no external references, it is said to be "satisfied". The public symbols are not removed from the object module because they may be needed later if a new module is added that has an external reference to one of the public symbols.

If LOCATE finds an external reference in an object module it is processing, it issues a warning message but continues to produce the absolute module. The absolute module can be executed, perhaps in debug mode with a breakpoint specified to stop processing before the instruction containing the unsatisfied external reference is reached. If that instruction is executed, results are unpredictable because the address in the instruction is undefined.

.

Use of Libraries

Libraries make your job of building programs from object modules via the LINK program even easier. The library manager program LIB creates and maintains files containing object modules. LIB creates a directory of the modules in each library file to keep track of the modules it contains.

The LINK program treats library files in a special way. If you specify a library file as input to LINK after specifying the modules to be included, LINK searches the library for modules that contain public symbols to match the unresolved external references in the preceding modules. If a module from the library is included but it also has unresolved external references, LINK searches the library again trying to find the module with the public symbols to satisfy the new external references. This process is repeated until a search has been made to satisfy all external references.

114

٠.

The DATA segment is located 680H bytes above the top of ISIS-II and STACK is located immediately following DATA. CODE is located next, but instead of being placed immediately following STACK it is placed at address 6000H as specified by the CODE control. The /commons/ (if any) immediately follow CODE and MEMORY follows the /commons/. In other words, the segments are still located in the sequence specified by the default order and the ORDER control but the locations are modified by the individual segment location controls.

If you are going to locate some segments at specific addresses and let LOCATE place the rest, you should use the ORDER control to modify the default sequence so that segments are located in an order that corresponds with the specific addresses in the controls. If you aren't careful, conflicts can occur. Be sure to specify the MAP control, to verify that segments are placed as intended. Conflicts do not stop the LOCATE function, because there are circumstances where you will want apparent conflicts such as the location of an absolute segment in an internal gap in a segment.

When you want to locate FORTRAN common segments to specific addresses, you should also locate the MEMORY segment to an address above the top of the highest common segment. LOCATE handles the common segments in an arbitrary order. You will not know ahead of time what order the common segments will be handled by the command. If the common segment that you place at low memory is the last one handled by LOCATE, the MEMORY segment will immediately follow it and will conflict with all segments above it.

LIB Command

LIB uses a temporary file named LIB.TMP on the disk to which the output is directed. If you have a file by this name on the output disk it will be destroyed.

WARNING

The ISIS-II LIB program allows you to create specially formatted files to contain libraries of object modules, to maintain these libraries by adding and deleting modules, and to obtain a listing of the modules in a library file. Libraries can be used as input to LINK, which may automatically link modules from the library that satisfy external references in the modules being linked.

The library manager program is called into operation by the LIB command. The syntax of the LIB command is:

LIB

١

ada ada Ser.

The operation of LIB is controlled by entering commands to indicate which operation LIB is to perform. LIB prompts for commands with an asterisk (*). The commands are:

CREATE ADD DELETE		· · ·	•,	' / <u>[</u> 1
EXIT	,		ŧ	. '

- NAME(<modname>) This control specifies the name to be assigned to the output module. The name can be from 1 through 31 characters, each of which must be a letter (A through Z), a digit (0 through 9), a question mark (?), or a commercial at sign (@). However, the first character of the name cannot be be a digit. If NAME(modname) is not specified, the name part of the output file specification is used as the module name.
- PRINT(<filename>) This control specifies the file to contain the link map. If omitted, the link map goes to the console output device (:CO:).

If a LINK command is longer than one line on your console (which must not be greater than 122 characters), you can continue it by entering an ampersand (&) as the last non-blank character before the carriage return. The ampersand cannot appear within a filename or control keyword. It can be placed between a keyword and the associated parameter list, for example:

PRINT& (:F1:PRTFIL)

is a valid use of the continuation character. LINK prompts for the continued line with a double asterisk (**). If necessary, subsequent lines can be continued also.



LINK uses a temporary file named LINK.TMP on the disk to which the output is directed. If you have a file by this name on the output disk, it will be destroyed.

"Appendix C: Error Messages" lists the LINK error messages.

Link Map

The link map produced by LINK includes the following information:

- The LINK sign-on message.
- The command used to call LINK (unless map is output to :CO:).
- The length of the relocatable segments in the output module.
- The addresses of absolute information in the output module.
- The names of the input modules.
- Unresolved external names.
- Non-fatal error messages.

The following example shows a link map for the output module contained in the file SHIP.WRK, which was produced from two modules explicitly listed in the input list, a module included from searching a library to resolve external references, and the public symbols of a fourth module.

SE -

Ð

LIST - List Library Modules and Their Public Symbols (2019) 611

The LIST command lists the module directory of the library file. The syntax of the LIST command is:

LIST <libfile>[(<modname>,...)][,...] [TO <listfile>] [PUBLICS]

where

s the name of the library file whose entire module directory is to be listed unless <modname> is also specified. In that case, only information about the specified modules is listed.

s the name of the file to contain the library listing. If omitted, the directory is listed on the current console output device (:CO:).

PUBLICS specifies that public names in each module are to be listed. If omitted, only the module names are listed.

The format of the listing when public names are requested is:



EXIT - Return to ISIS-II

The EXIT command returns control to ISIS-II. When finished with LIB, enter the EXIT command, followed by a carriage return. This terminates the LIB program and returns control to ISIS-II, which prompts for a command with a hyphen (-).

Example : The following example shows the creation of a library file and the entry in the library of two modules. The directory of the library is listed before exiting to ISIS-II.

1

```
-LIB
ISIS-II LIBRARIAN Vx y
*CREATE FOO LIB
*ADD SIN OBJ,COS OBJ TO FOO LIB
*LIST FOO LIB
SINE
COSINE
*EXIT .
```

"Appendix C: Error Messages" lists the LIB error messages.

4-19

The order of combining follows the order in which modules are specified in the input list. The first module specified is the first in order in combining. The segments of the second module follow the segments of the first module at the first available location.

Example : The following LINK command and explanation shows how modules are combined.

LINK A, B TO C

d'Est. int

- ;

1.10

Ľ

11 21 1

Sept. Strand

2 50

Module A contains code, data, and stack segments. Module B contains code and data segment. They are all byte relocatable. The resulting module C has the following structure



In the process of linking the input modules, external references are satisfied. For instance, if module A has a branch to a point in module B, it is no longer external when A and B are combined into C. If A or B has an external reference to a module in a library file, the library must be specified in the input list *after* the module that refers to it. Suppose the library file RTNS.LIB contained a module that satisfied an external reference in A. Then the input list could be specified A,RTNS.LIB,B or A,B,RTNS.LIB. "Appendix C: Error Messages" lists the LINK error messages.

Locate Command

The LOCATE program takes an input file containing a relocatable object module and produces an output file containing the object module with the relative addresses fixed to absolute locations. The LOCATE program is activated by the LOCATE command. The syntax of the LOCATE command is:

LOCATE <inputfile> [TO <outputfile>] [<controls>]

where:

<inputfile> is the name of the file containing the relocatable object code.

<outputfile> is the name of the file that is to contain the absolute object module. If TO <outputfile> is omitted, it uses the filename portion of <inputfile>. If a file already exists with the same name as specified by <outputfile> (or the defaulted name), it is overwritten with the new data. If <outputfile> is not specified, <inputfile> must consist of a filename and extension because the default name for the output file is the filename (without extension) from <inputfile>. Ξ

All the pieces of this overlay structure must be in separate files because they are loaded separately. The root calls A and B; A calls AA and AAA. If you locate the root first, you can use the memory map produced by LOCATE to determine the base address of A and B. Then locate A and B. Use the memory map produced by LOCATE for A to determine the base address of AA, AAA. The modules produced by LOCATE have absolute memory addresses assigned but external references are unsatisfied. These modules cannot be loaded into memory for execution but can be used with the PUBLICS keyword in the linking process.

Suppose the modules produced by LOCATE were given the extension of TMP. Suppose the root has external references to public symbols in A and B; A has external references to public symbols in the root, AA, and AAA; AA and AAA have external references to public symbols in A; B has external references to public symbols in the root. Then the following LINK commands would produce the satisfied modules ready to execute.

LINK ROOT.TMP,PUBLICS(A.TMP,B.TMP) TO ROOT LINK A TMP,PUBLICS(ROOT TMP,AA TMP,AAA TMP) TO A LINK AA TMP,PUBLICS(A.TMP) TO AA LINK AAA TMP,PUBLICS(A.TMP) TO AAA LINK B TMP,PUBLICS(ROOT TMP) TO B

The modules ROOT, A, AA, AAA, and B are absolute because of the previous LOCATE operation and fully satisfied because of the above LINK operation. They are connected but not combined.

To verify that all external references are satisfied in the modules produced by LINK, you can LOCATE them again. This time LOCATE should produce no message about unsatisfied external differences.



When you link without combining to produce overlays, you must provide overlay management in the design of your system. That is, before your program makes a reference to an overlay segment, it must make sure that segment is in memory. If not, the segment must be read into memory. When a segment in memory contains new data that must be saved, it must be written out before it is overlaid with another segment. The ability to link without combining provides the hooks for an overlay scheme. The runtime management of overlays must be designed into your software.

Memory Pages and the H and L Registers

Relocation types are provided for programs that reference memory by manipulating the H and L registers independently. (See the 8080/8085 Assembly Language Programming Manual 9800301, for a description of the HIGH and LOW operators.) You can store data on a page boundary and address elements in it by changing only the L register. If the data does not cross a page boundary, you do not have to change the H register at all.

However caution must be used if the HIGH operator is used on an arbitrary address in relocatable code, you may get an incorrect address because LOCATE assumes the unused portion of the address to be zero. If the unused portion of the address is not When a segment overlaps another segment, a warning, (OVERLAP) is printed in the map. This does not stop the locate function. This may be intentional, as in the sample map. The three byte absolute segment is designated to fit into the data segment.

Th	e following is	an example	of a memory r	nap:	ż	\$
	ISIS-II OBJEC -LOCATE TRI	T LOCATER V G REL MAP PF	x y INVOKED B' RINT(CO) NAM	Y IE(TRIG)		(****) ****
	MEMORY MA READ FROM WRITTEN TO MODULE STA	P OF MODULE FILE F0 TRIG FILE F0 TRIG ART ADDRESS	ETRIG REL 3000H		ι,	ε 25 π Εξ τ Ειτιδικικ μαριδι
	START	STOP	LENGTH	REL	NAME	1) 5 2 C
	0008H 3000H 3440H 3630H 472FH 4760H	000AH 343FH 472EH 3632H 475FH F6BFH	3H 440H 12EFH 3H 31H AF60H	A B A B B	ABSOLUTE CODE DATA ABSOLUTE (STACK MEMORY	MEMORY OVERLAP)
		\$	WAR	NING	ж т	, t ,

The length of the MEMORY segment is always computed to be the amount of available memory on the host Intellec development system. If the module is executed on the Intellec system, the MEMORY segment length is correct as specified. If the module is executed on a different system the actual amount of memory depends on the configuration of that system. LOCATE has no knowledge of the configuration of the target system

COLUMNS(number)

The COLUMNS control specifies whether the symbol table in the list file is to be printed in 1, 2, or 3 columns. The default is 1 This control is ignored unless SYM-BOLS, LINES, or PUBLICS is specified.

PRINT(file)

Ĩ

4

F

The PRINT control specifies a list file for the LOCATE program output. If the PRINT control is not specified, the output goes to the console output device (:CO:).

SYMBOLS

The SYMBOLS control specifies that a list of local symbols (within a module) and input module names is to be included in the symbol table in the list file. Normally, the printing of the symbol table is suppressed. Local symbols are listed in the table with a type of SYM and module names have the type MOD.



c

CHAPTER 5 USE OF ISIS-II AND THE MONITOR BY OTHER PROGRAMS

Writing programs that make use of ISIS-II and Monitor capabilities is the same as writing any other program except that the program includes ISIS-II or Monitor system calls. The placement of your program in memory must take into consideration how memory is organized under ISIS-II.

Line-editing is available to ISIS-II programs. It allows you to correct errors at the keyboard so that an error free line can be transmitted to the requesting program.

Memory Organization And Allocation

The organization of Intellec memory under ISIS-II is shown below. Interrupts 0 through 2 are reserved for ISIS-II and the Monitor. Interrupts 3 through 7 are available for use within your program. These locations, 24-63, are the only locations below 12K (3000H) that can be loaded with user code. Loading other locations below 12K is not allowed.

The ISIS-II resident area is reserved for the part of ISIS-II that is always resident in RAM memory. Although the ISIS-II resident area is protected from a program load operation, it is not protected from an executing program, which may accidentally destroy the integrity of ISIS-II by writing in this area, causing subsequent errors when system services are requested.

The buffer area is used by ISIS-II for input/output buffers of 128 bytes each. One permanent buffer is used by ISIS-II for console input/output. Other buffers are allocated and deallocated dynamically for you by ISIS-II according to the input/output requirements of your program. The minimum size of the buffer area allows for three buffers, including the ISIS-II permanent buffer. If more than two buffers are required by your program, the buffer area increases at the expense of the vacant area.



A partial list can be specified in the ORDER control. When a partial list is specified, the segments specified are located first in the order specified. The remaining (unspecified) segments follow in the default sequence. For example, the control:

ORDER(DATA)

results in the sequence: DATA, CODE, STACK, /commons/, MEMORY (assuming all segment types exist in the module.)

The first segment is located 680H bytes above the top of the ISIS-II code (3680H). This allows room for 13 input and output buffers (six open files and :CO: and :CI:). You can also change the order with the CODE, STACK, /name/, //, DATA, and MEMORY controls by specifying a specific address at which each will reside. The section "How LOCATE Locates Segments," following the control descriptions describes how the default order, ORDER control, and specific address controls interact to locate segments.

CODE(address)	
DATA(address)	
STACK(address)	1.41
/common name/(address)	
//(address) MEMORY(address)	

The segment locations can be specified explicitly with the segment controls. The controls are specified with the address. The address can be in decimal, hexadecimal, octal, or binary. The address must begin with a digit and may be followed by a letter specifying the base of number:

The specified addresses of some segments may be changed by LOCATE. If because of the addressing within a segment, it must reside at or between 256 byte multiples of memory, the Locate program will make the adjustment.

The section "How LOCATE Locates Segments," following the control descriptions describes how the default order, ORDER control, and specific address controls interact to locate segments.

10 4 5 C 14 5

1.01

NAME(name)

The NAME control specifies a name for the output module. The name can be from 1 through 31 characters, each of which must be a letter (A through Z), a digit (0 through 9), a question mark (?), or a commercial at sign (@). However, the first character of the name cannot be a digit. If NAME is not specified, the name in the header record of the input file is used.

RESTARTO

The RESTARTO control places a jump instruction at locations 0, 1, and 2 in the absolute module. The address in the jump instruction is the programs starting address (the address of the first instruction to be executed) taken from the input module or from the START control. You would use the RESTARTO control when

ž

. ۸.,

162 5 8

्र ्य टंग्र

140

11

If you want to cover the possibility of the program being called from a SUBMIT file where the console output device is also a disk file, four more buffers are needed, requiring an address of 3480H:

$$3000H + (128*9) = 3480H.$$

Example 2: Suppose a program opens a line-edited disk file (3 buffers), an echo file on disk (2 buffers), and also changes the attributes of a disk file with the ATTRIB system call while the files are open (2 buffers). The program origin point is calculated as follows:

3000H + (128*8) = 3400H.

NOTE

If you want to write a program independent of the type of device used for data transfers and independent of how it is called (from the console or from a SUBMIT file), you should allow for the maximum number of buffers it might need. This means that for any open file you would allow two buffers whether or not it is a disk file. You would also allow five buffers for the console input and output files, whether or not they are disk files.

Line-Edited Input Files

ISIS-II provides a special way of reading ASCII files called line-editing. Line-editing was designed for (but not restricted to) the case of a human user, prone to err, typing characters at a keyboard. The rubout key and control characters allow him to correct his mistakes and then transmit a perfect line by typing a carriage return to which a line feed is appended automatically.

ISIS-II is notified that a file is to be line-edited by a parameter in the OPEN system call. Associated with every line-edited file is a file to which ISIS-II sends an echo of the input. The echo file must be opened before the line-edited file. If no echo is desired, the byte bucket file :BB: can be specified as the echo file.

Terminating a Line

While a line is being physically entered from an input device, it is accumulated by ISIS-II in a 122-character line-editing buffer. The contents of the buffer are altered by ISIS-II when an editing character is entered. See explanation of editing characters below. No data is transferred to the requesting program until the line is terminated in one of three ways:

- A line feed is entered (automatically appended to every carriage return).
- An escape is entered.

. . .

۰. به ۱

• A non-editing character is entered as the 122nd character.

Reading from the Line-Edit Buffer

When the line has been terminated, a READ system call transfers data from the lineediting buffer to the requesting program's buffer. ISIS-II maintains a pointer to keep track of what characters have been read from the line-editing buffer. For example, if the line-editing buffer contains 100 characters and a READ system call with COUNT=50 is issued, the first 50 characters are transferred to the program's buffer and the buffer pointer is moved to the 51st character. The next READ system call transfers characters starting at the 51st character.

ŧ

Locating With the Default and ORDER Control

You can change the order totally with the ORDER control. When you specify all segments in the ORDER control the first segment is located 680H bytes above the top of ISIS-II and the rest of the segments immediately follow in the order specified. Gaps are generated only when required by the relocation type of the segment.

If you don't specify all the segments in the ORDER control:

- First, the segments specified in the ORDER control are located in the order specified.
- Next, the segments not specified in the ORDER control are located immediately following the last segment specified, in the default order.

If you submit the following ORDER control with the LOCATE command:

ORDER(DATA STACK)

the segments will be located in the following order:

DATA STACK CODE /commons/ (if FORTRAN) MEMORY

inal I'm to or

. . . .

12

Locating With the Default, ORDER Control, and Specific Addresses

You can change the order with a combination of the default order, an ORDER control, and specific segment location controls. You should not specify a segment in the ORDER control and with a segment location control. When all three forms of locating are used, segments are located according to the following:

- Segments are selected for placement in the order specified by the ORDER control and the default sequence as described in the preceding section.
- The starting address of a segment is either the address following the preceding segment (680H above ISIS-II for the first segment) or the address specified in a location control.

If the LOCATE command is submitted with the following controls:

ORDER(DATA STACK) CODE(6000H)

the segments are placed in the sequence:

DATA STACK CODE /commons/ MEMORY i.

For example, suppose the following command has been entered:

-TYPE F1 PROGA SRC(CR-LF)

```
1 25 1
```

The line-editing buffer for :CI: contains 20 characters as follows (the CR means carriage return, LF means line feed):

Ŧ	Y	р	E				1		Ρ	R	0	G	A		s	с	R	CR	LF
1	. 2	3	4	6	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20

When the TYPE program is loaded, the buffer pointer is at the fifth character (the space following TYPE). A READ call starts transferring characters at the fifth character. New input from :CI: to the line-edit buffer does not happen until the buffer pointer is moved to the end of the buffer (after the 20th character) and a READ call is issued.

Remember that when control is passed to the loaded program, the buffer pointer is positioned after the command name, not at the end of the buffer. This means that if no parameters are passed, the first READ from :C1: returns the carriage return-line feed left from the command line. For example, suppose the following command has been entered:

	1		•	•			•	•	41 ¹⁵ -
-PROGA BIN(CH-LF)		es.			. 1 ⁸⁴			,	11 '10
and the line-editing buffer contains 11 characters as		follows	ws:	le ⊣		. tř. 4	ינ' גיד רון פ		
									(K . K .)

₽	R	0	G	A		8	Т	Ν	CR	LF	P 67	1 K 10 K		1
1	2	3	4	5	6	7	8	9	10	11	1 ()***	•	•	٠,

- uts

When PROGA.BIN is loaded, the pointer is at the carriage return. If subsequent input is expected from the console input device, a READ must first be issued to clear the buffer of the carriage return-line feed.

If the program does not read from :CI:, the remaining carriage return-line feed is cleared by ISIS-II from the buffer before a new command is read by the command interpreter.

Summary Of System Calls

The ISIS-II and Monitor services that can be called by your program include the following:

- Input/output operations for the disk and the standard Intellec peripherals, except the Universal PROM Programmer (OPEN, CLOSE, READ, WRITE, SEEK, RESCAN, SPATH).
- Disk directory maintenance (ATTRIB, DELETE, RENAME, GETATT, GETD).
- Console device assignment and error message output (CONSOL, WHOCON, ERROR).
- Program loading and execution and return to the supervisor (LOAD, EXIT).

>

Continuation Lines

If a command to LIB is longer than one line on your console (which must not be greater than 122 characters), you can continue it by entering an ampersand (&) as the last non-blank character before the carriage return. The ampersand cannot appear within a filename or control keyword. It can be placed between a keyword and a parameter, for example:

i

Ħ

. .

DELETE PVT.LIB& (MOD1)

LIB prompts for the continued line with a double asterisk (**). If necessary, subsequent lines can be continued also.

CREATE - Create a Library File

The CREATE command creates an empty library file. You must use the ADD command to add modules to the library file. The syntax of the CREATE command is:

CREATE <filename>

where

<filename> specifies the name to be assigned to the new library file. If a file with that name already exists, an error message is sent to the console and L1B prompts for another command.

116 11

.:`

.

ц, r

ADD - Add Modules to a Library File

The ADD command adds object modules to a library file. The syntax of the ADD command is:

ADD <filename>[(<modname>,...)] [,...] TO <libfile>

where

<filename> can be the name of a library file or the name of a file containing an object module. If a library file is specified, all the object modules contained in it are added to <libfile> unless <modnames> are specified.

<modnames> can be specified only if <filename> is a library file. Only the object modules specified by <modnames> are added to <libfile>.

dibfile> is the library file being modified by the addition of modules in <filename>.

DELETE - Delete Modules from a Library File

The DELETE command deletes modules from a library file. The syntax of the DELETE command is:

DELETE <libfile> (<modname>,...)

where

<modname> specifies the object module to be deleted from <libfile>.

The ISIS entry point is defined in a routine in SYSTEM.LIB that must be included in your program. Use LINK, specifying the name of your program followed by the name SYSTEM.LIB. See Chapter 4 for more information on LINK.

System call identifying numbers can be defined in EQUATE statements before they are referenced in your program. This allows you to reference these calls symbolically. Only the specific system calls needed by your program need be defined. The following table lists the identifying numbers for the system calls.

SYSTEM CALL	-	IDENTIFIE	R	•	J.	*	
				4			
OPEN		0		۲ ^۱	1 ^t		
CLOSE		1		1 11			
DELETE		2					
READ		3					
WRITE		4			*		
SEEK	. ;	5		. ,			
LOAD	<i>/ </i>	6	-4	,			
RENAME	~	7	•				
CONSOL		8			,		
EXIT		9	د.	3			
ATTRIB		10			Ś		
RESCAN		11,					
ERROR		12					
WHOCON		13	45 1			÷	
SPATH		14					
	r	• •		,			
		(*			,	
		•			ŕ	2	
ut Calls							

File Input/Output Calls

Six system calls are available to your program for controlling file input/output. These subroutines let you open files for read or write operations, move the pointer in an open file, and close the files when you're finished. These data transferring services of the supervisor transfer variable-length blocks of data between standard peripheral devices and a memory buffer area in your program. In addition to the data transfer buffer in your program area, the disk supervisor requires two 128- byte buffers for each open disk file. This buffer is located in the buffer area described in the memory layout in Memory Organization and Allocation. These calls establish and maintain the MARKER and LENGTH quantities associated with the file being operated upon.

System Calls Cautions

Since some ISIS-II system calls reference monitor routines, you should not mix monitor routine calls with system routine calls, or unpredictable results may occur.

When an interrupt occurs, the location of program execution is saved. If you issue a system call as part of an interrupt service routine, this location information will be lost, with unpredictable results.

ISIS-II references files by number (AFTN, or active file table number). Be careful not to confuse the AFTN with the PL/M construction .AFTN. The period (.) specifies the address where AFTN is stored.

Good programming practice suggests frequent STATUS checks when making frequent system calls. Refer to the TYPE program in Appendix D for an example of how status checks are used.

{

Program Overlays And Linked Loading

计外部通知 计算法

When a program is larger than the available memory space, it is necessary to link modules without combining them into one module. Thus during execution when part of the program is no longer needed, another part can be loaded in the same area of memory, overlaying the part not needed. Under ISIS-II, programs or parts of programs to be loaded separately must be in separate files. The first load can be done by entering the name of the file as a command. The subsequent loads are done from a program with the LOAD system call or an I/O routine.

In the typical use of LINK and LOCATE, modules with external references are combined with modules that have matching public symbols to produce a module with no unsatisfied external references. In linking without combining, the external references must still be satisfied; that is, they must know the addresses of their matching public symbols. Using the keyword PUBLICS before a list of modules tells LINK that the modules are not to be combined in the output module but used only to supply the addresses of their public symbols.

In this way the external references of modules listed earlier in the input list are satisfied. For example,

LINK A, PUBLICS(B,C) TO A.SAT

results in a module A.SAT whose external references to symbols contained in B and C are satisfied. However, modules B and C must be absolute modules because LINK must know the absolute addresses of the public symbols. Therefore the typical use of LINK before LOCATE is reversed. You must LOCATE modules B and C first, creating modules with absolute addresses but perhaps with unsatisfied external references. The module created in this way can be considered a temporary module used only to supply addresses of public symbols needed by other modules.

Consider the following example. A root segment calls segment A and later calls segment AA, then segment AAA overlays AA. A diagram of this overlay structure follows where the vertical lines indicate a division in time (segments A and B are not in memory at the same time) and the horizontal lines indicate a division in memory space.



306.2

4-20

Assembly Language OPEN Call Example

OPEN	EXTRN EQU	ISIS 0	;LINK TO ISIS ENTRY POINT ;SYSTEM CALL IDENTIFIER
	MVI LXI	C,OPEN D,OBLK	;LOAD IDENTIFIER ;ADDRESS OF PARAMETERS ,BLOCK
	CALL	ISIS	
	LDA ORA	OSTAT A	;TEST ERROR STATUS
	JNZ	EXCEPT	;BRANCH TO EXCEPTION , STATE ,
•			
•			
OBLK:			PARAMETER BLOCK FOR OPEN
	DW	OAFT	POINTER TO AFTN
	DW	OFILE	POINTER TO FILENAME
ACCESS:	DW	1	;ACCESS, READ = 1, WRITE = 2, ;UPDATE = 3
ECHO:	DW	0	;IF ECHO <> 0,
			;ECHO = AFTN OF
			;ECHO OUTPUT FILE
	DW	OSTAT	;POINTER TO STATUS
;			
OAFT:	DS	2	(AFIN (RETURNED)
USTAT:			STATUS (RETURNED)
OFILE:	DB	THUTHLEEXI	;FILE TO BE OPENED

READ - Transfer Data From File to Memory

- 1

The READ call transfers data from an open file to a specified memory location specified by the calling program. See "Line-Edited Input Files" for information concerning reading of line-edited files.

· · .

A parameter list of five variables must be passed with the READ call:

- The AFTN of a file that is open for input or update. The AFTN is returned by a preceding OPEN call or is 1 for :CI:.
- The address of a buffer to contain the data read from the open file. The buffer must be at least as long as the count described below. If the buffer is too short, the memory locations that follow the buffer will be overwritten.
- The number of bytes (count) to be transferred from the file to the buffer.
- The address of a memory location in which ISIS will store the actual number of bytes successfully transferred. The same number is added to MARKER. The actual number of bytes transferred is never more than the number specified in the count parameter, above. For line-edited files, the actual number of bytes is never more than the number of bytes in the line-edit buffer. When a file is not line edited, the number of bytes is equal either to count or to LENGTH minus MARKER, whichever is fewer. If COUNT = 0, then ACTUAL = 0 may or may not indicate end-of-file. End-of-file is best indicated, in the case of line-edited files and COUNT greater than 0, by ACTUAL = 0; in the case of line files and COUNT.
- The address of a memory location in which ISIS will store nonfatal error numbers. The error numbers returned by the READ call are listed in Appendix C.

zero and the addition of the low order portion of the segment base address causes a carry into the high order portion, that carry will not be detected when the HIGH operator is used. For example, if HIGH is used on the relocatable address 1234H:

11011(125411) = 1211	t * /		1- 1
	~	• *	

and LOCATE adds a segment base address of 10F0H:

WITH HIGH OPERATOR

1200H	1234H
+10F0H	+10F0H
22F0H	2324H
THE HIGH PART OF	THE HIGH PART OF
WHICH IS 22H	WHICH IS 23H

WITHOUT HIGH OPERATOR

Because LOCATE has no knowledge of the low order portion of the address there is a chance that the located HIGH address will be off by one. The located address will be correct if there is no carry from the low order portion.

You can avoid this situation by only using the HIGH operator on addresses in segments that you have defined as page relocatable.

This circumstance does not exist with the LOW operator. Addresses on which LOW has been used will always be correct.

Savings in memory space and execution time can result from this method, but access to some areas of memory may be lost because of the way LINK and LOCATE act to preserve relocation types.

When LINK combines segments having different relocation types, it follows these rules:

- Byte relocatable segments follow the preceding segment at the next byte. The output segment is byte relocatable only if all input segments are byte relocatable. Otherwise, it is page relocatable.
- Page relocatable segments follow the preceding segment at the first available page boundary. The bytes from the end of the preceding segment to the page boundary, if any, are unused. The output segment is page relocatable.
- Inpage relocatable segments are located at the first location following the preceding segment if they fit within the page. Otherwise, they are located at the next page boundary and the bytes at the end of the previous page are unused. The output segment is inpage relocatable only if it is not more than 256 bytes and all input segments are inpage relocatable. Otherwise, the output segment is page relocatable.

The bytes that are unused in the process of preserving the relocation type of segments are flagged in the LINK memory map by the word 'gap.' These gaps are unused portions of the program; in a sense they are lost.

If LOCATE assigns the base addresses of segments, it does so in a way that preserves the relocation type of the segment. It also issues a message if an inpage relocatable segment is changed to page relocatable. If you specify a base address for a segment with a segment location control that violates the relocation type of the segment, LOCATE places the segment on the next higher page boundary and issues a message. ti

1.01

· •

30

4-22

ď.

ŝ

- The number of bytes (count) to be transferred from the buffer to the output file. The value of the count is added to MARKER. If this results in MARKER being greater than LENGTH, then LENGTH is set equal to MARKER. The number of bytes actually transferred by WRITE is exactly equal to count. Thus if the buffer length is less than count, memory locations following buffer are written to the file.
- The address of the memory location for the return of nonfatal error numbers. The error numbers returned by WRITE are listed in Appendix C.

ŧ

۰. ۴

· /.

PL/M WRITE Call Example

WRITE:	
PROCEDURE (AFTN, BUFFER, COUNT, STATUS) EXTERNAL;	
END WRITE;	
	;
DECLARE AFT\$IN ADDRESS;	
DECLARE BUFFER(128) BYTE;	
DECLARE STATUS ADDRESS;	
	17
•	
• CALL M/DITE /0, ("this is an example of string literal", 0DH 0AH) 38 - STATUS)	
OALL WRITE (V, ((INSIS ALL CAMPLE OF SIMILY METAL, ODE, OAL), 30 , 30 (100)	,
GALL WHITE (AFTSIN, BUFFEN, 120, STATUS),	
IF STATUS < >UTHEN	

1

۶

Assembly Language WRITE Call Example

	EXTRN	ISIS	LINK TO ISIS ENTRY POINT
WRITE	EQU	4	SYSTEM CALL IDENTIFIER
	MVI	C,WRITE	;LOAD IDENTIFIER
	LXI	D,WBLK	;ADDRESS OF PARAMETER :BLOCK
	CALL	ISIS	7 · · · · · · · · · · · · · · · ·
Ŧ	LDA ORA	WSTAT A	;TEST ERROR STATUS
	JNZ	EXCEPT	;BRANCH TO EXCEPTION ' '
•		•	
•		, 4	ŗ
WBLK:		• * ,	(PARAMETER BLOCK FOR 5)
WAFT:	DS	2	:FILE AFTN
	DW	OBUF	ADDRESS OF OUTPUT BUFFER
WCNT:	DW	128	, [™] ,
	DW	WSTAT	;POINTER TO STATUS
i			•
WSTAT:	DS	2	;STATUS (RETURNED)
OBUF:	DS	128	;OUTPUT BUFFER
;			^و بال

The program area is above the buffer area. The program base address is determined by the programmer and assigned by LOCATE or entered in an ORG statement of 8080/8085 assembly language absolute programs.

The command interpreter (ISIS.CL1) of ISIS-II, other nonresident ISIS-II routines (all commands except DEBUG), the editor, assembler, compiler, linker, locater, and library manager run in the program area. Whenever you communicate with ISIS-II via console commands, you communicate with the nonresident command interpreter running in the program area.

Nonresident routines of ISIS-II may use all available RAM for buffers. Therefore, user programs that must be permanently resident should be placed in ROM or in RAM that is physically discontiguous from the first contiguous block of RAM.

The first 32K of memory must be RAM. Above 32K memory can be any combination of ROM and RAM. The Monitor MEMCK routine can be called if a program needs to know the highest location of contiguous RAM.

The Monitor occupies the top 2K of memory. If your memory configuration encompasses addresses F800H to FFFFH those addresses are shadowed by the Monitor ROM and cannot be written. The Monitor also uses the top 320 bytes of contiguous RAM for its workspace; this area is above the address returned by a call to the MEMCK routine.

The maximum area required for buffers under ISIS-II must be determined before deciding the base address of your program (see Chapter 4). The number of buffers varies dynamically, but the buffer area must be as large as the maximum number of buffers allocated simultaneously.

If you locate the base address of your program below 3180H (or allocate less than 3 buffers), an error message is generated.

The program base address can be calculated using the following formula:

12,288 + (128*N)

where N is the maximum number of buffers required simultaneously by the program. Use the following rules to determine N:

· • • •

- 1. Each open disk file requires two buffers until the file is closed.
- 2. An open line-edited file including :CI: requires one buffer until the file is closed. For a disk file, this buffer is in addition to the two required in rule 1.
- 3. A system call that accesses a disk directory (LOAD, DELETE, RENAME, ATTRIB, CONSOL when it specifies a disk file) requires two buffers during the processing of the call. The buffers are released on return to the calling program.
- 4. When the CONSOL system call assigns the console input or output device to a disk file, three buffers are required for the console input file and two buffers are required for the console output file. These buffers are required until end-of-file. A program called by a system command in a SUBMIT file must also allow for these buffers in determining its origin point.

Example 1: A program that has no system calls, does not assign the console to a disk file, and is not called by a command in a disk file, needs three buffers. Therefore it can have a base address of 3180H. If the program is changed to open one disk file, it needs five buffers; the base address must be 3280H:

3000H + (128*5) = 3280H

If the file is open for update and the specified action would place the marker beyond the end of the file, ASCII nulls (00HH) are added to the file to extend the file to the marker. (Thus, LENGTH becomes equal to MARKER.)

If the extension of a file by the SEEK operation causes an overflow on the disk, a fatal error is reported, either during the execution of the SEEK call or when a program tries to write into the extended area of the file. This error can become evident at any time in the life of the file.

If an attempt is made to extend a file that is open only for input, the marker is set to the former end-of-file, and a non-fatal error occurs.

Move Marker to End of File

If the mode value is 4, the marker is moved to the end of the file. Block and byte parameters are ignored.

The other three variables that must be passed with the SEEK call are:

• •,

- The address of a memory location containing a 2-byte value used for the block number. A block is equivalent to 128 bytes, the same as a sector on the disk.
- The address of a memory location containing a 2-byte value used for the byte number. The byte number may be greater than 128.
- The address of a memory location in which ISIS will store nonfatal error numbers. The error numbers returned by the SEEK call are listed in Appendix C.

If MARKER has allocated more memory than LENGTH requires, a DIR will show the allocated location as in use. You can actually allocate more storage than exists on disk in this way. Data can still be written to these locations.

۰,

י א י . .

PL/M Seek Call Example

SEEK

ł

PROCEDURE (AFTN, MODE, BLOCKNO, BYTENO, STATUS) EXTERNAL; ** 1 16 . 19 DECLARE (AFTN, MODE, BLOCKNO, BYTENO, STATUS) ADDRESS, 54 . 235

END SEEK,	K. M. PERKING	۲
	D 31.4 AFTN, 41	
	,	**
DECLARE AFT\$IN ADDRESS,		
DECLARE BLOCKNO ADDRESS,		
DECLARE BYTENO ADDRESS,	- 3. 1	
DECLARE STATUS ADDRESS,		
	- 1	
CALL SEEK (AFT\$IN,0, BLOCKNO, BYTENO, STA	ATUS),	1,

IF STATUS <>0 THEN

If the READ system call requests 100 bytes and the line-editing buffer contains 50, only 50 bytes are transferred.

When all the characters in the line-editing buffer have been read, the buffer pointer is positioned after the last character. However, the buffer is not cleared yet. In fact, the RESCAN system call can be used to reposition the buffer pointer to the beginning of the line-editing buffer so subsequent READ system calls can reread the contents of the buffer.

When the contents of the line-editing buffer have been completely read (the pointer is after the last character), a READ system call transfers new input from the lineedited file into the line-editing buffer. When the line is terminated, the number of characters requested by READ are transferred to the program.

. 4. 1. 54 .

Editing Characters

The following characters are used to edit the input of a line-edited file. Control characters are entered by holding down the control key (CTRL) while the character is typed.

pea.

.'

- RUBOUT Pressing RUBOUT deletes the preceding character from the buffer.
- CONTROL/P A CONTROL/P causes the next character typed to be entered literally in the line-editing buffer. Use control-P when you want an editing character or terminating character entered in the buffer rather than causing its usual editing or terminating function.
- CONTROL/R A CONTROL/R has no effect except its echo, which is carriage return-line feed, followed by the current undeleted contents of the buffer.
- CONTROL/X CONTROL/X causes the entire contents of the buffer to be deleted, including itself. It is echoed as a #, carriage return, line feed.
- CONTROL/Z CONTROL/Z is the only way to indicate end-of-file from a keyboard input device. It acts like control-X except that it has no echo and it causes the READ system call to return immediately without transferring any characters, thus simulating an end-of-file. If more characters are entered after the control-Z, they are entered in the line-editing buffer and can be read by a subsequent READ system call.

Reading a Command Line

Reading a command line from the console input device is a special case of reading a line-edited file.

When a command is entered at the console, it is collected by ISIS-II in the lineediting buffer for :CI: and is not available to the command interpreter (a nonresident ISIS-II routine) until it is terminated. The command interpreter reads only the command name and then calls the program with that name, leaving the line-editing buffer pointer positioned after the command name. The loaded program can issue a READ, which transfers data starting with the first parameter, or the program can issue a RESCAN to position the pointer to the beginning of the buffer so it can read the command name.

ĩ

دل 1

, , *†* '

Assembly Language RESCAN Call Example

RESCAN	EXTRN EQU	ISIS 11	LINK TO ISIS ENTRY POINT SYSTEM CALL IDENTIFIER
	MVI LXI	C,RESCAN D,IBLK	,LOAD IDENTIFIER ;ADDRESS OF PARAMETER .BLOCK
	CALL	ISIS	,
	LDA ORA	ISTAT A	;TEST ERROR STATUS
	JNZ	EXCEPT	, BRANCH TO EXCEPTION , ROUTINE
IBLK:		,	,PARAMETER BLOCK FOR BESCAN
IAFŤ:	DS DW	2 ISTAT	,AFTN FROM OPEN ;POINTER TO STATUS
•			
ISTAT:	DS	2	;STATUS (RETURNED)
;			the france of the

CLOSE - Terminate Input/Output Operations on a File

The CLOSE call removes a file from the system input/output tables and releases the buffers allocated for it by OPEN. All files should be closed when input/output processing is complete. If the file closed is a paper tape punch device (:HP: or :TP:) 12 inches of trailer (ASCII null characters) are punched.

A parameter list of two variables must be passed with the CLOSE call:

- The AFTN of the file to be closed. The AFTN was returned by a preceding OPEN call.
- The address of a memory location for the return of nonfatal error numbers. The nonfatal error numbers issued by CLOSE are listed in Appendix C.

1. . 1

۱

PL/M CLOSE Call Example

.

CLOSE: PROCEDURE (AFTN, STATUS) EXTERNAL; DECLARE (AFTN, STATUS) ADDRESS; END CLOSE;

DECLARE AFT\$IN ADDRESS; DECLARE STATUS ADDRESS;

CALL CLOSE (AFT\$IN,.STATUS); IF STATUS <> 0 THEN

5-15

- Monitor I/O routines for control of peripheral devices (CI, CO, RI, PO, LO, UI, UO).
- Monitor status routines for peripheral devices (CSTS, UPPS, IOCHK, IOSET, MEMCHK).

The interface to these services is a call to ISIS-II that specifies the services desired and the address of the parameter list the supervisor is to access. The specific calling sequences are described with the call descriptions. Note that an ISIS-II call uses your stack. Your stack must have the depth necessary to handle the call. A call to ISIS-II destroys the contents of the CPU registers.

The system calls are described in terms of their operation and the parameters your program must supply.

To clarify the effect of certain system calls on your files, two integer quantities, LENGTH and MARKER, are associated with each file in this description. LENGTH is the number of bytes in the file. MARKER is the number of bytes already read or written in the file (that is, it acts as a file pointer).

System Call Syntax and Usage

Many of the ISIS-II system calls have names and functions similar to those of the ISIS-II commands previously discussed. This is true because use of ISIS-II by another program is essentially the same as your use of ISIS-II when seated at the console.

The ISIS-II system calls can be called from your PL/M or Assembler Language programs. If your program does make an ISIS-II system call, you must remember to link your object program with SYSTEM.LIB using the LINK program.

SYSTEM.LIB is a library file supplied with your system disk. It contains the procedures necessary to interface your programs containing ISIS-II system calls with the ISIS-II system.

, **1**

PL/M Calls

Your PL/M program can interface to ISIS by performing calls to procedures in SYSTEM.LIB. Your program must include external procedure declarations so the proper procedures in SYSTEM.LIB will be included with your program by LINK. These external procedure declarations may be declared as type address, but may also be values as well as addresses of values.

Assembler Language Calls

The interface between the 8080/8085 Assembler Language program and ISIS is accomplished by calling a single ISIS entry point (labeled ISIS) and passing two parameters. The first parameter is a number that identifies the system call; the second is the address of a control block that contains the additional parameters required by the system call. The first parameter is passed in register C and the address of the control block is passed in the register pair DE. The entry point must be defined in your program as an external:

Le t c et

5.

EXTRN ISIS
<u>،</u> ۲

11

1

T

1

13 - high speed paper tape reader	
14 - user reader 1	
15 - user reader 2	
16 - teletype paper tape punch (teletype)	•
17 - high speed paper tape punch	
18 - user punch 1	
19 - user punch 2 · · ·	
20 - line printer	t da
21 - user list 1	
22 - byte bucket (a pseudo input/output device)	<i>r</i> ,
23 - console input	
24 - console output	
25 - disk drive 6	
26 - disk drive 7	
27 - disk drive 8	
28 - disk drive 9	

The file name and extension are the ISIS file name.

The device type specifies the type of peripheral with which the file is associated. The possible values for this field are:

- 0 sequential input device
- 1 sequential output device
- 2 sequential input/output device
- 3 random access input/output device

The drive type field specifies the type of drive controller if the device type field is 3. If the device type is anything except 3, the drive type is undefined. The possible values for a device type of 3 are:

0 - controller not present	er an area de géneration a co
2 - two-board single density	the state of the state
3 - integrated single density	わかか 在来り こい
4 - two-board hard disk	, + mi rlearia i · ·

• The address of a memory location for the return of a nonfatal error number. The nonfatal error numbers issued by the SPATH call are listed in Appendix C.

	-	1 C 2417 4	4	و می د	- 4
	n		7.	30 IV	٦
PL/M SPATH Call Example	·	١		*	
SPATH PROCEDURE (FILE,BUFFER,S DECLARE (FILE,BUFFER,S	TATUS) STATUS)	EXTERNAL; ADDRESS,	•	•	, .
END SPATH;			3	,	
			0		÷
		, ir 3.	۲ ,		ł
DECLARE FILENAM(15) BYTE; DECLARE BUF\$IN(12) BYTE, DECLARE STATUS ADDBESS	77	``	·• t	2 L	Ţ
			•	· · ·	4
					3.
CALL SPATH(FILENAM, .BUF\$IN IF STATUS <> 0 THEN	N, STATI	JS);	'	ر اندر د ر اندر د •	. v:

OPEN - Initialize File for Input/Output Operations

The OPEN call initializes ISIS tables and allocates buffers that are required for input/output processing of the specified file. If the specified file is a punch device (:HP: or :TP:), 12 inches of leader (ASCII nulls) are punched.

A parameter list of five variables must be passed with the OPEN call:

- An address of a two byte field in which ISIS will store the active file number (AFTN) of the file that is opened. Your program will use this value for other calls relative to this file. :CI: and :CO: are always open and have the AFTNs 1 and 0 permanently assigned. Excluding :CI: and :CO:, you can only have six files open at any one time. Be careful not to confuse AFTN with the PL/M construction .AFTN. The period prefacing .AFTN signifies the location in memory of AFTN.
- The address of the ASCII string containing the name of the file to be opened. The ASCII string can contain leading space characters but no embedded space characters. It must be terminated by a character other than a letter, digit, colon (:), or period (.). A space can be used.
- A value indicating the access mode for which the file is being opened. A value of 1 specifies that the file is open only for input to the system (READ). A value of 2 specifies that the file is open only for output from the system (WRITE). A value of 3 specifies that the file is open for update, READ and WRITE. When a file is opened for input, MARKER is set to 0 and LENGTH is unchanged. If the file specified for input is nonexistent, a nonfatal error occurs. When a file is opened for output, MARKER and LENGTH are set to 0. If the file specified for output is nonexistent, a disk file is created with the specified filename and all attributes of the new file are reset. Specifying a disk file whose format or write-protect attributes are set causes a nonfatal error. When a file is opened for update, MARKER is set to 0. If the file already exists, LENGTH is unchanged. If the file is nonexistent, a file is created with the specified filename and all attributes reset. LENGTH is set to 0. Opening a file for an access mode that is not physically possible causes a nonfatal error. For example, opening :HP: (highspeed paper tape punch) for input or opening :LP: (line printer) for update causes an error.
- The AFTN of the echo file if the file is to be opened for line editing. The echo file must be previously opened for output (ACCESS=2). The AFTN of the echo file is passed in the least significant byte of the field. If this field contains 0, no line editing is done. To specify an AFTN of 0 for :CO:, a nonzero value must be in the most significant byte and zero in the least significant byte. For example, FF00H specifies the AFTN for the :CO: device.
- The address of a memory location for the return of nonfatal error numbers. The error numbers that OPEN can return are listed in Appendix C.

2

m gent

OPEN PROCEDURE (AFT DECLARE (AFTN	NPTR,FILE,ACC	ESS,MODE,S SS,MODE,ST	TATUS) EX ATUS) ADI	(TERNA DRESS,	L, .,	
CNU OFEN,		۲ <u>۱</u>	ł	÷.	· ,	. *
	s * 14	1 22	•		,£	۲. ۲.
DECLARE AFT\$IN DECLARE FILENAN DECLARE STATUS	ADDRESS, ME(15) BYTE DA ADDRESS,	TA (''F1'MYPF -	log SRC');	; •	، در. ر ۱۰۰۰	; ; ;
CALL OPEN(AFT\$IN IF STATUS < > 0 THE	,.FILENAME,1,0 N .	, STATUS);		· • •		; ; , , ,

PL/M OPEN Call Example

. .

DECLARE FILENAM(20) BYTE; DECLARE STATUS ADDRESS;

CALL DELETE (FILENAM, .STATUS); IF STATUS <> 0 THEN ..

Assembly Language DELETE Call Example

DELETE	EXTRN EQU	ISIS 2	;LINK TO ISIS ENTRY POINT ;SYSTEM CALL IDENTIFIER
ı	MVI LXI	C,DELETE D,DBLK	;LOAD IDENTIFIER ;ADDRESS OF PARAMETER ;BLOCK
	CALL LDA OBA	ISIS DSTAT	;TEST ERROR STATUS
	JNZ	ÊXCEPT	;BRANCH TO EXCEPTION ;ROUTINE
•			
DBLK:	DW DW	DFILE DSTAT	;PARAMETER BLOCK FOR ;DELETE ;POINTER TO FILENAME ;POINTER TO STATUS
, DSTAT: DFILE: ;	DS DB	2 'FILE.EXT	;STATUS (RETURNED) ';NAME OF FILE TO BE DELETED

RENAME - Change Disk Filename

The RENAME call allows your program to change the name of a disk file.

A parameter list of three variables must be passed with the RENAME call:

- The address of an ASCII string that contains the old file name. The string can contain leading spaces but no embedded spaces. It must be terminated by a character other than a letter, digit, colon (:), or period (.). You can use a space.
- The address of an ASCII string that contains the new file name. The string can contain leading spaces but no embedded spaces. It must be terminated by a character other than a letter, digit, colon (:), or period (.). You can use a space. The device portion of the name must be the same as that in old name.
- The address of a memory location for the return of a nonfatal error number. The nonfatal error numbers issued by RENAME are listed in Appendix C.

PL/M READ Call Example

Assembly Language READ Call Example

	EXTRN	ISIS	LINK TO ISIS ENTRY POINT	
READ	EQU	3	SYSTEM CALL IDENTIFIER	
	MVI	C.BEAD	LOAD IDENTIFIER	
	I XI	D.BBLK	ADDRESS OF PARAMETER	
		2,	BLOCK	
	CALL	ISIS		
	LDA	RSTAT	,TEST ERROR STATUS	
	ORA	Α		
	JNZ	EXCEPT	BRANCH TO EXCEPTION	
			ROUTINE	
		,	* <i>•</i>	
•				
•			·	
RBLK	_		PARAMETER BLOCK FOR READ	
RAFT.	DS	2	;FILE AFTN	
	DW	IBUF	,ADDRESS OF INPUT BUFFER	
RCNT:	DW	128	,LENGTH OF READ REQUESTED	
	DW	ACTUAL	,POINTER TO ACTUAL	
	DW	RSTAT	;POINTER TO STATUS	
;				
ACTUAL:	DS	2	COUNT OF BYTES READ	
			,(RETURNED)	
RSTAT:	DS	2	(STATUS (RETURNED)	
IBUF:	DS	128	;INPUT BUFFER	
;			. , `	
			. **	

WRITE - Transfer Data From Memory to File

The WRITE call transfers data from a specified location in memory called a buffer to an open file. A parameter list of four variables must be passed with the WRITE call:

- The AFTN of a file open for output or update. The AFTN was returned by a preceding OPEN call or is 0 for :CO:.
- The address of the memory location of the buffer from which data is to be transferred, or a string literal of the format *.string literal*, where the period (.) specifies the contents of the string buffer labeled *.string literal*.

12

- .1

1174

;;

- An identifier indicating which attribute is to be changed. The identifier can be:
 - 0 invisible attribute
 - 1 system attribute
 - 2 write protect attribute
 - 3 format attribute
- A value indicating whether the attribute is to be set (turned on) or reset (turned off). The value is stored in the low order bit of the low order byte. A value of 1 specifies that the attribute be set and a value of 0 specifies that it be reset.
- The address of a memory location for the return of a nonfatal error number. The nonfatal error numbers issued by the ATTRIB call are listed in Appendix C.

PL/M ATTRIB Call Example

1.7

Assembly Language ATTRIB Call Example

;

EXTRN ISIS ;LINK TO ISIS ENTRY POINT ATTRIB EQU 10 **,SYSTEM CALL IDENTIFIER** MVI C,ATTRIB ;LOAD IDENTIFIER LXL D,ABLK ;LOAD PARAM ADDR CALL ISIS LDA ASTAT ,TEST ERROR STATUS ORA А JNŻ EXCEPT ;BRANCH TO EXCEPTION ,ROUTINE ABLK: ;PARAMETER BLOCK FOR ATTRIB DW FILEN ;POINTER TO FILE NAME DW 2 :ATTRIBUTE IDENTIFIER DW 0 :SET/RESET SWITCH DW ASTAT ;POINTER TO STATUS **FILEN** DS 15 ;FILE NAME FIELD ASTAT: DS 2 **STATUS (RETURNED)**

SEEK - Position Disk File Marker

The SEEK call allows your program to find the location of or to change the value of MARKER associated with a disk file open for read or update. The SEEK call can only be used with a file open for update or read. The MARKER can be changed in four ways: moved forward, moved backward, moved to a specific location, or moved to the end of the file. A nonfatal error occurs if SEEK is issued for a file opened for output.

A parameter list of five variables must be passed with the SEEK call:

- The AFTN of a disk file opened for update or input. The AFTN was returned by a preceding OPEN call.
- A mode value from 0 through 4 that indicates what action should be performed on the MARKER. The block and byte parameters (see below) are used to represent the current MARKER position or to calculate the desired offset.

Return Marker Location

If the mode value is 0, the system returns a pair of block and byte values that signify the current position of the marker. For example, if the marker is just beyond the first block of the file, the system might return the numbers 1 and 0 in the addresses assigned to block and byte, respectively. It might also return the numbers 0 and 128, which point to the same byte in the file. The value of MARKER is given by the following equation:

MARKER = 128 * (block number MODULO 32768) + byte number

Move Marker Backward

If the mode value is 1, the marker is moved backward, toward the beginning of the file. The block and byte parameters determine the offset; for example, if block is equal to 0 and byte is equal to 382, the marker is moved backward 382 bytes. To define an offset of N, use block and byte values such that

N = 128 * (block number MODULO 32768) + byte number

If N is greater than MARKER, i.e., if the prescribed action would place the marker before the beginning of the file, MARKER is set to 0 (beginning of file), and a non-fatal error occurs.

Move Marker to Specific Location

If the mode value is 2, the marker is moved to a specific position in the file. The block and byte parameters define the position; for example, if block is equal to 27 and byte is equal to 63, the marker will be moved to block 27, byte 63. Similarly, if both block and byte are equal to 0, the marker is moved to the beginning of the file. If the file is open for update and the prescribed action would place the marker beyond the end of the file, ASCII nulls (00HH) are added to the file to extend the file to the marker. (Thus, LENGTH becomes equal to MARKER.)

Move Marker Forward

If the mode value is 3, the marker is moved forward, toward the end of the file. The block and byte parameters define the offset N, according to the following equation:

N + 128 * (block number MODULO 32768) + byte number

	LHLD PUSH POP	STATP H D GETATT	;STATUS
	LDA ORA	GSTAT	;TEST ERROR STATUS
;	JNZ	EXCEPT	BRANCH TO EXCEPTION
FILEP:	DW	GFILE	POINTER TO FILE
ATTP:	DW	ATTRIB	,POINTER TO ATTRIBUTE
STATP.	DW	GSTAT	, POINTER TO STATUS
; GFILE:	DB	':F0:FILE.EXT'	;FILE PATHNAME
ATTRIB:	DS	1	;ATTRIBUTE VALUE ;(RETURNED)
GSTAT:	DS	2 7 5 16	STATUS (RETURNED)

GETD—Obtain File Device Directory

The GETD call allows your program to access information in a file device directory. Six parameters must be passed in the GETD call:

- The address variable containing the number for the directory from which entries are to be returned. Valid integer values are 0-9, representing :F0:-:F9:, respectively.
- A pointer to an address value which must be initialized to zero when the first display request of a sequence is made. Changing this value will cause an error. The system assigns a value to this word which is returned in subsequent requests for directory entries and acts as a pseudo-connection for subsequent calls.
- An address value which contains the number of entries to be returned. A value of 0 terminates the current display request sequence and releases the pseudo-connection. The program must make a final call to GETD with count = 0 to release the connection unless it is automatically released.
- A pointer to the address value containing the number of directory entries returned by the system. When this number is less than the number of entries requested, the last directory entry has already been returned and the pseudo-connection will be automatically released.
- A pointer to the memory structure where directory entries are returned. The structure form is:

DECLARE ENTRY ST	RUCTU	IRE(
RESERVED1 FILE\$NAME RESERVED2	(1) (9) (6)	BYTE, BYTE, BYTE);	ţ	- · Jr. -

where

r

FILE\$NAME is a 9-byte field with two subfields left-justified and zerofilled. The first 6 bytes represent the name and the remaining 3 bytes are the file extension.

Assembly Language SEEK Call Example

SEEK	EXTRN EQU	ISIS 5	;LINK TO ISIS ENTRY POINT ,SYSTEM CALL IDENTIFIER	,
к к I к	MVI LXI	C,SEEK D,SBLK	;LOAD IDENTIFIER ,ADDRESS OF PARAMETER ,BLOCK]4
		ISIS SSTAT A	TEST ERROR STATUS	
	JNZ	EXCEPT	;BRANCH TO EXCEPTION ;ROUTINE	ı
• •			· · · ·	
SBLK: SAFT	DS	2	,PARAMETER BLOCK FOR SEI ;AFTN FROM OPEN	EK
MODE:	DS DW DW	2 BLKS NBYTE	;TYPE OF SEEK ,POINTER TO BLKS ,POINTER TO NBYTE	
;	DW	SSTAT	POINTER TO STATUS	
BLKS: NBYTE SSTAT.	DS DS DS	2 2 , 2	NUMBER OF SECTORS TO SK NUMBER OF BYTES TO SKIP STATUS (RETURNED)	"b
:			د	

RESCAN - Position MARKER to Beginning of Line

The RESCAN call is used on line-edited files only. It allows your program to move the MARKER to the beginning of a logical line that has already been read. Thus the next READ call starts at the beginning of the last logical line read. This line is not echoed (output to the echo file), it has already been input from the keyboard and echoed. Thus the subsequent READ does no input from a file but only reads from a buffer in memory.

A parameter list of two variables must be passed with the RESCAN call:

. .

- The AFTN of a file open for line-edited input (echo file AFTN specified) by a preceding OPEN call.
- The address of a memory location for the return of nonfatal error numbers. The error numbers returned by the RESCAN call are listed in Appendix C.

1.7

ŧ+ .,

3

. 1.

PL/M RESCAN Call Example

```
RESCAN

PROCEDURE (AFTN, STATUS) EXTERNAL,

DECLARE (AFTN, STATUS) ADDRESS;

END RESCAN;

.

DECLARE AFT$IN ADDRESS;

DECLARE STATUS ADDRESS;

.

.

.

CALL RESCAN (AFT$IN, .STATUS);

IF STATUS <>0 THEN ...
```

	LHLD PUSH POP	GSTAT H D	;STATUS
	CALL LDA ORA	GETD DSTAT A	;TEST ERROR STATUS
	JNZ	EXCEPT	BRANCH TO EXCEPTION
;			· · · · ·
; DID.	DW	1	DIRECTORY IDENTIFIER FOR 'F1:
CONN:	DW	0	DIRECTORY CONNECTION
COUNT:	DW	8	ENTRY COUNT
ACTP:	DW	DACT	,POINTER TO ACTUAL
BUFFP:	DW	DBUF	,POINTER TO BUFFER
GSTAT:	DW	DSTAT	;POINTER TO STATUS
DACT.	DS	2	;COUNT OF ENTRIES READ ;(RETURNED)
DBUF:	DS	128	;DIRECTORY BUFFER
DSTAT:	DS	2	;STATUS (RETURNED)
;			

Console Reassignment and Error Message Output

Three system calls are available to your program for system console control. These system calls allow you to change the device used as the system console, to determine which device is the current console, and, if needed, to send an error message to the console.

CONSOL - Change Console Device

.

£

The CONSOL call allows your program to change the console input and output devices (:CI: and :CO:) to devices other than the initial system console.

A parameter list of three variables must be passed with the CONSOL call:

- The address of an ASCII string that contains the name of the file to be used for system console input. The string can contain leading spaces but no embedded spaces. It must be terminated by a character other than a letter, digit, colon (:), or period (.). You can use a space. Before opening the new file, the file is closed unless it happens to be :CI: which is always open. If the specified file cannot be opened, a fatal error occurs. Do not use SUBMIT to run programs which contain CONSOL calls which change the console input device name.
- The address of an ASCII string that contains the name of the file to be used for system console output. The string can contain leading spaces but no embedded spaces. It must be terminated by a character other than a letter, digit, colon (:) or period (.). You can use a space. Before opening the new file, the current output file is closed unless it happens to be :CO: which is never closed. If the specified file cannot be opened, a fatal error occurs.
- The address of a memory location for the return of a nonfatal error number. The nonfatal error numbers issued by the CONSOL call are listed in Appendix C.

15 . 11 .

7

Assembly Language CLOSE Call Example

CLOSE	EXTRN EQU	ISIS 1	;LINK TO ISIS ENTRY POINT ;SYSTEM CALL IDENTIFIER	ન કર્સ
	MVI LXI	C,CLOSE D,CBLK	, LOAD IDENTIFIER , ADDRESS OF PARAMETER ; BLOCK	
	CALL LDA ORA	ISIS CSTAT A	, TEST ERROR STATUS	
	JNZ	EXCEPT	;BRANCH TO EXCEPTION ,ROUTINE	
; CBLK:			, PARAMETER BLOCK FOR .CLOSE	
CAFT:	DS DW	2 CSTAT	,FILE AFTN ,POINTER TO STATUS	~ <u>p</u> ù
; CSTAT [.] ;	DS	2 • *	;STATUS (RETURNED)	-
	1 7 .	J1		

SPATH - Obtain File Information

The SPATH call allows your program to obtain information relating to a specified file. The information returned by this call includes the device number, file name and extension, device type, and if a disk file, the drive type.

A parameter list of three variables must be passed with the SPATH call:

- The address of an ASCII string containing the name of the file for which ٠ information is requested. The string can contain leading spaces but no embedded spaces. It must be terminated by a character other than a letter, digit, colon (:), or period (.). A space can be used.
- . The address of a 12-byte memory location in which the system will return the information. After the call is completed, the buffer will contain the following information: . 115 . ۰.

Byte 0 - Device number	*).' ·· , · 'gu
Bytes 1 through 6 - file name	
Bytes 7 through 9 - file name extension	a 1
Byte 10 - Device type	
Byte 11 - Drive type	1737 , Utaren a Madd are
The possible values for device number are:	「「「」」 こうがけ ・+ とりょう
0 - disk drive 0 1 - disk drive 1 2 - disk drive 2 3 - disk drive 3	· ·
4 - disk drive 4 5 - disk drive 5 6 - teletype input 7 - teletype output	
8 - CRT input 9 - CRT output	and the strategy of the second s
10 - user console input 11 - user console output 12 - teletype paper tape reader	

ł

· · · · ·

PL/M WHOCON Call Example

WHOCON: PROCEDURE (AFTN,BUFFER) EXTERNAL; DECLARE (AFTN,BUFFER) ADDRESS; END WHOCON,	ι.	ł	
DECLARE BUFF\$IN(15) BYTE;			
CALL WHOCON (1,.BUFF\$IN);			

Assembly Language WHOCON Call Example

	EXTRN	ISIS	
WHOCON	EQU	13	CALL IDENTIFIER
;			
	MVI	C,WHOCON	;LOAD IDENTIFIER
	LXI	D,WBLK	;LOAD PARAM ADDR
	CALL	ISIS	
,			
WBLK:			
AFTN:	DS	2	AFTN FOR IN OR OUT
	DW	BUFIN	,POINTER TO BUFFER
	DW	STATUS	POINTER TO STATUS RETURN
;			
BUFIN	DS	15	BUFFER FOR RETURN
			FILE NAME
STATUS:	DS	2	STATUS RETURN
;			
		,	ز
			· ,

ERROR - Output Error Message on System Console

The ERROR call enables your program to send an error message to the initial system console.

A parameter list of two variables must be passed with the ERROR call:

- The error number to output to the console. The error number must be in the low order eight bits of the parameter. Only the numbers 101 through 199 inclusive should be used for user programs; the other numbers (0-100 and 200-255) are reserved for system programs. The system displays the error in the following format: ERROR nnn, USER PC mmmm where nnn is the error number specified in the call and mmmm is the return address in the calling program.
- (Assembly language only) The address of a memory location for return of an error number.

Semoly Lang		Cun Example		
	EXTRN	ISIS	LINK TO ISIS ENTRY POIN	Т
SPATH	EQU	14	SYSTEM CALL IDENTIFIEF	1
;				
	MVI	C,SPATH	;LOAD IDENTIFIER	
	LXI	D,SBLK	,LOAD PARAM ADDR	
	CALL	ISIS		هه د ۲
	LDA	SSTAT	TEST ERROR STATUS	-
	OHA	A		F,
	JNZ	EXCEPT	;BHANCH TO EXCEPTION ;ROUTINE	
				<i>₹</i> #1,
•			,	<u>``-</u>
				× ~~
SBLK:			,PARAMETER BLOCK FOR ,SPATH	3
	DW	FILEN	, POINTER TO FILE NAME	* 1
	DW	BUFIN	,POINTER TO BUFFER	
	DW	SSTAT	;POINTER TO STATUS	**
;	50	45		·
FILEN	D5	10		
BUFIN.	DS	12	BUFFERFORDATA	
SSIAI.	05	2	(STATUS (RETURNED)	
;			s # 1	1
			, 1 5 €x‡ ₹	9711
		1		*b -
			\$	• • 11

Assembly Language SPATH Call Example

Disk Directory Maintenance



Five system calls are available to your program for changing and accessing information in the disk directory. These calls allow you to delete a disk file, rename a disk file, change the attributes of a disk file, and obtain attribute and directory information about a disk file.

ه و ورو بر م ور ژ. و و هر می مدی

DELETE - Delete a File from the Disk Directory

The DELETE call removes a specified file from its disk. The space allocated to the file is released. The space can then be reused for another file.

A parameter list of two variables must be passed with the DELETE call:

- The address of an ASCII string that specifies the name of the file to be deleted. The file to be deleted must not be open. The string can contain leading space characters but no embedded spaces. It must be terminated by a character other than a letter, digit, colon (:), or period (.). You can use a space.
- The address of a memory location for the return of a nonfatal error number. The error numbers returned by DELETE are listed in Appendix C.

PL/M DELETE Call Example

```
DELETE:
PROCEDURE (FILE,STATUS) EXTERNAL;
DECLARE (FILE,STATUS) ADDRESS;
END DELETE,
```

· · · · · ·

.

124.5

NOTE

When control passes to the Monitor, the Monitor saves the CPU registers and system status by pushing these items on the stack belonging to the program that issued the LOAD system call. If the newly loaded program overlays the area formerly occupied by the stack, it will be overwritten when the Monitor pushes items on the stack. Therefore, the stack should be located in an area of memory that will not cause the newly loaded program to be overwritten when the Monitor uses the stack.

- The address of a memory location for the return of the loaded program entry point address when the control value is zero. The entry point is obtained from the loaded program. A zero is returned if the program is not a main program.
- The address of a memory location for the return of a nonfatal error number. The error numbers issued by the LOAD call are listed in Appendix C.

PL/M LOAD Call Example

LOAD[,] PROCEDURE (FILE,BIAS,SWITCH,ENTRY,STATUS) EXTERNAL; DECLARE (FILE,BIAS,SWITCH,ENTRY,STATUS) ADDRESS; END LOAD;

DECLARE FILNAM(15) BYTE; DECLARE ENTRY ADDRESS; DECLARE STATUS ADDRESS;

CALL LOAD (.FILNAM,0,1, ENTRY, STATUS); IF STATUS <> 0 THEN .

• • • • •

Assembly Language LOAD Call Example

EXTRN	ISIS	
EQU	6	;CALL IDENTIFIER
KA)/I	C 1 O 4 D	
INEVI	C,LUAU	,LOAD IDENTIFIER
LXI	D,LBLK	;LOAD PARAM ADDR
CALL	ISIS	
LDA	LSTAT	;TEST ERROR STATUS
ORA	Α	
JNZ	EXCEPT	;BRANCH IF ERROR
		• • •
		فالعاد وساف
DW	FILNAM	;POINTER TO FILE NAME
DS	2	,BIAS FIELD
DS	2	CONTROL SWITCH
DW	ENAD	POINTER TO ENTRY ADDRESS
DW	LSTAT	;POINTER TO STATUS
DS	15	;FILE NAME FIELD
DS	2	ENTRY POINT ADDR (RETURN)
	2	STATUS (RETURNED)
00	-	, or an object of all by
	EXTRN EQU MVI LXI CALL LDA ORA JNZ DW DS DS DS DS DS DS DS DS DS DS	EXTRN ISIS EQU 6 MVI C,LOAD LXI D,LBLK CALL ISIS LDA LSTAT ORA A JNZ EXCEPT DW FILNAM DS 2 DS 2 DW ENAD DW LSTAT DS 15 DS 2 DS 2 DS 2

PL/M RENAME Example

```
RENAME:

PROCEDURE (OLDFILE,NEWFILE,STATUS) EXTERNAL;

DECLARE (OLDFILE,NEWFILE,STATUS) ADDRESS;

END RENAME;

.

DECLARE OFILE(20) BYTE;

DECLARE OFILE(20) BYTE;

DECLARE NFILE(20) BYTE;

DECLARE STATUS ADDRESS;

.

.

.

CALL RENAME (.OFILE, NFILE,.STATUS);

IF STATUS <>0 THEN .
```

Assembly Language RENAME Call Example

	EXTRN	ISIS	LINK TO ISIS ENTRY POINT;
RENAME	EQU	7	;SYSTEM CALL IDENTIFIER
i			
	LXI	D,NBLK	,ADDRESS OF PARAMETER BLOCK
	CALL	ISIS	, = = = = : :
	LDA ORA	NSTAT A	;TEST ERROR STATUS
	JNZ	EXCEPT	;BRANCH TO EXCEPTION ;ROUTINE
•	•		
•			-
NBLK:			;PARAMETER BLOCK FOR .BENAME
	DW	FILE2	POINTER TO OLD FILENAME
	DW	FILE1	POINTER TO NEW FILENAME
	DW	NSTAT	POINTER TO STATUS
;			
NSTAT:	DS	2	(STATUS (RETURNED)
FILE1:	DB	'FILE.NEW	;NEW NAME OF FILE
HILE2:	DB	'FILE.OLD '	OLD NAME OF FILE

ATTRIB - Change the Attributes of a Disk File

The ATTRIB call allows your program to change an attribute of a disk file.

A parameter list of four variables must be passed with the ATTRIB call:

• The address of an ASCII string containing the name of the file whose attribute is to be changed. The string can contain leading space characters but no embedded spaces. It must be terminated by a character other than a letter, digit, colon (:), or period (.). A space can be used.

31

These routines are available as ISIS-II calls. The following sections describe how to use each of these routines, how and where information is passed to them, how and where information is returned, and an example of each.

NOTE

A call to a Monitor I/O routine from an Assembly language program changes the contents of the registers. If the contents of a register must be saved, you should store them before calling the Monitor, and then restore them after return from the Monitor I/O routine.

CI - Console Input Routine

The Console Input routine is a routine which reads a character entered at the Intellec Console input device and returns it as a byte variable (if called from PL/M) or in the A-register (if called from the assembler). No parameters are passed to the routine. The routine, once called, loops until a character is input at the console device. The character is not echoed on the Console Output device.

The name of the Console Input routine in SYSTEM.LIB is CI.

PL/M CI Call Example

This example is of a routine which reads a string of characters from the Console device. The routine terminates when a carriage return is detected or when the number of characters specified by BUFSIZ has been read. If a carriage return is detected, the DONE code is executed and if the buffer is filled, the OVFL code is executed.

CI. PROCEDURE BYTE EXTERNAL; /*ENTRY POINT INTO SYSTEM LIB*/ END CI. /*BUFFER SIZE*/ DECLARE BUFSIZ LITERALLY '122': DECLARE BUFFER(BUFSIZ) BYTE: /*BUFFER FOR STORING CHARACTERS*/ DECLARE INDEX BYTE: /*INDEX INTO BUFFER*/ DECLARE CR LITERALLY '0DH'; /*CARRIAGE RETURN*/ INDEX = 0./*READ IN CHARACTER AND STRIP OFF*/ BUFFER(INDEX) = CI AND 7H; /*PARITY BIT*/ -4 A r 361 DO WHILE BUFFER(INDEX) <> CR; • • IF INDEX < LAST (BUFFER); DO; INDEX = INDEX + 1;BUFFER(INDEX) = CI AND 7FH; /*CONTINUE READING UNTIL A CARRIAGE*/ /*RETURN HAS BEEN INPUT OR THE*/ /*BUFFER IS FULL*/ END; ELSE 1 2 44 3 4 DO: • /*OVFL CODE*/ END: ٦ END; /*DONE CODE*/

ł

• . L

2

.> : "

GETATT—Obtain Attribute Information

The GETATT call allows your program to access the attribute associated with a disk file.

Three parameters must be passed with the GETATT call:

- The address of an ASCII string representing the name of the file for which attribute information is to be returned. The string can contain leading space characters, but no embedded spaces. It must end with a space.
- The address of a one-byte field to which attributes for the file are to be returned. The following defines this byte:

bit 0 set = invisible bit 1 set = system bit 2 set = write-protect bit 3 = reserved bit 4 = reserved bit 5 = reserved bit 6 = reserved bit 7 set = format

• The address of an address variable for the return of the completion status for the requested operation. Zero indicates completion with no error. A nonzero value is a nonfatal error number. The error numbers issued by the GETATT system call are listed in Appendix C.

PL/M-80 GETATT Call Example

GET PI ENC	TATT. ROCEDURE (PATH, ATTRIB, STATUS)EXTERNAL; DECLARE (PATH, ATTRIB, STATUS) ADDRESS, DGETATT,	
•		
•		
•		
•	DECLARE FILE(15) BYTE; DECLARE STATUS ADDRESS; DECLARE ATTRIB BYTE;	

Assembly Language GETATT Call Example

	EXTRN	GETATT	;MUST BE LINKED ;WITH SYSTEM.LIB
; ;GETATT			
	LHLD PUSH	FILEP H	;FILE PARAMETER
	LHLD	ATTP	ATTRIBUTE POINTER
	PUSH	н	
	POP	В	

÷

Assembly Language CO Call Example

	EXTRN	со	;ENTRY POINT INTO SYSTEM.LIB
CR	EQU	0DH	,CARRIAGE RETURN
BUFFER.	DS	122	BUFFER CONTAINING OUTPUT
•	LXI	H,BUFFER	;HL CONTAIN ADDRESS OF ,BUFFER
LUOP:	MOV	C,M	;GET CHARACTER FROM
	CALL	со	OUTPUT THE CHARACTER TO
	MVI	A,CR	۰ د ۱۰ دوم ۱
	СМР	M	;IS IT A CARRIAGE RETURN?
	JZ	EXIT	GO TO EXIT IF IT IS
	INX	н	INCREMENT BUFFER POINTER
	JMP	LOOP	OUTPUT NEXT CHARACTER
EXIT:			

RI - Reader Input Routine

The Reader Input routine reads a single character from the system Reader device and returns it as a byte value (if called from PL/M) or in the A-register (if called from the assembler). If a character is not read within 250 milliseconds, an end-of-file condition is simulated and a value of zero is returned with the 8080 carry condition code set to 1. Thus the condition of the carry bit specifies whether or not valid data was returned. Your program must handle the end-of-file character when it is read.

The name of the Reader Input routine in SYSTEM.LIB is RI.

PL/M RI Call Example

The following example uses the Reader Input routine to read a string of characters from paper tape and store them in a buffer. When the reader runs out of tape or a control/Z (1AH) character (used here as an end-of-file character) is read the operation is terminated. In this simple example there is no check made for overflowing the buffer area.

RI: PROCEDURE BYTE EXTERNAL;	/*ENTRY POINT INTO	SYSTEM.	LIB*/	
END RI;		d	•4	·
DECLARE BUFFER\$PTR ADDRESS;				
DECLARE BUFFER BASED BUFFER\$PTR	BYTE;		•	i
DECLARE ENDFILE LITERALLY '1AH',	/*END OF FILE CONDI	TION*/		
DECLARE TEMP BYTE;	/*TEMPORARY VARIA	BLE IN C	ASE*/	•
	/*READ RESULTS IN E	END OF FL	LE*/	
	/*CONDITION*/			. 14
DECLARE ESCAPE BYTE;	/*BOOLEAN TO DECIE	DE IF*/		. <i>1</i> 11
	/*SHOULD EXIT ROUT	TINE*/	•	· ,
DECLARE TRUE LITERALLY '01H';	•	•• ,	7	
DECLARE FALSE LITERALLY '00H';				
BUFFER\$PTR = .MEMORY;	/*INITIALIZE THE BUF	FER*/		-
	/*POINTER*/			1
TEMP = RI;	/*READ IN FIRST CHA	RACTER*	1	

• A pointer to the memory location for the return of the status for the requested operation. Zero indicates no error A nonzero value corresponds to a nonfatal error number. The error numbers issued by the GETD system call are listed in Appendix C

GETD requires loading an ISIS overlay (ISIS OV0) into the top of a 64K memory space with the LOAD system call before calling GETD LOAD places this overlay between 0E800H and 0F6BFH. Access the overlay entry point by linking to SYSTEM LIB. Avoid overwriting the overlay when accessing the directory desired

Reserved fields returned by GETD are different from one ISIS system call to another. Do not use 'reserved' fields in a user program which employs GETD

PL/M-80 GETD Call Example

GETD

PROCEDURE (DID,CONN,COUNT,ACTUAL,TABLE,STATUS) EXTERNAL, DECLARE (DID,CONN,COUNT,ACTUAL TABLE,STATUS) ADDRESS,

٩,

12 8

, (5)

11

لم مرد

END GETD,

DECLARE (DUMMY, STATUS, CONN, ACTUAL) ADDRESS,

DECLARE TABLE (50) STRUCTURE (Reserved (1) Byte, Filename (9) Byte, Reserved (6) Byte),

CONN = 0,

CALL LOAD ((' FO ISIS OVO'),0,0, DUMMY, STATUS),

CALL GETD (1, CONN, 50, ACTUAL, TABLE (0), STATUS)

IF STATUS < >0 THEN

Assembly Language GETD Call Example

,			
,GETD			
	EXTRN	GETD	,MUST BE LINKED
			,WITH SYSTEM LIB
ISIS OV	0 MUST B	E LOADED B	EFORE CALLING GETD
	LXI	H,O	
	SHLD	CONNP	,INITIAL 0
	LHLD	DID	,DIRECTORY
	PUSH	н	
	LXI	H,CONN	CONNECTION POINTER
	PUSH	н	
	LHLD	COUNT	,COUNT
	PUSH	н	
	LHLD	ACTP	,ACTUAL
	PUSH	н	
	LHLD	BUFFP	,BUFFER POINTER
	PUSH	н	
	POP	в	

DECLARE BUFFER(122) BYTE;	<pre>/* BUFFER CONTAINING STRING TO */ /* BE OUTPUT */</pre>
DECLARE INDEX BYTE;	/* INDEX INTO BUFFER */
DECLARE END\$FILE LITERALLY'1AH',	/* END OF FILE*/
INDEX = 0;	
CALL PO(BUFFER(INDEX)),	<pre>/* OUTPUT THE FIRST CHARACTER */</pre>
DO WHILE BUFFER(INDEX) <> END\$FILE;	
INDEX = INDEX + 1;	, k
CALL PO(BUFFER(INDEX)),	/* CONTINUE TO OUTPUT UNTIL */
	/* AN END-OF-FILE HAS BEEN PUNCHED */

Assembly Language PO Call Example

END;

	EXTRN	PO	;ENTRY POINT INTO SYSTEM.LIB FOR PO
EOF	EQU	1AH	;CONTROL/Z
BUFFER	DS	122	;BUFFER CONTAINING OUTPUT STRING
;			
	LXI	H,BUFFER	;HL CONTAINS ADDRESS OF BUFFER
LOOP:			
	MOV	C,M	;GET CHARACTER FROM BUFFER
	CALL	PO	OUTPUT THE CHARACTER TO THE
	MVI	A,EOF	,LOAD THE EOF CHARACTER INTO THE ;A-REG
	CMP	м	;IS IT AN END-OF-FILE?
	JZ	EXIT	GO TO EXIT IF IT IS
	INX	н	INCREMENT BUFFER POINTER
	JMP	LOOP	OUTPUT NEXT CHARACTER
EXIT:			

u

2

LO - List Output Routine

The List Output routine takes a single character (passed as a byte parameter if called from PL/M or passed in the C-register if called from Assembler) and transmits it to the system list device.

The name of the List Output routine in SYSTEM.LIB is LO.

'*

PL/MLO Call Example

This example uses the List Output routine to output a string of characters to the list device. The routine terminates after an ETX (03H) character is detected in the output string and is transmitted to the list device. In this simple example there is no check to see if the buffer has been exhausted.

/* ENTRY POINT INTO SYSTEM LIB */
<pre>/* BUFFER CONTAINING STRING TO */ /* BE OUTPUT */</pre>
/* INDEX INTO BUFFER */ /* TERMINAL CHARACTER */

PL/M CONSOL Call Example

```
CONSOL:

PROCEDURE (INFILE,OUTFILE,STATUS) EXTERNAL,

DECLARE (INFILE,OUTFILE,STATUS) ADDRESS;

END CONSOLE;

DECLARE INFILE(6) BYTE;

DECLARE OUTFILE(6) BYTE;

DECLARE STATUS ADDRESS;

CALL CONSOL (.INFILE,.OUTFILE,.STATUS);

IF STATUS <>0 THEN ...
```

Assembly Language CONSOL Call Example

	EXTRN	ISIS	LINK TO ISIS ENTRY POINT	
CONSOL	EQU	8	SYSTEM CALL IDENTIFIER	
;				
	MVI	C,CONSOL	;LOAD IDENTIFIER	, 'i
	LXI	D,CBLK	;LOAD PARAM ADDR	
	CALL	ISIS		
	LDA	CSTAT	;TEST ERROR STATUS	
	ORA	A		,
	JNZ	EXCEPT	BRANCH TO EXCEPTION	
			;ROUTINE	
;				
CBLK:			PARAMETER BLOCK FOR	
			CONSOL	
	DW	INFILE	POINTER TO FILE NAME	
	DW	OTFILE	POINTER TO FILE NAME	
	DW	CSTAT	POINTER TO STATUS	,
;				
INFILE:	DS	15	;INPUT FILE NAME	
OTFILE:	DS	15	OUTPUT FILE NAME	é .
CSTAT:	DS	2	STATUS (RETURNED)	
;			· · · · · · · · · · · · · · · · · · ·	AL, 1
•				

WHOCON - Determine File Assigned as System Console

The WHOCON call allows your program to determine what file is assigned as the current system input console or output console.

A parameter list of three variables must be passed with the WHOCON call:

- A value that indicates whether the input or output file (:Cl: or :CO:) name is to be returned. A value of 0 specifies output and a value of 1 specifies input.
- The address of a 15-byte buffer reserved by your program for the return of the name of the file assigned to :CI: or :CO:. The name is returned as an ASCII string terminated by a space.
- (Assembly language only) The address of a memory location for return of an error number.

Before calling the Universal PROM Programmer Input routine, you should call the Universal PROM Programmer Status routine (described later in this chapter) to ascertain the current status of the UPP. If an error occurs in the process of reading from the UPP, the content of the A-register is meaningless. Thus, you should follow the call to the UPP input routine with another call to the UPP status routine.

The name of the Universal PROM Programmer Input routine in SYSTEM.LIB is UI.

PL/M UI Call Example

The following PL/M procedure reads the first LENGTH locations from a PROM in socket 1 into the user buffer pointed to by BUFFER\$ADDRESS. If it encounters any UPP error, it will stop immediately and return the nonzero value of the UPP status byte; otherwise, it will return a value of zero after LENGTH locations have been read.

UI PROCEDURE(PROM\$ADDR) BYTE EXTERNAL	L,/* RETURNS DATA IN PROM */
DECLARE PROM\$ADDR ADDRESS,	/* AT PROM\$ADDR */
END UI,	
UPPS PROCEDURE BYTE EXTERNAL,	/* RETURNS UPP STATUS */
END UPPS,	
READ\$PROM\$TO\$BUFFER_PROCEDURE(BUF	FER\$ADDRRESS,LENGTH) BYTE,
DECLARE (BUFFER\$ADDRESS, LENGTH) ADD	RESS,
DECLARE (BUFFER BASED BUFFER\$ADDRES	S)(1) BYTE,
DECLARE SOCKET\$1 LITERALLY'2000H';	/* SELECT SOCKET 1 MASK */
DECLARE SOCKET\$2 LITERALLY'0000H',	/* SELECT SOCKET 2 MASK */
DECLARE BUSY LITERALLY'01H',	/* UPP BUSY STATUS */
DECLARE COMPLETE LITERALLY'02H',	/* OPERATION COMPLETE STATUS */
DECLARE STATUS BYTE,	/* SAVE FOR STATUS */
DECLARE 1 ADDRESS,	
DOI=0TOLENGTH-1,	
DO WHILE ((UPPS AND BUSY) $<> 0$),	/* WAIT FOR UPP READY */
END,	с. 4. ¹
BUFFER(I) = UI(I OR SOCKET\$1),	/* READ DATA */
IF (STATUS = UPPS) <> COMPLETE	·
THEN	/* CHECK STATUS */
RETURN STATUS;	· , /
END;	,
RETURN 0,	
END READ\$PROM\$TO\$BUFFER,	, , , , , , , , , , , , , , , , , , ,
	e the second

Assembly Language UI Call Example

c

The following assembly language procedure implements the same function as the preceding PL/M example. Note that the status value is returned in the A-register.

	EXTRN	UI		;ROUTINE TO READ FROM DATA
	EXTRN	UPPS		, ROUTINE TO READ UPP STATUS
BUSY	EQU	01H		,UPP BUSY CODE
COMPLT	EQU	02H		UPP OPERATION COMPLETE CODE
SOC1	EQU	2000H		SOCKET 1 SELECT MASK
SOC2	EQU	0000H		;SOCKET 2 SELECT MASK
BUFAD [.]	DW	0		,SAVE FROM BUFFER POSITION
LENGTH.	DW	0	•	SAVE FOR COUNT
PROMAD [.]	DW	0	40	SAVE FOR PROM ADDRESS OR'D WITH
				.'SOC1'

PL/M ERROR Call Example

ERROR: PROCEDURE (ERRNUM) EXTERNAL, DECLARE (ERRNUM) ADDRESS, END ERROR;	ي داني م
DECLARE ENUM ADDRESS;	۰۰ _۵ . ۳۰
CALL ERROR (ENUM);	· • • • • • •

Assembly Language ERROR Call Example

ERROR	EXTRN EQU	ISIS 12	,CALL IDENTIFIER
;	MVI LXI CALL	C,ERROR D,EBLK ISIS	,LOAD IDENTIFIER ,LOAD PARAM ADDR
; EBLK			
ERNUM.	DS DW	2 STATUS	;ERROR NUMBER FIELD ,ISIS-II WANTS TO RETURN A
STATUS:	DS	2	STATUS, SO PUT IT HERE

Program Execution

Two system calls allow your program to transfer control to another program (LOAD) or to ISIS (EXIT). The LOAD call can be used to load another program and then transfer control to it, to the Monitor, or have control returned to the calling program. The EXIT call is used to terminate processing and return to ISIS.

LOAD - Load a File of Executable Code and Transfer Control

The LOAD call allows your program to load a LOCATED or absolute object file. After the file is loaded, control is passed to the loaded program, the calling program, or to the Monitor depending on the value of a parameter.

A parameter list of five variables must be passed with the LOAD call:

- The address of an ASCII string containing the name of the file to be loaded. The string can contain leading spaces but no embedded spaces. It must be terminated by a character other than a letter, digit, colon (:), or a period (.). You can use a space.
- A bias value to be added to the load address of the program. The program is loaded at the adjusted address. The use of the bias does not mean that the program is relocatable. Usually the code cannot be executed at the biased address. For most applications, the bias will be zero.
- A value indicating where control is transferred after the load. A value of zero returns control to the calling program. The debug toggle is unchanged. A value of 1 transfers control to the loaded program. The debug toggle is reset. If the program is not a main program, its entry point is zero, which causes control to vector through location zero to the Monitor. A value of 2 transfers control to the Monitor. The debug toggle is set. The Monitor Execute (G) command can be used to start the program.

UO, PROCEDURE(PROM\$DATA, PROM\$ADDR) EXTERNAL, /* PROGRAM PROM LOCATION */ /* 'PROM\$ADDR' WITH DATA */ DECLARE PROM\$DATA BYTE; DECLARE PROM\$ADDR ADDRESS; /* 'PROM\$DATA' */ END UO, UPPS: PROCEDURE BYTE EXTERNAL; /* RETURNS UPP STATUS */ END UPPS: PROGRAM\$PROM\$FROM\$BUFFER: PROCEDURE(BUFFER\$ADDRESS,LENGTH) BYTE; DECLARE (BUFFER\$ADDRESS, LENGTH) ADDRESS; DECLARE (BUFFER BASED BUFFER\$ADDRESS)(1) BYTE; DECLARE SOCKET\$1 LITERALLY'2000H'; /* SELECT SOCKET 1 MASK */ DECLARE SOCKET\$2 LITERALLY'0000H'; /* SELECT SOCKET 2 MASK */ DECLARE BUSY LITERALLY'01H', /* UPP BUSY STATUS */ DECLARE COMPLETE LITERALLY'02H'; **1* OPERATION COMPLETE STATUS *1** DECLARE STATUS BYTE; /* SAVE FOR STATUS */ DECLARE I ADDRESS: DOI=0TOLENGTH-1; DO WHILE ((UPPS AND BUSY) <> 0); /* WAIT FOR UPP READY */ END, CALL UO(BUFFER(I), I OR SOCKET\$1); /* PROGRAM LOCATION */ IF (STATUS: = UPPS) <> COMPLETE THEN /* CHECK STATUS */ RETURN STATUS; END: , RETURN 0: END PROGRAM\$PROM\$FROM\$BUFFER;

Assembly Language UO Call Example

The following assembly language procedure implements the same function as the preceding PL/M example. Note that the status value is returned in the A-register.

BUSY COMPLT SOC1 SOC2 BUFAD: LENGTH: PROMAD:	EXTRN EXTRN EQU EQU EQU EQU DW DW DW	UO UPPS 01H 02H 2000H 0000H 0 0 0	;ROUTINE TO WRITE PROM DATA ;ROUTINE TO READ UPP STATUS ;UPP BUSY CODE ;UPP OPERATION COMPLETE CODE ;SOCKET 1 SELECT MASK ;SOCKET 2 SELECT MASK ;SAVE FOR BUFFER POSITION ;SAVE FOR BUFFER POSITION ;SAVE FOR PROM ADDRESS OR'D ;WITH 'SOC1'
PPFB:	MOV MOV SHLD	H,B L,C BUFAD	;STORE 'BUFFER\$ADDRESS'
	LXI +	H,SOC1	;SET UP PROMAD TO 'SOC1' TO GET ;'SOC1 OR ADDR'
	SHLD	PROMAD	
	XCHG		;STORE 'LENGTH'
	SHLD	LENGTH	
PPFB1:	MOV	A,H · -	;CHECK IF NO LOCATIONS LEFT ;TO READ
	ORA	L	
	RZ		;RETURN WITH RESULT ZERO IF DONE
PPFB2:	CALL	UPPS	;CHECK FOR 'NOT BUSY' STATUS
	ANI	BUSY	
	JNZ	PPFB2	;LOOP WHILE BUSY
	LHLD	PROMAD	SET UP PROM ADDRESS
	MOV	B,H	;UO EXPECTS ADDRESS IN BC
	MOV	C,L	

EXIT - Terminate Program and Return to ISIS-II

The EXIT call can be used by your program to terminate execution and return to ISIS-II. All open files are closed, with the exception of :CO: and :CI:. The current system console assignment is not changed.

A parameter list of one variable must be passed with the EXIT call:

• (Assembly language only) The address of a memory location for return of an error number.

PL/M EXIT Call Example

EXIT PROCEDURE EXTERNAL; END EXIT,
•
CALL EXIT,
•

Assembly Language EXIT Call Example

	EXTRN	ISIS	
EXIT	EQU	9	;CALL IDENTIFIER
;			
	MVI	C,EXIT	;LOAD IDENTIFIER
	LXI	D,EBLK	,LOAD PARAM ADDR
	CALL	ISIS	
;			
EBLK			
	DW	ESTAT	,POINTER TO STATUS
;			
ESTAT:	DS	2	,STATUS FIELD
,			

Monitor I/O Interface Routines

The Monitor contains the following I/O interface routines:

- Console Input, which reads a character entered at the system console.
- Console Output, which writes a character to the system console.
- Reader Input, which reads a character from the system reader device.
- Punch Output, which writes a character to the system punch device.
- List Output, which writes a character to the system list device.
- UPP Input, which reads a byte from the Universal PROM programmer. (Series II only)
- UPP Output, which writes a byte to the Universal PROM programmer. (Series II only)

DECLARE CTLC LITERALLY '03H';	/* CONTROL/C SIGNALS TERMINATE */ /* OPERATION */
IF CSTS THEN	
DO,	/* A KEY HAS BEEN PRESSED */
IF CI = CTLC THEN	
DO;	
	/* CONTROL/C RECEIVED TERMINATE */
	/* OUTPUT OPERATION, */
	· . ·
END	

END,

Assembly Language CSTS Call Example

	EXTRN	CSTS	,ENTRY POINT INTO SYSTEM LIB FOR ;CSTS
	EXTRN	Cl	ENTRY POINT INTO SYSTEM LIB FOR CI
CTLC	EQU	03H	;CONTROL/C SIGNALS TERMINATE ;OUTPUT
	CALL	CSTS	;GET CONSOLE STATUS
	RRC		,ROTATE TO CARRY FLAG
	JNC	CONT	,NO CHARACTER, CONTINUE OUTPUT ,OPERATION
	CALL	CI	,THERE IS A CHARACTER, GET IT
	CPI	CTLC	,IS IT A CONTROL/C
	JZ	TERM	;IF YES, BRANCH TO TERMINATE CODE
CONT			
,			CODE TO CONTINUE OUTPUT
			OPERATION
TERM			
			CODE TO TERMINATE OUTPUT

UPPS - Universal PROM Programmer Status Routine (Series II only)

The Universal PROM Programmer Status routine returns an eight bit status byte as a byte value (if called from PL/M) or in the A-register (if called from the Assembler). The meaning of the bits in the status byte are:

;OPERATION



. .

٠,

3

Assembly Language C	CI Call	Example
---------------------	---------	---------

	EXTRN	CI	ENTRY POINT INTO SYSTEM.LIB
BUESIZ	FOU	122	BUFFER SIZE
001012	EQU		CABBIAGE BETRUN
BIIEEEB	05	BUESIZ	BUFFER
JUFFER.	00	DUPSIZ	,DOFFER
3	LXI	H,BUFFER	HL POINT TO BEGINNING OF
	MVI	D BUESIZ	SET UP BUEFER SIZE COUNTER
LOOP		0,001 012	JET OF BOTTER BILL OUDATER
LUUI .	CALL	CI	GET CHABACTER
		754	
	MOV	λ. Δ	STORE IT IN BUFFER
			US IT A CARRIAGE RETURN
	17	DONE	
	32	DONE	CODE
` -	INIX	ц	
• 1	INA	п	
,	DCD	0	
	DOR	D	
	17		
	JZ	OVEL	IF BUFFER FULL, JUMP TO THE
		1005	
DONE	JMP	LOOP	GET THE NEXT CHARACTER
DONE:			DANE ADDE
			DONE CODE
01/51			
OVFL:		1.	
· · .		- 1	1 18
O - Console	Output Roy	utine	

CO - Console Output Routine

The Console Output routine takes a single character (passed as a byte parameter if called from PL/M or passed in the C-register if called from the assembler) and transmits it to the system console output device.

The name of the Console Output routine in SYSTEM.LIB is CO.

PL/M CO Call Example

This example uses the Console Output routine to output a string of characters to the Console device. The routine terminates after a carriage return is detected in the output string and is transmitted to the Console device. In this simple example there is no check to see if the buffer has been exhausted.

CO [·] PROCEDURE (CHAR) EXTERNAL, DECLARE CHAR BYTE; END CO;	/*ENTRY POINT INTO SYSTEM.LIB*/
DECLARE BUFFER(122) BYTE;	/*BUFFER CONTAINING STRING TO BE*/ /*OUTPUT*/
DECLARE INDEX BYTE;	/*INDEX INTO BUFFER*/
DECLARE CR LITERALLY '0DH';	/*CARRIAGE RETURN*/
INDEX ≠ 0;	
CALL CO(BUFFER(INDEX));	/*OUTPUT THE FIRST CHARACTER*/
DO WHILE BUFFER(INDEX) < > CR; INDEX = INDEX + 1;	
CALL CO(BUFFER(INDEX));	/*CONTINUE OUTPUTTING UNTIL A*/
	/*CARRIAGE RETURN HAS BEEN OUTPUT*/

END;

У

Masks to check for physical device codes:

CONSOLE	TTY	00H	00000000B	PUNCH	TTY	00H	0000000B
	CRT	01H	00000001B		PUNCH	10H	00010000B
	BATCH	02H	00000010B		Reserved	20H	00100000B
	Reserved	03H	00000011B		Reserved	30H	00110000B
READER	ттү	00H	00000000B	LIST	TTY	00H	00000000B
	PUNCH	04H	00000100B		CRT	40H	01000000B
	Reserved	08H	00001000B		PRINTER	80H	10000000B
	Reserved	0CH	00001100B		Reserved	C0H	11000000B

Note: The Monitor is initially configured when turned on to assign the console and list to the first device operated during initialization and the TTY to all other devices.

The name of the check system I/O configuration routine in SYSTEM.LIB is IOCHK.

PL/M IOCHK Call Example

This example checks which device is assigned as the system punch. If the high speed stand-alone device is being used, the program can go ahead and punch a tape because this type of device is presumed to be turned on and ready. However, if another device (e.g., TTY) is assigned as the punch device, a message must be sent to the operator to turn the punch on.

IOCHK: PROCEDURE BYTE EXTERNAL; END IOCHK;	/* ENTRY POINT INTO SYSTEM.LIB */
DECLARE DEVMSK LITERALLY'00110000B'; / DECLARE TYPE LITERALLY '00010000B';	* MASK TO ISOLATE PUNCH ASSIGNMENT */ /* MASK FOR HIGH SPEED PUNCH DEVICE */
IF (IOCHK AND DEVMSK) <> TYPE THEN DO;	
	/* PUNCH DEVICE IS NOT */
	/* HIGH SPEED PUNCH, SO SEND */
	/* MESSAGE TO THE OPERATOR */
END;	

Assembly Language IOCHK Call Example

	EXTRN	IOCHK	;ENTRY POINT INTO SYSTEM.LIB FOR ,IOCHK
DEVMSK	EQU	00110000B	MASK TO ISOLATE PUNCH DEVICE
TYPE ;	EQU	00010000B	;MASK FOR HIGH SPEED PUNCH
	CALL	IOCHK	;GET THE STATUS BYTE
	ANI	DEVMSK	;MASK ALL BUT THE PUNCH ;ASSIGNMENT
	CPI	TYPE	YES, BRANCH TO PUNCH CODE
	JZ	CONT	;OTHERWISE, EXECUTE CODE TO SEND ;MESSAGE TO THE OPERATOR

CONT:

IF CARRY THEN ESCAPE = TRUE; ELSE ESCAPE = FALSE;	
DO WHILE NOT ESCAPE;	
BUFFER = TEMP AND 7FH;	/*STORE THE CHARACTER AFTER*/
	/*STRIPPING OFF PARITY BIT*/
IF BUFFER <> END\$FILE THEN	¥**
DO	×
BUFFER\$PTR = BUFFER\$PTR + 1,	
TEMP = RI,	/*CONTINUE READING IN THE NEXT*/
	/*CHARACTER*/
IF CARRY THEN ESCAPE = TRUE,	•
END,	
END,	

Assembly	' Language	RI Call	Example
----------	------------	---------	---------

	EXTRN	RI	ENTRY POINT INTO SYSTEM LIB
EOF	EQU	1AH	, END OF FILE CONDITION
	LXI	H,BUFFER	, ,HL POINTS TO BEGINNING OF ,BUFFER
LOOP.			5.4
	CALL	RI	;GET A CHARACTER
	JC	EXIT	;EXIT IF CARRY BIT SET (I E 250
			;MS. TIME-OUT)
	ANI	7FH	STRIP OFF PARITY BIT
	MOV	M,A	STORE IT IN THE BUFFER
	CPI	EOF	,IS IT AN EOF CHARACTER?
	JΖ	EXIT	,EXIT IF IT IS
	INX	Н	,OTHERWISE, MOVE THE
			,BUFFER POINTER
	JMP	LOOP	,GET THE NEXT CHARACTER
EXIT:			
			,EXIT CODE
BUFFER	DS	1	,EXPANDABLE BUFFER
		,	;
			ć D 1

PO - Punch Output Routine

The Punch Output routine takes a single character (passed as a byte parameter if called from PL/M or passed in the C-register if called from assembler) and transmits it to the System Punch device.

The name of the Punch Output routine in SYSTEM.LIB is PO.

٠,

PL/M PO Call Example

This example uses the Punch Output routine to output a string of characters to the Punch device. The routine terminates after a Control/Z(1AH) is detected in the output string and is transmitted to the Punch device. In this simple example there is no check to see if the buffer has been exhausted.

PO: PROCEDURE (CHAR) EXTERNAL; /* ENTRY POINT INTO SYSTEM.LIB*/ DECLARE CHAR BYTE; END PO, The BOOT program determines the last 256 byte page of RAM by checking the first byte of each page starting from the beginning of memory. When the first non-RAM location is encountered, the previous byte of memory is considered to be the last byte of RAM in the system. (A 2K region is skipped from E800H to EFFFH. The BOOT ROM resides at these locations.)

This test allows the user to add additional ROMs to the system or to use memorymapped I/O boards in the system as long as the locations used begin at the start of a 256 byte page of memory. It is always best to use the last page(s) of physical memory for these purposes to preserve RAM for use by ISIS.

Example: If you use the 16 contiguous memory-mapped locations from F700H to F70FH for a peripheral controller, the top of user memory then becomes F700H-140H, or F5C0A.

PL/M MEMCK Call Example

The following example obtains the highest address of contiguous memory available.

MEMCK: PROCEDURE ADDRESS EXTERNAL; /* ENTRY POINT INTO SYSTEM.LIB */ END MEMCK;

DECLARE MADR ADDRESS; //* ADDRESS TO CONTAIN VALUE RETURNED BY MEMCK */

MADR = MEMCK;

Assembly Language MEMCK Call Example

	EXTRN	MEMCK	;ENTRY POINT INTO SYSTEM.LIB FOR ;MEMCK
MADR:	DS	2	CONTAINS VALUE RETURNED BY MEMCK
;			
	CALL	MEMCK	
	SHLD	MADR	STORE ADDRESS IN MADR

5-45

INDEX = 0, CALL LO(BUFFER(INDEX)); DO WHILE BUFFER(INDEX) <> ETX, INDEX = INDEX + 1, ., CALL LO(BUFFER(INDEX)),			/* OUTPUT THE FIRST CHARACTER */ /* CONTINUE TO OUTPUT UNTIL AN ETX */ /* HAS BEEN TRANSMITTED */
END,			en en le
Assembly Langu	Assembly Language LO Call Example		ی م ۲
EXT BUFFER: ; LOOP: EXIT [,]	EXTRN EQU DS LXI MOV CALL MVI, CMP JZ INX JMP	LO 03H 122 H,BUFFER C,M LO A,ETX M EXIT H LOOP	ENTRY POINT INTO SYSTEM LIB FOR LO TERMINATING CHARACTER BUFFER CONTAINING OUTPUT STRING ,HL CONTAINS ADDRESS OF BUFFER GET CHARACTER FROM BUFFER OUTPUT THE CHARACTER TO THE LIST ,LOAD EXT CHARACTER INTO A-REG IS IT AN END OF FILE? BRANCH TO EXIT IF IT IS INCREMENT BUFFER POINTER OUTPUT NEXT CHARACTER

UI - Universal PROM Programmer Input Routine (Series II only)

The Universal PROM Programmer Input routine reads eight bits of data from the Universal PROM Programmer (UPP) and returns it as a byte value (if called from PL/M) or in the A-register (if called from the Assembler). The PROM address of the desired data is passed as an address parameter (if called from PL/M) or is loaded into register pair BC (if called from the Assembler), as shown below:





7

The Monitor is a control program that provides supervisory functions for the Intellec microcomputer development systems. It processes the commands you enter at the console device. The set of available commands provide the following facilities:

- Displaying and modifying memory and processor registers.
- Initiating execution of your programs.
- Inserting breakpoints into your programs before execution.
- Reading hexadecimal data from an external device into memory.
- Writing hexadecimal data from memory to an external device.
- Invoking resident diagnostics.

Your communication with the Monitor is through the system console. When you enter the Monitor, the sign-on message and a prompt character are displayed on the system console. The prompt character is a period (.) at the left margin of the system console.

Command Entry

You can enter commands at the console anytime after the prompt character is displayed at the left margin.

All Monitor commands are single alphabetic characters. Some commands have optional parameters and some have required parameters. For example, the X command displays the contents of all the registers. But if you only want to see the contents of a single register, you can specify that register in the command. However, the D command, which displays the contents of memory, requires that beginning and ending memory locations be included in the command.

Normally, commands are ended by pressing the return key on the keyboard. There are exceptions to this and will be fully explained in the individual command descriptions.

Thus the general syntax of the Monitor commands is:

<command>[<parameters>]<CR>]

where:

<command> is the single alphabetic character for the command.

<parameters> are one or more variable data supplied with the command. Parameters can be numeric or alphabetic. When a numeric parameter is called for, it must be entered in hexadecimal form and is limited to four hexadecimal digits (0000H through FFFFH). Larger numbers can be entered but only the four rightmost digits are used by the system. For example, the value 123456H is treated as 3456H by the system.

<CR> is the carriage return key on the keyboard.

Where a comma is shown in the syntax, you can use either a comma or a space unless otherwise noted under the individual commands.

RPTB:	MOV	H,B	;STORE 'BUFFER\$ADDRESS'
	MOV	L,C	
	SHLD	BUFAD	
	LXI	H,SOC1	;SET UP PROMAD TO 'SOC1' TO GET
			;'SOC1 or ADDR'
	SHLD	PROMAD	
	XCHG		;STORE 'LENGTH'
	SHLD	LENGTH	
RPTB1:	MOV	A,H	CHECK IF NO LOCATIONS LEFT TO
			;READ
	ORA	L	
	RZ		;RETURN WITH RESULT ZERO IF DONE
RPTB2	CALL	UPPS	CHECK FOR 'UPP NOT BUSY' STATUS
	ANI	BUSY	
	JNZ	RPTB2	;LOOP WHILE BUSY
	LHLD	PROMAD	SET UP PROM ADDRESS
	MOV	B,H	UI EXPECTS ADDRESS IN BC
	MOV	C,L	
	INX	н	INCREMENT POSITION FOR NEXT TIME
	SHLD	PROMAD	STORE IT BACK
	CALL	UI	;READ PROM LOCATION
	LHLD	BUFAD	READ CURRENT BUFFER POSITION
	MOV	M,A	;STORE PROM VALUE
	INX	н	, INCREMENT POSITION FOR NEXT TIME
	SHLD	BUFAD	
	CALL	UPPS	CHECK IF OPERATION OK
	CPI	COMPLT	
	RNZ		;RETURN WITH BAD STATUS IF NOT
			;COMPLETE
	LHLD	LENGTH	;CHECK LOOP COUNTER
	DCX	н	;DECREMENT COUNT
	SHLD	LENGTH	, · · ·
	JMP	RPTB1	:LOOP

UO - Universal PROM Programmer Output Routine (Series II Only)

The Universal PROM Programmer Output routine transfers eight bits of data as a byte parameter (if called from PL/M) or from the C-register (if called from the Assembler) to the UPP. The PROM address to be programmed is passed as an address parameter (if called from PL/M), or with the most significant byte in the D-register and the least significant byte in the E-register (if called from the Assembler). See the Universal PROM Programmer Input Routine (UI) for a description of the address bits.

Before calling the Universal PROM Programmer Output routine, you should call the Universal PROM Programmer Status routine (described later in this chapter) to ascertain the current status of the UPP. You should also follow the call to the UPP output routine with another call to the UPP status routine to determine the success of the operation.

The name of the Universal PROM Programmer output routine in SYSTEM.LIB is UO.

PL/M UO Call Example

The following PL/M procedure programs the first LENGTH locations of a PROM in socket 2 from the user buffer pointed to by BUFFER\$ADDRESS. If it encounters any UPP errors, it will stop immediately and return the nonzero value of the UPP status byte; otherwise, it will return a value of zero after LENGTH locations have been programmed.

Ę

When the Monitor detects a checksum error when reading from an input device, such as a paper tape reader, it displays a cross-hatch (#) and destroys all the data from the record in which the error occurred. Subsequent records are not read.

Command Categories

The Monitor commands are divided into seven categories:

- Monitor I/O configuration
- Memory control
- Register control
- Paper tape 1/O
- Program execution
- Utility
- Diagnostics (the Z\$ command, described in *Intellec Series II Installation Manual*)

Monitor I/O Configuration Commands

The Monitor has four system devices defined:

- Console
- Reader
- Punch
- List

You have the option of selecting the actual peripheral device that will perform the required function. For example, the Console device accepts commands and data and presents error and informational messages. To perform these functions you can assign a teletype console, a CRT console, a paper tape reader (in conjunction with a printer), or some non-standard device (for which you must write the driver program).

There are two Monitor commands with which you can control the I/O configuration:

- Assign (A) to change device assignment.
- Query (Q) to find what devices are currently assigned.

To make I/O device assignments, you must understand the characteristics of the system devices.

The Console is an interactive, character-orientated input and output device. To be used as a Console, a device must have all these characteristics. A teletypewriter and a CRT terminal have all these characteristics. A paper tape punch has all but the input characteristic, therefore it can't be assigned as a Console.

The Reader is a character-oriented input device that transfers data on command and notifies the calling system when no more data is available. A paper tape reader meets these qualifications.

The Punch is a character-oriented output device that accepts a character from the calling system and records it on an external medium. A paper tape punch meets these qualifications.

INX	н	;INCREMENT POSITI	ON FOR NEXT TIME
SHLD	PROMAD	,STORE IT BACK	
LHLD	BUFAD	,READ CURRENT BU	IFFER POSITION
MOV	A,M	;READ PROM VALUE	<u>-</u>
INX	н	;INCREMENT POSITI	ON FOR NEXT TIME
SHLD	BUFAD		
CALL	UO	;PROGRAM VALUE1	NTO PROM -
CALL	UPPS	,CHECK IF OPERATIO	ON OK IBA !
CPI	COMPLT		
RNZ		;RETURN WITH BAD	STATUS IF NOT
		,COMPLETE	. · /
LHLD	LENGTH	;CHECK LOOP COUN	NTER 1 1 16
DCX	н	;DECREMENT COUN	IT - ^ -
SHLD	LENGTH		
JMP	PPFB1	;LOOP	41 J. V. HA
			· · · · · ·

113 14

(_7A". _____

11.70

5

System Status Routines

The Monitor contains the following system status routines:

- Console input status, which determines if a character is ready for input from the Console input device.
- Universal PROM programmer status, which reads an eight bit status byte from the Universal PROM Programmer.
- System I/O configuration status, which returns an eight bit byte describing the current I/O assignments.
- Set I/O configuration, which changes the current I/O assignments. $\frac{\partial^{10-5}}{\partial^{10-5}}$
- RAM memory status, which returns the highest RAM address available to the user.

The following sections describe how to use each of these routines, how and where information is passed to them, how and where information is returned, and an example of each.

CSTS - Console Input Status Routine

The Console Input Status routine tests the Console device to determine if a character is ready for input. If this routine is called from PL/M, it returns a value of 00H if no key has been pressed since the last call to the Console Input Routine (Cl), or a value of 0FFH if a key has been pressed. If this routine is called from the assembler, then the 00H or 0FFH value will be returned in the A-Register.

The name of the Console Input Status routine in SYSTEM.LIB is CSTS.

PL/M CSTS Call Example

The following example tests the Console Input Device during a Console Output operation so that the operator has the facility to signal that the output operation be terminated. A Control/C (03H) character entered at the Console Input Device will signal this termination.

1 . 19

CSTS. PROCEDURE BYTE EXTERNAL;	/* ENTRY POINT INTO SYSTEM LIB FOR */
END CSTS, CI. PROCEDURE BYTE EXTERNAL;	/* ENTRY POINT INTO SYSTEM.LIB FOR CI */
END CL	

¢

*

READER	T or TTY (teletype terminal) P or PTR (high speed paper tape reader) 1 or 2 (user-defined devices for which user-written driver programs are present)	
PUNCH	T or TTY (teletype terminal) P or PTP (high speed paper tape punch) 1 or 2 (user-defined devices or which user-written driver programs are present)	
LIST	or TTY (teletype terminal) For CRT (Intellec II compatible CRT terminal) For LPT (line printer) (user-defined device for which a user-written driver rogram is present)	

Examples of the Assign Command: To assign a high speed paper tape reader as the system Reader device:

.AR=P<CR>

or

.AREADER=PTR<CR>

To assign a CRT terminal as the system Console device:

.AC=C<CR>

or

.ACONSOLE=CRT<CR>

Q - Query Command

The Query command displays the current status of the system I/O devices. It displays a list of the system devices and the physical devices assigned to them. The format of the Query command is:

.

,, ...,

• •

.

Q

where:

Q is the Query command code. No parameters are allowed with this command.

Example of the Query Command: To list the current assignments of system devices:

.Q<CR>

The system displays:

C=T R=T P=T L=L

This response indicates that a teletype terminal is assigned as the Console, Reader, and Punch devices. A line printer is assigned as the *List* device, not the Console device.

6-5

2

: . *

If the UPP is not present or is timed-out, the value returned is 0FFH.

For additional information concerning the meaning of the status bits, see the Universal PROM Programmer Hardware Reference Manual.

The name of the Universal PROM Programmer Status routine in SYSTEM.LIB is UPPS.

See the description of UI and UO for examples of the use of UPPS.

IOCHK - Check System I/O Configuration Routine

The Check System I/O Configuration routine returns a value which describes the current assignment of physical devices to the logical system devices (Console, Reader, Punch, and List). It is returned as a byte value (if called from PL/M) or in the A-Register (if called from the assembler). This value is divided into four 2-bit fields:



The following table shows the meaning of the possible values in each field:

VALUE	CONSOLE	READER	PUNCH	LIST
00	TTY	ТТҮ	TTY	ŤΤΥ
01	CRT	H.S.READER	H.S PUNCH	CRT
10	ВАТСН	Reserved	Reserved	LINE PRINTER
11	Reserved	Reserved	Reserved	Reserved

The following are lists of the mask values you must use to check for specific system devices and types of physical devices assigned to them. The mask values are shown in hexadecimal and binary representation.

Masks to check for system device:

CONSOLE	03H	00000011B
READER	0CH	00001100B
PUNCH	30H	00110000B
LIST	C0H	11000000B

5-42
F - Fill Command

The Fill command writes a specified 1-byte constant into a specified RAM area. If ROM or PROM is specified, no error is issued, and the command continues to completion even though the memory does not change.

The format of the Fill command is:

F<low-address>,<high-address>,<constant><CR>

where:

F is the Fill command code.

vaddress> specifies the beginning of the memory range to be filled with the <constant>. The memory address must be entered in hexadecimal.

<high-address> specifies the last byte of the memory range to be filled with the <constant>. The memory address must be entered in hexadecimal.

<constant> is the byte to written to the specified address range. The <constant> must be entered as a hexadecimal number.

All three parameters of the Fill command are required.

If a character other than 0 through F is entered, the command is terminated and the prompt character (.) is displayed.

Example of the Fill Command: To initialize memory locations 20H through 2FH with 00H:

F20,2F,00<CR>

M - Move Command

The Move command copies a specified area of memory into an area of RAM. The move is done on a byte by byte basis, that is, the first byte of the specified area is copied to the new location, then the second byte is copied to the location following the first new location, and so forth. The data in the original location is not destroyed. Any data existing at the new location is overlaid.

The format of the Move command is:

M<start-address>,<end-address>,<destination-address><CR>

where:

ز ۲۰ یو ۱۱ بر ۲۰ یو ۱۰ یو از ا

1:1

• :

M is the Move command code.

<start-address> specifies the address of the first byte to be moved. The address must be specified in hexadecimal.

<end-address> specifies the address of the last byte to be moved. The address must be specified in hexadecimal.

<destination-address> specifies the address to which the first byte (start- address) is to be move. Each subsequent byte is moved to a location one higher than the last.

All three parameters are required.

IOSET - Set System I/O Configuration Routine

The Set System I/O Configuration routine modifies the system I/O configuration assignments. The new configuration is passed to the routine as a byte parameter (if called from PL/M) or in the C-register (if called from the assembler). Refer to the description of the IOCHK routine for a specification of this configuration byte parameter.

The name of the Set System I/O Configuration routine in SYSTEM.LIB is IOSET.

PL/M IOSET Call Example

The following PL/M sequence changes the Console device to be the CRT.

IOSET: PROCEDURE(CONFIG) EXTERNAL;	/* ENTRY POINT INTO SYSTEM.LIB */ /* FOR IOSET */
DECLARE CONFIG BYTE;	
END IOSET;	
IOCHK: PROCEDURE BYTE EXTERNAL;	/* ENTRY POINT INTO SYSTEM.LIB */
	/* FOR IOCHK */
END IOCHK;	

DECLARE DEVMSK LITERALLY '00000011B'; /*MASK TO ISOLATE CONSOLE ASSIGNMENT*/ DECLARE NEWDEV LITERALLY '00000001B'; /*MASK TO ASSIGN CRT TO CONSOLE*/

CALL IOSET((IOCHK AND (NOT DEVMSK)) OR NEWDEV);

Assembly Language IOSET Call Example

	EXTRN	IOSET	;ENTRY POINT INTO SYSTEM. LIB FOR ;IOSET
	EXTRN	ЮСНК	;ENTRY POINT INTO SYSTEM.LIB FOR ;IOCHK
DEVMSK	EQU	00000011B	;MASK TO ISOLATE CONSOLE ;ASSIGNMENT
NEWDEV	EQU	00000001B	;MASK TO ASSIGN CRT TO CONSOLE
	CALL	ЮСНК	;GET THE CURRENT I/O STATUS
	ANI	NOT DEVMSK	CLEAR THE CURRENT CONSOLE ;ASSIGNMENT
	ORI	NEWDEV	ASSIGN THE CRT TO THE CONSOLE ;DEVICE
	MOV	C,A	
	CALL	IOSET	SET THE NEW ASSIGNMENT

MEMCK - Check RAM Size Routine

The Check RAM Size routine returns the highest memory address of contiguous memory available to the user. This address is the highest address available after the Monitor has reserved its own memory (320 bytes) at the top of contiguous RAM. This value is returned as an address value (if called from PL/M) or in the H and L registers (if called from the assembler).

The name of the Check RAM Size routine in SYSTEM.LIB is MEMCK.

In a system containing 64K of RAM, the user top of memory is 0FFFFH minus 2K for the Monitor PROM and minus 320 bytes for Monitor RAM space, or 0F6COH. In a 32K system the top of memory is 7ECOH, since the 2K for the monitor is still located between 62 and 64K.

٦

- End the command and not modify the data byte by pressing the carriage return key: S100,FF-<CR>
- Any combination of the first two and finally ending with a carriage return: S100,FF-AA,00-,11-22<CR>. The example changes the first byte from FFH to AAH, leaves the second byte unchanged, and changes the third byte from 11H to 22H.

Register Command

There is one command to display register contents and to modify register contents. You can display the contents of all the registers, but to modify a register, you must specify a single register with the command.

k

The registers you can display and modify and their symbols in the Monitor are:

- A CPU A register
- B CPU B register
- C CPU C register
- D CPU D register
- E CPU E register
- F CPU flag byte
- H CPU H register
- I Intellec interrupt mask
- L CPU L register
- M CPU H and L registers combined
- P CPU program counter
- S CPU stack pointer

The F register is packed with the CPU condition flags:



X - Register Command (Display Form)

This form of the Register command displays the contents of all the registers. To modify register contents, use the modify form of the command. The format of the display form of the command is:

X<CR>

t

 \mathcal{C} 4 • 2 י ג ¥ ş ١ ī -/

1

2

The Intellec Monitor

Examples of the Modify Form of the Register Command: To examine but not change the M register:

XM 1234-<CR>

To examine and change the M register:

.XM 1234-5678<CR>

એક હ

114

To examine all the registers in sequence and change the D and H registers:

XA 00-,11-,22-,33-FF,44-,02-,55-FF,EC-,66-,FF66-,FC9C-,E410-<CR>

To examine and change the interrupt mask (1) and the L register:

XIFE-FC, 45-44<CR>

Paper Tape I/O Commands

The Monitor has four commands to support your usage of paper tape:

- Read (R), which reads data from a paper tape into the Intellec memory.
- Write (W), which writes data from Intellec memory to paper tape.
- End-of-File (E), which writes an end-of-file record to paper tape.
- Null Leader/Trailer (N), which writes null leader and trailer characters to paper tape.

The Intellec reads and writes paper tape in hexadecimal format. This format is described in detail in Appendix A.

R - Read Command

The Read command reads a paper tape in hexadecimal format from the device assigned as the Reader and loads the data into memory at the location specified in the record. A bias value can be specified in the command. The bias is a value that is added to the address specified in the record. The record is then loaded at a location determined by the address plus the bias value.

The format of the Read command is:

R<bias><CR>

where:

R is the Read command code.

<bias> specifies a value (modulo 65,536) to be added to the load address contained in the paper tape record. The data is loaded at the memory location specified by the record address and the bias value. The bias value must be specified in hexadecimal. Normally, a value of 0 is used.

NOTE

The addition of the bias value does not imply that the code is relocatable. In some cases, the code would not be executed at the biased location.

The data read is not changed in any way by the specification of a bias value.

د به محمد بر ام د ب

Entry Errors

The Monitor checks for several error conditions:

- Invalid characters
- Address value errors
- Checksum errors

4#

The Monitor checks the validity of each character entered at the Console device. As soon as it encounters an invalid character, it displays a cross-hatch (#) and aborts the command. It displays the prompt character on the next line and waits for more input:

4 is rejected because it is not a valid command.

The first character entered must be a valid command, otherwise it is rejected by the Monitor.

When the Monitor is expecting an address in hexadecimal (all addresses are entered in hexadecimal) any character other than 0-9 and A-F is rejected:

.D1000,1FFG#

• • . •

G is not a valid hexadecimal digit.

Many commands require two addresses where the first address is lower than the second. If the first address is higher than the second, the operation will be performed on the single address specified as the first address. For example, there is a command that fills memory with a constant value. If you meant to say fill memory from address 900 to address 1000 with FF but entered the addresses in the opposite order:

.F1000,900,FF

The Monitor would place a FF in address 1000 and do nothing else. No indication that an error occurred is given. You will only find the error when you notice that a single byte was filled instead of 100H bytes.

Addresses are evaluated modulo 65,536. That means that the highest address that will be accepted is FFFF in hexadecimal. If addresses higher than FFFF are entered, only the last four digits will be used and the command will be executed. For example, if in the previous addressing error example, we had entered 10000 instead of 1000:

.F10000,900,FF

The command would have been evaluated as:

F0000,900,FF

and memory from address 0 through 900 would have been filled with FF. This is not what you wanted, in fact, you probably wiped out data you wanted. As you'll find out later in this chapter, it did wipe out some of the memory that the Monitor itself uses. No indication of this error is given except that the Monitor will not function correctly for some commands without rebooting the system. \$

You can specify an entry point address in the end-of-file record written with the End-of-File command. The entry point address is the address of the first instruction in the program to be executed. When this address is specified in the end-of-file record, the address is loaded into the Intellec program counter when the tape is read with a Read command. The program can then be executed by a simple Execute (G) command (described later). If the load address field is 0, the program counter is not altered by the Read command.

The format of the End-of-File command is:

E<entry-point><CR>

where:

E is the End-of-File command code.

<entry-point> specifies the entry point address of the program in the file to
which the end-of-file record is being added. <entry-point> must be specified in
hexadecimal. Of course an <entry-point> value does not make any sense unless
the file contains executable code. A zero should be specified if an entry point
address is not wanted.

Examples of the End-of-File Command:

To punch an end-of-file record in a tape that has just been written and specify an entry point address to be used when the tape is read with a Read command:

E0<CR>

To punch an end-of-file record in a tape that has just been written and specify an entry point address to be used when the tape is read with a Read command:

.E1000<CR>

N - Null Command

The Null command punches a 60 null character leader or trailer. The null character is a 00H. You should punch a leader before writing data to a tape and after the endof-file record. It makes the tape easier to load and saves the data on the tape from the usual damage that tape ends incur through normal handling.

The format of the Null command is:

N<CR>

where:

N is the Null command code.

Example of the Null Command: To punch a leader or trailer in a paper tape:

.N<CR>

The List device is a character-oriented output device that accepts a character from the calling program and records it on an external medium in human readable form. A line printer meets these qualifications.

One of four actual devices can be assigned to each of the system devices. The devices for which the Monitor has driver programs are:

- Teletype console with a keyboard, printer, paper tape reader, and punch. This type of device can be assigned to all the system devices.
- CRT devices with a keyboard that are compatible with the Intellec system. This type of device can be assigned to the Console or the List device.
- High speed paper tape reader. This type of device can be assigned to the Reader device.
- High speed paper tape punch. This type of device can be assigned to the Punch device.
- Line printer. This type of device can be assigned to the List device.
- Batch. This is a non-interactive mode in which CONSOLE input is read from the assigned READER device and written to the assigned LIST device. In preparing a command file for BATCH input, the user should enter commands in exactly the same way as if the system were in interactive mode. Each command should end with a carriage return/line feed pair. The period (prompt) character which is generated by the Monitor in interactive mode should not appear as part of the command. Since the Monitor will continue to read from the READER until the CONSOLE is reassigned, the last command in the BATCH command file should reassign the CONSOLE to prevent the Monitor from reading off the end of the tape.

A - Assign Command

You can assign one physical device to a system with the Assign command. The format of the comand is:

A<logical-device>=<physical-device>

where:

A is the Assign command code.

logical-device> specifies which of the system devices is to be assigned a <physical-device>. The possible values for <logical-device> are:

C or CONSOLE R or READER P or PUNCH L or LIST

The equal sign (=) must be entered.

<physical-device> specifies which of the physical devices is to be assigned to the <logical-device>. The possible values of <physical-device> for each <logical-device> are:

> CONSOLE T or TTY (teletype terminal) C or CRT (Intellec II compatible CRT terminal) B or BATCH (batch mode) 1 (user-defined device for which a user-written program is present)

where:

× . .

G is the Execute command code.

<start-address> specifies the address to be placed in the program counter. Control of the Intellec is passed to this address. The address must be specified in hexadecimal.

.

.

breakpoint1> and
breakpoint2> specify points in the program where control will be passed back to the Monitor. The breakpoints are entered in hexadecimal.

When breakpoints are specified, command entry is in the following sequence:

 Enter the command code and, optionally, the start-address followed by a comma: G1FA.

• •

.

r

2

- 2. The Monitor displays a dash: G1FA.--
- Enter the first breakpoint address: G1FA,-22C
- 4. Enter another comma if a second breakpoint is to be specified or a carriage return if only one breakpoint is wanted. If a second breakpoint is entered, follow it with a carriage return:

G1FA,-22C,-24E<CR> or G1FA,-22C<CR>

If the command contains a syntax error, no breakpoints are set. The command must be re-entered and the breakpoints again specified.

When either of the breakpoints are reached and control is returned to the Monitor, or when control is returned to the Monitor because of an interrupt 0, both breakpoints are eliminated. If you want them when you resume execution of your program you must specify them again.

Examples of the Execute Command: To pass control to the program address in the program counter:

G<CR>

Ď

To pass control to the program whose entry point is 30A:

G30A<CR>

To pass control to the program whose entry point is 30A and to set a breakpoint at address 400 within that program:

.G30A,-400<CR>

To pass control to the program whose entry point is 30A and to set two breakpoints, at addresses 400 and 500, within that program:

G30A,-400,-500<CR>

Memory Control Commands

There are four Monitor commands with which you can work with the Intellec memory. The commands that only read memory can be used on RAM as well as PROM and ROM. The commands that write to memory can only effectively be used on RAM. If you specify ROM or PROM with these commands, no error indication is given but the write portion of the command is not executed.

The Memory control commands are:

- Display (D) which displays a specified range of memory.
- Fill (F) which overlays a specified range of RAM with a constant value.
- Move (M) which copies the contents of a specified portion of memory into another RAM location.
- Substitute (S) which modifies RAM on a byte-by-byte basis.

D - Display Command

The Display command displays a section of memory formatted into lines of 16 bytes separated by spaces with the address of the first byte at the left margin.

The format of the Display command is:

D<low-address>,<high-address><CR>

where:

D is the Display command code.

<low-address> specifies the beginning of the memory range to be printed. The address must be specified in hexadecimal. <low-address> must be less than or equal to <high-address>. If <low-address> is equal to <high- address>, a single byte is printed. Also, if <low- address> is greater than <high- address>, a single byte is printed.

<high-address> specifies the end of the memory range to be printed. The address must be specified in hexadecimal.

Both parameters of the Display command are required.

If the List device is not ready, the Display command will hang. To continue, make the List device ready, or, if that isn't possible, press the interrupt 0 button on the main chassis.

Example of the Display Command: To print the contents of memory locations 109H through 12AH:

D109,12A<CR>

The system prints:

0109 09 0A 0B 0C 0D 0E 0F 0110 01 02 03 04 05 06 07 08 09 0A 0B 0C 0D 0E 0F 0120 01 02 03 04 05 06 07 08 09 0A



Interrupt processing is controlled by logic on the processor board. It provides an eight-level priority interrupt structure, using an Interrupt Mask Register (the I-register), and a "current operating level" indicator, which keeps track of the level of interrupt currently serviced. The Interrupt Mask Register is set by a program or from the Console device. You select which interrupts will be acknowledged at any time.

Interrupts 0, 1, and 2 are reserved for internal use and cannot be referenced by the user.

Priority of Interrupts

There are eight levels of interrupts, numbered 0 through 7. The levels correspond to the eight Interrupt switches and lights on the front panel. Interrupt 0 has the highest priority and Interrupt 7, the lowest. An interrupt is not serviced until all higher priority interrupts are serviced. An interrupt of level 4 that is currently being serviced can be interrupted to service an interrupt of level 3, 2, 1, or 0. It cannot be interrupted to service one of level 5, 6, or 7, nor can it be interrupted by another level 4.

The Interrupt Mask Register

The Intellec Interrupt Mask Register (1-register) determines which interrupts are accepted by the system. The Interrupt Mask Register contains eight bits, each of which corresponds to an interrupt level:

BITS	7	6	5	4	3	2	1	0	
INTERRUPT LEVELS	7	6	5	4	3	2	1	0	

A "1" bit in the Interrupt Mask Register prevents the corresponding interrupt from being serviced. A "0" bit allows the interrupt to be serviced. For example, the Intellec Monitor sets the Interrupt Mask Register to 0FEH (11111110B) which blocks all interrupts except interrupt 0.

The Interrupt Mask Register can be set programmatically by writing the desired value to Port 0FCH. For example:

MVI A,0F0H OUT 0FCH

sets the Interrupt Mask Register to 11110000B, blocking interrupts 4 through 7 and allowing interrupts 0 through 3.

A program can also read the current value of the Interrupt Mask Register from Port 0FCH. For example:

IN 0FCH

places the current value of the Interrupt Mask Register into the A-register.

2

Because the command works on a byte by byte basis, you should be careful when attempting to move a block of data to a location within the block. By the time the command reaches the end of the block, the data will have been overlaid by the first data moved.

Examples of the Move Command: To move the data currently at address 0100H through 0200H to address 0400H through 0500H:

M100,200,400<CR>

To move the data currently at address 1000H through 1FFFH to address 1500H through 24FFH.

M1500,1FFF,1A00<CR>

M1000,14FF,1500<CR>

If you tried to do the above example with a single command:

M1000,1FFF,1500<CR>

the first 500H bytes would be copied as you expected, but the second 500H bytes would be a copy of the first 500H because bytes 1500H through 1FFFH were overlaid by the first 500H bytes.

S - Substitute Command

The Substitute command displays memory locations on an individual basis and gives you the option of modifying each location as it is displayed.

The Substitute command functions differently than most of the Monitor commands. The function of this command is performed before the carriage return ($\langle CR \rangle$) is entered. The use of the command is described after the syntax and parameter descriptions. The format of the Substitute command is:

S<address>,[<data-byte>][,[<data-byte>]][...]<CR>

where:

S is the Substitute command code.

<address> specifies a RAM address. The address must be specified in hexadecimal.

<data-byte> specifies a single byte of data in hexadecimal that is to replace the byte currently at the location specified by address. This is an optional parameter. If it is not entered, the byte specified by address is not modified.

The Substitute command functions in the following manner:

- 1. Enter the command code and the address followed by a comma: S100,
- 2. The contents of the specified memory location followed by a dash is displayed: S100,FF-
- 3. You can now:
 - Modify the contents of the address by entering a new byte in hexadecimal: S100,FF-AA
 - Look at the next sequential byte of data by entering a comma: S100,FF-,00-

٠

Þ

The following example shows the skeleton of the code necessary to service an interrupt at level 1.

	ASEG		VECTOR GOES AT ABSOLUTE
	ORG JMP	8 INT1	,RST ADDRESS FOR INTERRUPT 1
	CSEG		;PUT CODE IN RELOCATABLE CODE :SEGMENT
INT1:			
1	EI		;ROUTINE CAN BE INTERRUPTED
	PUSH	PSW	;SAVE
	PUSH	в	; REGISTERS
	PUSH	D	
	PUSH	н	3
	-		

<code to service interrupt and remove signal>

•

•		
POP	н	,RESTORE
POP	D	, REGISTERS
POP	В	· · · ·
DI		;CRITICAL SECTION.
		; DISABLE INTERRUPTS
MVI	A,20H	;RESTORE CURRENT OPERATING LEVEL
OUT	0FDH	
POP	PSW	;RESTORE A REG AND FLAGS
El		, PERMIT INTERRUPTS AFTER NEXT
		; INSTRUCTION
RET		THE RETURN MUST IMMEDIATELY
		FOLLOW THE EI TO MAKE SURE
		;IT IS EXECUTED BEFORE ANOTHER
		;INTERRUPT OCCURS

where:

X is the Register command code.

No parameters are used with this form of the command.

Example of the Display Form of the Register Command: To display the contents of the Intellec registers:

X<CR>

** sas ** ** ** ** ** **

d.

The system displays:

A=00 B=78 C=00 D=47 E=11 F=02 H=FC I=FC L=20 M=FC20 P=1024 S=CD10

X - Register Command (Modify Form)

The modify form of the Register command allows you to display and optionally change the contents of the registers, one at a time.

This form of the Register command functions differently than most of the Monitor commands. The function of the command is performed before the carriage return $(\langle CR \rangle)$ is entered. The use of the command is described after the syntax and parameter descriptions. The format of the modify form of the Register command is:

X <register>, [<data>] [,[<data>]] [,...] <CR>

where:

X is the Register command code.

<register> specifies a single register by letter.

<data> specifies one or two bytes of data (depending on the register) to be placed in the register. The data must be entered in hexadecimal.

The modify form of the Register command functions in the following manner:

- 1. Enter the command code and the register letter:
- 2. The contents of the specified register followed by a dash is displayed:
- 3. You can now:
 - Modify the contents of the register by entering new hexadecimal data: XC FF-00
 - Look at the contents of the next sequential register by entering a comma: XC FF-, EE-
 - End the command and not modify the register by pressing the carriage return key: XC FF-<CB>

• Any combination of the first two and finally ending with a carriage return: XCFF-EE,EE-,02-82<CR>

This example changes the C register from FFH to EEH, leaves the D register unchanged, and changes the flag byte from 02H to 82H.



APPENDIX A HEXADECIMAL PAPER TAPE FORMAT

Object code is stored on paper tape in an ASCII representation of the program in memory. The code is blocked into records, each of which contains the record type, length, type, memory load address, and checksum in addition to the data. Figure A-1 shows the frames of a tape record.



Figure A-1. Paper Tape Record Format

The Record Mark is a colon (3AH) and is used to signal the start of a record.

The Record Length is the count of the data bytes in the record. A record length of zero indicates end-of-file.

The Load Address specifies the address at which the first data byte will be loaded. The successive data bytes will be stored in successive memory locations.

The Record Type specifies the type of this record. All data records are type 0. Endof-file records can be type 0 or 1.

The Data consists of two frames per memory word. The data is represented by hexadecimal values 00H through FFH.

The Checksum is the negative of the sum of all 8-bit bytes in the record, beginning with the Record Length and ending with the last Data byte, evaluated modulo 256. The sum of all bytes in the record (including the checksum) should be zero.

Examples of the Read Command: To read a paper tape into memory:

R0<CR>

To read a paper tape into a memory location that is 1000H above the address specified in the tape record:

R1000<CR>

W - Write Command

The Write command punches the contents of a specified memory area to the assigned punch device. The memory area is specified by the beginning and ending addresses of the data to be punched.

The Write command does not put an end-of-file record on the paper tape. Thus you can punch non-contiguous areas of memory as a single file. The end-of-file record is written by the End-of-File command (E).

The format of the Write command is:

W<start-address>,<end-address><CR>

where:

W is the Write command code.

<start-address> specifies the first memory location to be punched onto the tape. <start-address> must be specified in hexadecimal.

<end-address> specifies the last memory location to be punched into the tape. <end-address> must be specified in hexadecimal. <end-address> must be higher than <start-address>.

The final record in a paper tape file must be an end-of-file record. After you have written the last memory area to tape, you must write an end-of-file record with the End-of-File command.

Examples of the Write Command: To write the contents of memory locations 200H through 3AFH to paper tape:

.W200,3AF<CR>

To write the contents of memory locations 450H through 54FH and locations 1000H through 1FFFH to paper tape as a single file:

.W450,54F<CR>

.W1000,1FFF<CR>

E - End-of-File Command

Every paper tape file must have an end-of-file record as the last record. If the endof-file record is missing, the reader will read off the end of the tape.



The following table is for hexadecimal to decimal and decimal to hexadecimal conversion. To find the decimal equivalent of a hexadecimal number, locate the hexadecimal number in the correct position and note the decimal equivalent. Add the decimal numbers.

To find the hexadecimal equivalent of a decimal number, locate the next lower decimal number in the table and note the hexadecimal number and its position. Sub-tract the decimal number from the table from the starting number. Find the difference in the table. Continue this process until there is no difference.

BYTE					BY	TE	
HEX	DEC	HEX	DEC	HEX	DEC	HEX	DEC
_							
0	0	0	0	0	0	0	0
1	4,096	1	256	1	16	1	1
2	8,192	2	512	2	32	2	2
3	12,288	3	768	3	48	. 3	3
4	16,384	4	1,024	4	64	4	4
5	20,480	5	1,280	5	80	5	5
6	24,576	6	1,536	6	96	6	6
7	28,672	7	1,792	7	112	7	7
8	32,768	8	2,048	8	128	8	8
9	36,864	9	2,304	9	144	9	9
Α	40,960	A	2,560	A	160	A	10
В	45,056	В	2,816	Б	176	В	11
С	49,152	C	3,072	С	192	С	12
D	53,248	D	3,328	D	208	D	13
Ē	57,344	E	3,548	E	224	E	14
F	61,440	F	3,840	F	240	F	15

Execute Command

The Execute command lets you transfer control of the Intellec system from the Monitor to your own program. You can specify the starting address and one or two breakpoints with the command. The starting address is optional. If it isn't specified in the command, the address in the program counter will be used. In the following conditions, you can be sure that the desired address is in the program counter:

- You interrupted your program with the interrupt 0 switch on the front of the Intellec and you have done nothing to destroy the program's registers.
- You loaded the program from paper tape and the end-of-file record contained the entry point address. This entry point address is loaded into the program counter by the Monitor.
- You modified the program counter to your entry point address with the Register command.
- Your program returned control to the Monitor because a breakpoint was encountered.

A breakpoint is the address of an instruction within your program that, if fetched, results in the return of control to the Monitor. You may want to do this so you can check the contents of certain registers or data fields at this point in your program. When a breakpoint is reached, the instruction at the address is not executed before control is returned to the Monitor. The instruction at the breakpoint is executed when you return control to your program with the Execute command.

There are two important points you must know when using breakpoints to debug and test your program:

- In saving the CPU status for your program, the Monitor uses the top 12 bytes of your program stack. This pushes the status of your registers and program counter into the stack. You should be aware of this when examining the stack. When control is returned to your program, your registers are restored and the stack pointer is reset as if the breakpoint had never occurred.
- The Intellec interrupt system is enabled when the Monitor is entered. The Monitor cannot determine the state of the interrupt system just prior to exit from your program. It is assumed that the interrupt system was enabled and so interrupts are enabled when control is returned to your program. It is your responsibility to either enable or disable the interrupt system.

G - Execute Command

The Execute command gives control of the Intellec to the program at the address specified or implied in the command. It optionally sets one or two breakpoints in the program to which control is passed.

· · · · · · ·

If breakpoints are specified, the Execute command functions differently than most of the Monitor commands. Before the carriage return is entered, the Monitor prompts for breakpoints if a comma is entered after typing G. This use of the command is described after the syntax and parameter descriptions. The format of the Program Execute command is:

ر د

G[<start-address>][,<breakpoint1>][,<breakpoint2>]<CR>



APPENDIX C ERROR MESSAGES

This appendix lists the error messages issued by the various ISIS-II commands.

The numbered messages are listed in the first section. The unnumbered messages that are issued by specific commands are listed in subsequent sections.

Numbered ISIS-II Error Messages

By convention, error numbers 1-99 inclusive are reserved for errors that originate in or are detected by the resident routines of ISIS-II; error numbers 100-199 inclusive are reserved for user programs; and numbers 200-255 inclusive are used for errors that may be encountered by nonresident system routines. In the following list an asterisk precedes errors that are always fatal. The other errors are generally nonfatal unless they are issued by the CONSOL system call. See Tables C-1 and C-2.

- 0 No error detected.
- * 1 Limit of 19 buffers exceeded.
 - 2 AFTN does not specify an open file.
 - 3 Attempt to open more than six files simultaneously.
 - 4 Illegal filename specification.
 - 5 Illegal or unrecognized device specification in pathname.
 - 6 Attempt to write to a file open for input.
- * 7 Operation aborted; insufficient disk space.
- 8 Attempt to read from a file open for output.
- 9 No more room in disk directory.
- 10 Pathnames do not specify the same disk.
- 11 Cannot rename file; name already in use.
- 12 Attempt to open a file already open.
- 13 No such file.
- 14 Attempt to open for writing or to delete or rename a write-protected file.
- *15 Attempt to load into ISIS-II area or buffer area.
- 16 Illegal format record.
- 17 Attempt to rename/delete a non-disk file.
- *18 Unrecognized system call.
- 19 Attempt to seek on a non-disk file.
- 20 Attempt to seek backward past beginning of file.
- 21 Attempt to rescan a non-lined file.
- 22 Illegal ACCESS parameter to OPEN or access mode impossible for file specified.
- 23 No filename specified for a disk file.
- * 24 Disk error (see below).
- 25 Incorrect specification of echo file to OPEN.
- 26 Incorrect second parameter in ATTRIB system call.
- 27 Incorrect MODE parameter in SEEK system call.
- 28 Null file extension.
- *29 End of file on console input.
- *30 Drive not ready.
 - 31 Attempted seek on write-only (output) file.
- 32 Can't delete an open file.
- *33 Illegal system call parameter.
- 34 Bad third parameter in LOAD system call.
- 35 Attempt to extend a file opened for input by seeking past end-of-file.

~!

Utility Command

There is one utility command that does hexadecimal addition and subtraction for you. Many of your early errors in programming will come from mistakes in performing hexadecimal arithmetic.

H - Hexadecimal Command

The Hexadecimal command adds and subtracts two hexadecimal numbers for you. The numbers can be up to and including four hexadecimal digits. The format of the Hexadecimal command is:

H<number1>,<number2><CR>

where:

H is the Hexadecimal command code.

<number1> specifies the first number to be added. This is number is used as minuend for the subtraction. The number must be entered in hexadecimal.

<number2> specifies the second number to be added. This number is used as the subtrahend for the subtraction.

The command displays two four-digit values. The first is the addition of the two numbers and second is the subraction. Negative numbers must be entered in their twos complement form.

If more than four digits are entered, the command uses the rightmost four digits. The leading digits are lost.

Example of the Hexadecimal Command: To add and subtract E49 (minuend) and 111 (subtrahend):

.HE49,111<CR>

î

2

01	ID field miscompare.
02	Data Field CRC error.
04	Seek error.
08	Bad sector address.
0A	ID field CRC error.
0B	Protocol violations.
0C	Bad track address.
0 E	No ID address mark or sector not found.
0F	Bad data field address mark.
10	Format error.
20	Attempt to write on Write protected drive.
40	Drive has indicated a Write error.
80	Drive not ready.

-2 ·

. .

For hard disks, nn has the following meanings:

Table C-1. Nonfatal Error Numbers Returned by System Calls

OPEN	3, 4, 5, 9, 12, 13, 14, 22, 23, 25, 28.
READ	2, 8.
WRITE	2, 6
SEEK	2, 19, 20, 27, 31, 35.
RESCAN	2, 21
CLOSE	2. ·
SPATH	4, 5, 23, 28.
DELETE	4, 5 , 13, 14, 17, 23, 2 8, 32 .
RENAME	4, 5, 10, 11, 13, 17, 23, 28.
ATTRIB	4, 5, 13, 23, 26, 28
GETATT	4, 5, 13, 23, 28.
GETD	3, 4, 5, 13, 23.
CONSOL	None; all errors are fatal.
WHOCON	None.
ERROR	None
LOAD	3, 4, 5, 12, 13, 22, 23, 28, 34
EXIT	None.

Table C-2. Fatal Errors Issued by System Calls

	OPEN	1, 7, 24, 30, 33.
	READ	24, 30, 33.
	WRITE	7, 24, 30, 33.
	SEEK	7, 24, 30, 33.
	RESCAN	33.
	CLOSE	33.
	SPATH	33
	DELETE	1, 24, 30, 33.
	RENAME	1, 24, 30, 33.
	ATTRIB	1, 24, 30, 33.
	GETATT	1, 24, 30, 33.
	GETD	1, 24, 30, 33.
	CONSOL	1, 4, 5, 12, 13, 14, 22, 23, 24, 28, 30, 33
	WHOCON	33
	ERROR	33
	LOAD	1, 15, 16, 24, 30, 33
L		

112 -

11 2.01

Interrupt Mask Register Initialization

The interrupt mask register is initialized by the monitor when the system is turned on and when the RESET button is pressed. At both of these times it is set to 0FEH (11111110B); only interrupt 0 is allowed. If ISIS-II is boot loaded, the mask register is set to 0FCH (11111100B); interrupts 0 and 1 are allowed.

Interrupt Acceptance

When an interrupt occurs, the interrupt mask register is checked to see if an interrupt of that level is permitted. If it is not, no further action is taken, but the interrupt is not cleared and remains pending. If the interrupt is permitted, the "current operating level" is checked to see if another interrupt of equal or higher priority is being serviced. If so, the new interrupt remains pending until the value of the "current operating level" is less than the priority of the the new interrupt.

1

When the new interrupt can be serviced all interrupts from the Multibus are locked out, while an RST instruction to the appropriate interrupt address (see the following table) is generated and the "current operating level" is set to the new value. The interrupt lock out is then removed.

The addresses called when an interrupt is accepted are:

INTERRUPT			ł
LEVEL	ADDRESS		÷۰ ،
0	0000H		
1	0008H		
2	0010H		
3	0018H	1	in the second second
4	0020H		
5	0028H		(
6	0030H		
7	0038H		

. . .

Interrupt Removal

The program servicing an interrupt must do two things: transmit a signal to the interrupting device, telling it to remove the interrupt signal it generated initially; and restore the "current operating level" maintained by the system. The former action is device-dependent. The latter is accomplished by writing a value of 20H to port 0FDH. *This must be done with interrupts disabled*. If the code permits another interrupt to be serviced while this is being done, a stack overflow could result. The following is a sample sequence in assembly language for doing this:

<remove int<="" th=""><th>terrupt signal fro</th><th>om external device></th><th>\$</th></remove>	terrupt signal fro	om external device>	\$
DI		, DISABLE INTERRUPTS	,
MVL	A,20H		
ουτ	0FDH		
POP	PSW	;RESTORE A-REGISTER AND FLAGS	
EI		,ENABLE INTERRUPTS	

The following is a sample PL/M sequence for restoring the current operating level:

DISABLE,	/*DISABLE INTERRUPTS*/
OUTPUT(0FDH) = 20H,	/*RESTORE THE INTERRUPT LOGIC*/
ENABLE,	/*ALLOW INTERRUPTS*/

The file specified in the message was used with a list of module names in the LINK command, therefore it was expected to be a library file. The file actually was not a library file. This could be caused by a misspelled file name.

filename, SEGMENT TOO LARGE

```
1.5° - 5
```

. ^

An output segment is greater than 64K bytes. The segment portion in the file specified in the message cannot be added to the output segment because it would then be greater than 64K.

filename, INSUFFICIENT MEMORY

LINK cannot generate the output file specified in the message because there is insufficient memory for its work space, which is needed primarily for the symbol table.

Non-Fatal Error Messages

Nonfatal errors issued by LINK are written to the map file and the current console output device (if different). LINK completes processing before returning to ISIS-II.

MORE THAN 1 MAIN MODULE, CONFLICT IN modname

LINK found more than one main module in the input list. The module named in the message is found after another main module was detected previously. All main modules are included in the output module, but the starting address of the output module is taken from the first main module in the input list.

name - MULTIPLY DEFINED, DUPLICATE IN modname

The public name specified in the message was defined in more than one module, the second definition was detected in the module specified in the message.

MODULE NOT IN LIBRARY, LOOKING FOR filename (modname)

The module in the input list was not found in the specified library.

/name/ - UNEQUAL COMMON LENGTH, CONFLICT IN modname

Two named common segments with the same name but different lengths were encountered. The module containing the conflicting definition is specified in the message.

LOCATE Error Messages

Fatal Error Messages

Fatal errors encountered by LOCATE cause a message to be sent to the console output device. LOCATE terminates processing and returns control to ISIS-II.

The errors that are caused by improper command entry are followed by a partial image of the command with a cross hatch (#) in the vicinity of the error.

INVALID SYNTAX		`•	· ~	. ,	• •	22
partial command image	••	\$	1	٠.	14	''⇒ '

 $\overline{)}$ A

÷

There is an error in the internal format of the specified file. This error may be the result of a misspelled file name. The error may have occurred when the language translator produced the module or in a previous LINK, in which case you should translate the source module again and re-LOCATE. If the problem persists, it should be reported on a Software Problem Report (SPR).

filename, PROGRAM EXCEED 64K

The output module to be placed in the output file exceeds the maximum of 64K bytes.

filename, INSUFFICIENT MEMORY

LOCATE cannot process the input file specified in the message because there is insufficient memory for its work space.

Non-fatal Error Messages

Non-fatal error messages issued by LOCATE are written to the map file and the current console output device (if different). LOCATE completes processing before returning the ISIS-II

INPAGE SEGMENT > 256 BYTES COERCED TO PAGE BOUNDARY

If this message is issued, a segment marked as inpage relocatable is greater than 256 bytes. Relocation types are described in Chapter 4.

UNSATISFIED EXTERNAL(n) external name

This message is printed when an unsatisfied external name is encountered in the input file. The number (n) is the running count of the number of unsatisfied external names encountered previously, it is also used in the following message when a reference is made to the unsatisfied external name.

REFERENCE TO UNSATISIFIED EXTERNAL(n) AT xxxxH

A reference was made to the unsatisfied external name identified by the count (n) at the address specified.

(MEMORY OVERLAP FROM xxxxH THROUGH xxxxH)

This message is issued if the same memory location is defined in more than one program segment.

***E22

ч. а та -

1 . 7

£1 ...

Lib Error Messages

All LIB command error messages are nonfatal because LIB is an interactive program. The command (ADD, CREATE, DELETE, EXIT, or LIST) that caused the error is aborted.

The errors that are caused by improper command entry are followed by a partial image of the command with a cross hatch (#) in the vacinity of the error.

•1

INSUFFICIENT MEMORY

· ·

laer i

* **`**

Error Messages

1

1

The specified file contains a record of insufficient length.	7	51.5 F
	•	* 1
filename, PREMATURE EOF	۰.	5
		 1
The EOF record occurred before the length of the file indica	ted it should.	. 3
	. •	1.
pamai commano image	Ł	. G
	4 * 4(fr)	tte v v M
There is a missing left parenthesis "(" in the command.		- 15 ste

modname- ATTEMPT TO ADD DUPLICATE MODULE

The specified module already exists in the library.

MODULE NAME TOO LONG partial command image

The specified module name exceeds 31 characters.

RIGHT PARENTHESIS EXPECTED partial command image

There is a missing right parenthesis ")" in the command.

symbol- PUBLIC SYMBOL ALREADY IN LIBRARY

You attempted to add a module that contains a PUBLIC symbol that already exists in the library.

'TO' EXPECTED partial command image

The TO file is not specified in the ADD command.

UNRECOGNIZED COMMAND

An illegal or misspelled command (i.e., not ADD, CREATE, DELETE, EXIT, or LIST) was entered.

Editor Error Messages

The Editor issues the following error messages:

"n" ILLEGAL IN THIS CONTEXT

The "n" represents an alphanumeric character that is not an Editor command. Any commands that precede the illegal character are executed. Any commands that follow the illegal character are not executed.

CANNOT FIND "text"

r , 1

~

۰ · ·

¢,

ŗ



This appendix describes two programs—one written in PL/M, one written in 8080/8085 Assembly Language, with identical functions. Both programs allow you to type a file to the :C0: device by specifying:

TYPE filename

rather then

COPY filename to C0

The PL/M program must be compiled and linked with SYSTEM.LIB and PLM80.LIB and located to an actual memory location before it can be executed. The assembly language program must be assembled, linked to SYSTEM.LIB and located to an actual memory location before it can be executed.

PL/M Version of TYPE

TYPE DO,

DECLARE BUFFER(128) BYTE, DECLARE ACTUAL\$COUNT ADDRESS, DECLARE STATUS ADDRESS, DECLARE AFT\$IN ADDRESS, DECLARE READ\$ACCESS LITERALLY '1',

OPEN

```
PROCEDURE (AFT,FILE,ACCESS,MODE,STATUS) EXTERNAL, A 2010 Stress, DECLARE (AFT,FILE,ACCESS,MODE,STATUS) ADDRESS, END OPEN,
```

CLOSE PROCEDURE (AFT,STATUS) EXTERNAL, 33 DECLARE (AFT,STATUS) ADDRESS, END CLOSE,

READ

PROCEDURE (AFT, BUFFER, COUNT, ACTUAL, STATUS) EXTERNAL, DECLARE (AFT, BUFFER, COUNT, ACTUAL, STATUS) ADDRESS, END READ,

WRITE

PROCEDURE (AFT, BUFFER, COUNT, STATUS) EXTERNAL; DECLARE (AFT, BUFFER, COUNT, STATUS) ADDRESS; END WRITE,

EXIT

PROCEDURE EXTERNAL, END EXIT,

ERROR.

PROCEDURE (ERRNUM) EXTERNAL, DECLARE (ERRNUM) ADDRESS, END ERROR, · ·

-

• •

춃

	· · ·		
201	Unrecognized switch.		
202	Unrecognized delimiter character.		
203	Invalid command syntax.	~	
204	Premature end-of-file.		
206	Illegal disk label.		
207	No END statement found in input.		
208	Checksum error.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ç
209	Illegal records sequence in object module file.		
210	Insufficient memory to complete job.	• · · · · · · · · · · · · · · · · · · ·	
211	Object module record too long.	,	'
212	Bad object module record type.		
213	Illegal fixup record specified in object module file.		
214	Bad parameter in a SUBMIT file.		
215	Argument too long in a SUBMIT invocation.	(a. 73), "salah sa sa sa sa	
216	Too many parameters in a SUBMIT invocation.	testel per white	7
217	Object module record too short.		
218	Illegal object module record format.	· · · ·	•
219	Phase error in LINK.	i e	
220	No end-of-file record in object module file.	1 12 - 14 - 14 - 14 - 14 - 14 - 14 - 14	
221	Segment overflow during Link operation.	نۍ م -	
222	Unrecognized record in object module file.		
223	Fixup record pointer is incorrect.	e e e e e e e e e e e e e e e e e e e	'1
224	Illegal record sequence in object module file in LINK.		
225	Illegal module name specified.	· · · · ·	
226	Module name exceeds 31 characters.	کی ا	
227	Command syntax requires left parenthesis.		
228	Command syntax requires right parenthesis.		
229	Unrecognized control specified in command.	·· 1, ·	
230	Duplicate symbol found.	·	
231	File already exists.		
232	Unrecognized command.	•	
233	Command syntax requires a "TO" clause.	16 1 32 1	
234	File name illegally duplicated in command.	· · · · · · · · · · · · · · · · · · ·	
235	File specified in command is not a library file.	· · · · · · · · · · · · · · · · · · ·	
236	More than 249 common segments in input files.	11 k +\$*	
237	Specified common segment not found in object file.		
238	Illegal stack content record in object file.		
239	No module header in input object file.	·)	
240	Program exceeds 64K bytes.	,	

When error number 24 occurs, an additional message is output to the console:

		· •	د
STATUS=00nn		`	.s A
D=x T=yyy S=zzz	د	•	·· (· / [

where x represents the drive number, yyy the track address, zzz the sector address, and where nn has the following meanings for floppy disks: • Ŧ

			۰. ب	-	•	
01	Deleted record.				. '	
02	Data field CRC error.	۰,	•	, r .		
03	Invalid address mark.	1.3.4		•	۶ ۲	
04	Seek error.	1.1	• •	۰, ¹	a	
08	Address error.		•		*	
0A	ID field CRC error.		•	1		
0E	No address mark.					
0F	Incorrect data address mark.				۲ ۴	
10	Data overrun or data underrur	1.				
20	Attempt to write on Write Pro	tected d	rive.		,	
40	Drive has indicated a Write err	or.				
80	Drive not ready.					

ŧ

÷

4

*

,

	ORA JNZ LHLD SHLD	A ERR AFT CAFT	ſ	с т. r
; LOOP	M M/1			u
	LXI CALL LDA ORA JNZ	D,RBLK ISIS STATUS A FRR	, READ THE INPUT FILE	2 3
	LHLD MOV ORA JZ MVI	ACTUAL A,H L DONE C,WRITE	; WRITE TO THE CONSOLE	· ·
	LXI CALL LDA ORA JNZ	D,WBLK ISIS STATUS A ERR	-	
DONE:	JMP	LOOP		
	MVI LXI CALL	C,CLOSE D,CBLK ISIS	; CLOSE THE INPUT FILE	
	MVI LXI CALL	C,EXIT D,XBLK ISIS	; NORMAL EXIT	
; ERR:				
	MVI LXI CALL	C,ERROR D,EBLK ISIS	; ERROR MESSAGE	
	MVI LXI CALL	C,EXIT D,X BLK ISIS	; ERROR EXIT	١
;	DSEG	; B	EGINNING OF DATA SEGMENT	
OBLK:	DW DW	AFT BUFFER		
	DW DW DW	1 0 STATUS	; READ ACCESS ; NO ECHO	
; CBLK				,
CAFT:	DS DW	2 STATUS		
; RBLK:				
AFT:	DW DW DW DW DW	1 BUFFER 128 ACTUAL STATUS		

۰

Link Error Messages

Fatal Error Messages

Fatal errors encountered by LINK cause a message to be sent to the console output device. LINK terminates processing and returns control to ISIS-II.

The errors that are caused by improper command entry are followed by a partial image of the command with a cross hatch (#) in the vicinity of the error.

```
INVALID SYNTAX partial command image
```

There is an error in the command as entered. The error may be an unrecognized keyword, a missing comma, or a non-blank character following an ampersand.

. .

G

4

DUPLICATE FILE NAME partial command image

The same file name is specified both as an input and output file.

'TO' EXPECTED partial command image

The command syntax requires a "TO" clause to specify the output file.

LEFT PARENTHESIS EXPECTED partial command image

A PUBLICS, NAME, or PRINT keyword is not followed by a "(".

RIGHT PARENTESIS EXPECTED partial command image

The list following a PUBLICS, NAME, or PRINT keyword is not ended with a ")".

INVALID NAME partial command image

A module name contains an illegal character.

NAME TOO LONG partial command image

A module name greater than 31 characters was encountered in the command.

UNRECOGNIZED CONTROL partial command image

A character string other than NAME, MAP, or PRINT was encountered when a control keyword was expected.

filename,	PREMATURE EOF
filename,	CHECKSUM ERROR
filename,	RECORD TOO LONG
filename,	ILLEGAL RELO RECORD
filename,	FIXUP BOUNDS ERROR
filename,	ILLEGAL RECORD FORMAT
filename,	NOEOF
filename,	BAD RECORD SEQUENCE
filename,	ILLEGAL STACK CONTENT RECORD
filename.	NO MODULE HEADER RECORD

There is an error in the internal format of the specified file. This error may be the result of a misspelled file name. The error may have occurred when the language translator produced the module or in a previous LINK, in which case you should translate the source module again and relink. If the problem persists, it should be reported on a Software Problem Report (SPR).

filename, NOT A LIBRARY



3

4

Decimal	Octal	Hexadecimal	Character		Decimal	Octal	Hexadecimal	Character
0	000	00	NUL		64	100	40	0
1	001	01	SOH		65	101	41	Ā
2	002	02	STX		66	102	42	B
3	003	03	ETX		67	103	43	ō
4	004	04	EOT		68	104	44	ă
5	005	05	ENQ		69	105	45	F
6	006	06	ACK		70	106	46	F
7	007	07	BEL		71	107	47	Ġ
8	010	08	BS		72	110	48	Ĥ
9	011	09	нт н		73	111	49	1
10	012	0A	LF		74	112	4A	J
11	013	0B	VT		75	113	4B	к
12	014	0C	, FF		76	114	4C	L
13	015	0D	CR		77	115	4D	М
14	016	0E	SO		78	116	4E	N
15	017	0F	SI SI		79	117	4F	0
16	020	10	DLE		80	120	50	Р
17	021	11	DC1		81	121	51	Q
18	022	12	DC2		82	122	52	R
19	023	13	DC3	ĺ	83	123	53	S
20	024	14	DC4		84	124	54	ΙT
21	025	15	NAK		85	125	55	U
22	026	16	SYN		86	126	56	V
23	027	17	ETB	1	87	127	57	W
24	030	18	CAN		88	130	58	X
25	031	19	EM		89	131	59	Y
26	032	1A	SUB	ļ	90	132	5A	Z
27	033	18	ESC		91	133	58	1
28	034		FS 00		92	134	50	l
29	030	10			93	135	50	
21	030	15			94	130		Λ
22	0.07	20			90	137	3F 80	
33	040	21			07	140	61	
34	041	27			08	141	62	
35	043	23	#	ł	90	143	63	
36	044	24	ŝ		100	144	64	d d
37	045	25	%	1	101	145	65	0 e
38	046	26	8		102	146	66	f
39	047	27	Ĩ		103	147	67	, n
40	050	28	(104	150	68	h b
41	051	29	l ì		105	151	69	1
42	052	2A	· ·		106	152	6A	
43	053	2B	+	1	107	153	6B	ĺŔ
44	j 054	2C	'	l	108	154	6C	1
45	055	2D	-		109	155	6D	m
46	056	2E		Î .	110	156	6E	n
47	057	2F	1		111	157	6F	0
48	060	30	0	ŀ	112	160	70	р
49	061	31		ł	113	161	71	P q
50	062	32	2		114	162	/2	r
1 21	063	33	3		115	163	/3	S.
52	004	34				104	14 75	t
53	005	35	5		110	100	/5	L L
104 66	000	30			110	167	/0 77	V
50	070	20			120	170	70	W
57	070	20			120	171	70	X
58	072	30	3		199	179	7	l ^y
50	073	38		1	123	173		1 1
ñã l	074	30			124	174		l i
l 61	075	30	l ì		125	175		
62	076	3E			126	176	7E	l ~
63	077	3F	2		127	177	7F	DEL
L	L	I	L	1	·		I	

Table E-1. ASCII Code List

There is an error in the command as entered. The error may be an unrecognized keyword, a missing comma, or a non-blank character following an ampersand.

'TO' EXPECTED partial command image

The "TO" clause was not specified in the LOCATE command and the input file name does not contain an extension.

LEFT PARENTHESIS EXPECTED partial command image

A COLUMNS, ORDER, START, STACKSIZE, CODE, DATA, STACK, MEMORY, /common name/, //, NAME, or PRINT keyword is not followed by a "(".

RIGHT PARENTHESIS EXPECTED partial command image

14 4 4 T S 1

[

ł٠

The list following a COLUMNS, ORDER, START, STACKSIZE, CODE, DATA, STACK, MEMORY, /common name/, //, NAME, or PRINT keyword is not ended with a ")".

۰.,

INVALID NAME partial command image

A module name or /common name/ contains an illegal character.

NAME TOO LONG partial command image

A module name or /common name/ greater than 31 characters was encountered in the command.

common name, COMMON NOT FOUND

The input module does not contain the common segment that was specified in the command.

UNRECOGNIZED CONTROL / partial command image

A character string other than NAME, MAP, PRINT, COLUMNS, SYMBOLS, LINES, PUBLICS, PURGE, ORDER, CODE, DATA, STACK, MEMORY, /, RESTARTO, START, or STACKSIZE was encountered when a control keyword was expected.

filename, PREMATURE EOF	5 BE 67	611.17	ب متحم مرًّ
filename, RECORD TOO LONG	ri s 🔒		
filename, ILLEGAL RELO RECORD		7	٤
filename, ILLEGAL RECORD FORMAT filename, NO EOF	۰ ۲		1 3 M.
filename, BAD RECORD SEQUENCE filename, ILLEGAL STACK CONTENT RECORD			¢ !
filename, NO MODULE HEADER RECORD	۰ ۰	•	. ÷

intel

INDEX

* t

. 3-41 // 4-14 /common name/, 4-14 ?, 3-7 :, 2-4 :BB:, 2-5 :CI:, 2-4 :CO:, 2-4 :Fn:, 2-4 :HP:, 2-4 :HR:, 2-4 :LP:, 2-4 :TI:, 2-4 :TO:, 2-4 :TP:, 2-4 :TR:, 2-4 :VI:, 2-4 :VO:, 2-4 A command Editor, 3-53 Monitor, 6-4 A switch of FORMAT command, 3-13 aborting commands, Editor, 3-41 absolute code converted from hexadecimal code, 3-39 absolute object module, 4-3 absolute information, 4-3 accepting interrupts, 7-2 accessing devices, 2-5 files, 2-5 ADD command, 4-18 addressing relative, 4-4 AFTN, 5-8 aids, user, 3-1 angle brackets, 3-54 append command, 3-53 arithmetic with hex, 6-16 ASCII Codes, E-1 ASEG, 4-3 ASM80. 4-1 assembler, 1-2 assembler and relocation, 4-21 assembly language calls, 5-6 assign command, 6-4 asterisk (), 3-41 ATTRIB command, 3-37 ATTRIB system call, 5-20 attributes, 3-6 attributes, change from console, 3-37 with system call, 5-21 attribute system call, 5-22 B command, 3-44 B switch of COPY command, 3-31 base address, 4-2 BB (byte bucket), 2-5

£

1

Т

1

ł

ł

beginning of text command, 3-44 blocks, 3-5 BOOT switch, 2-7 breakpoint, 6-14 buffer use by SUBMIT, 3-25 byte bucket (:BB:), 2-5 byte relocation, 4-22 C command, 3-45 C switch of COPY command, 3-21 calls, system ATTRIB, 5-20 CI, 5-31 CLOSE, 5-15 CO, 5-32 CONSOL, 5-25 1 CSTS, 5-40 3 **DELETE**, 5-18 **ERROR**, 5-27 EXIT, 5-30 GETATT, 5-22 GETD, 5-23 **IOCHK**, 5-42 10SET, 5-44 LO, 5-35 1.1 LOAD, 5-28 **MEMCHK**, 5-44 **OPEN**, 5-8 PO, 5-34 **READ**, 5-9 RENAME, 5-19 RESCAN, 5-14 RI, 5-33 SEEK, 5-12 SPATH, 5-16 UI, 5-36 UO, 5-38 UPPS, 5-41 WHOCON, 5-26 WRITE, 5-10 care of disks, 2-5 carriage return and line feed characters, 3-42 change console device, 5-25, 5-44 change disk file attributes, 5-20 change disk file name, 5-19 changing disk file attributes, 3-37 character command, 3-45 characteristics, recording disk, 3-5 CI (device), 2-4 CI (system call), 5-31 CLOSE, 5-15 closing files, 2-5, 5-16 CO (device), 2-4 CO (system call), 5-32 CODE, 4-13 code conversion commands HEXOBJ, 3-39 **OBJHEX**, 3-40

1.1

There is not enough memory available for execution of the command.

INVALID MODULE NAME partial command image

A module name in the command is invalid. It may have in illegal first character.

INVALID SYNTAX partial command image

There is an error in the command. Check for the following:

- Misspelled keywords.
- Ampersand followed by a non-blank character.
- ADD: TO <filename> not followed by a <CR>.
- DELETE: <libname>(<modname>) not followed by a <CR>.
- DELETE: <modname> not specified.
- CREATE: <filename> not followed by <CR>.
- LIST: TO <filename> not followed by PUBLICS or <CR>.

FILE ALREADY EXISTS

The file specified in a CREATE command already exists.

filename, BAD RECORD SEQUENCE

The file specified in the command has an unexpected record sequence. It may not be terminated with an EOF record. You may have attempted to ADD a non-object or non-library file to a library.

filename, CHECKSUM ERROR

The specified file contains a record that has an invalid checksum. Go back and generate the file again.

filename, DUPLICATE SYMBOL IN INPUT

You have attempted to ADD a file that contains a PUBLIC symbol that already exists in the library.

filename, ILLEGAL RECORD FORMAT

The file specified in the command has an illegal format. The object file may contain a name that has more than 31 characters. The file may contain records in an improper order.

filename(modname): NOT FOUND

· · ·

42

You have attempted to delete a non-existant module. You may have misspelled the name.

filename, NOT LIBRARY

The specified file is not a library.

filename, OBJECT RECORD TOO SHORT
CSEG, 4-2 I CSTS, 5-40 current system console, 3 2 D command Editor, 3-49 Monitor,6-6 DATA, 4-14 data segment, 4-2 data, reading from disk, 3-53 DEBUG command, 3-23 debug mode, 3 3 debug toggle, 3-3 debugging and processing errors, 3 3 decimal to hexadecimal conversion, B 1 DELETE (LIB command), 4-18 DELETE (system call), 5 18 DELETE command, 3 34 delete characters, 3-49 delete file from directory, 5-18 deleting a disk file, 3-34 descriptions of LOCATE controls //, 4-14 /common name/, 4-14 CODE, 4-14 COLUMNS (number), 4 12 DATA, 4-14 LINES, 4-13 MAP, 4-11 MEMORY, 4 14 NAME, 4 14 NOPRINT, 4-12 **ORDER**, 4-13 PRINT, 4-12 PUBLICS, 4 13 **PURGE**, 4-13 RESTARTO, 4-15 STACK, 4-14 STACKSIZE, 4-15 START, 4-15 SYMBOLS, 4-12 determine console assignment 5-26, 5-42 determining memory space from console, 3 53 from program, 5 44 device accessing, 2-5 designations, 2-4 management, 2-3 name format, 2-3 names, system, 2-4 different source languages, using, 4-4 DIR command, 3-26 directory content, disk, 3-6 listing command, 3 26 maintenance calls, 5-19 system call, 5-23 dısk addressing, 2-5 care, 2-5 directory content, 3-6 directory listing command, 3-26 directory maintenance calls, 5-19 drives, 1-1, 2-1

2

errors, 3-3 file attribute changing, 3-37 file attribute system call, 5-22 file copying, 3-28 17 file deletion, 3 34 file directory system call, 5-23 file marker, positioning, 5-12 file renaming, 3 36 t I files, 1 2 format, 3-10, 3-12 formatting commands, 3-10, 3-12 ۱. hard platter, 2-2 initialization command, 3-10 maintenance commands, 3 10 operating system, 1-1 organization, 3 5 recording characteristics, 3 5 reading data, 3-53 -3 display command, 6 6 double density disks, 2 1 DSEG, 4-2 ·0 1 · E command Editor, 3-51 Monitor, 6 12 easier debugging and program 1 modification, 4-4 echo file, 5 8 EDIT command, 3-40 210 editing, 2-3 editing characters, 5 4 editing, line, 3-1 'n, Editor command aborting, 3-41 command entry, 3 41 command parameters, 3 41 HIL due commands 3 " " A, 3-53 B, 3-44 C, 3-45 D. 3-49 1 1 E, 3-51 4 85 E F, 3-46 1, 3-47 ł K, 3-49 L, 3-45 <u>ب</u> 4 د 5 M, 3 53 4. Q, 3-52 S, 3-48 1 7 T. 3-50 W, 3-52 Z, 3-44 ; error messages, C-9 ٤, £ formatting characters, 3-41 functions, 3 40 745 activating, 3 42 saving your work, 3-51 terminating a session, 3-51 using, 3-40 end of file command, 6-7 end of file control, 3-2 end of text command, 3 44 entry error, Monitor, 6 2 **ERROR**, 5-27 error message output, 5-27

Ν

27.8 3

The "text" represents a search argument in an F or S command that was not found in the file, from the pointer location to the end. When this message is displayed, the pointer location is not changed by the F or S command. If any commands follow the F or S command in a command string, they are not executed.

. . .

147.11

-11

::1

21

'n

1.3 4

31.4

1-2

. . . .

1 .-

e 14 - 14

٦,

all solid on 1

ہائے یہ ب

• •

• 1

ITERATION STACK FAULT

t

1

1

This message is issued when command string iterations are nested more than eight deep. None of the nested commands are executed. Any commands that preceded the first iteration string are executed. Any commands that follow the outer iteration string are not executed.

÷

۵

2

Intellec series II, 1-1 interations of command strings, 3-54 interfaces peripheral, 1-1 interrupt acceptance, 7-2 mask register, 7-2 processing, 7-1 removal, 7-2 switches, 3-3 intersegment references, 4-5 intrasegment references, 4-5 introduction, 1-1 invisible attribute, 3-6 **IOCHK**, 5-42 **IOSET**, 5-44 ISIS-II command format, 3-10 ISIS-II commands **ATTRIB**, 3-37 COPY, 3-28 **DEBUG**, 3-23 DELETE, 3-34 DIR, 3-26 EDIT, 3-40 Editor A, 3-53 B, 3-44 C, 3-45 D, 3-49 E, 3-51 F, 3-46 I, 3-47 K, 3-49 L, 3-45 M, 3-53 Q, 3-52 S, 3-48 T, 3-50 W, 3-52 Z, 3-44 **FORMAT**, 3-12 Functions, 1-2 HEXOBJ, 3-39 **IDISK**, 3-10 L1B, 4-17 ADD, 4-18 **CREATE**, 4-18 **DELETE**, 4-18 EXIT, 4-19 LIST, 4-19 LINK, 4-7 LOCATE, 4-10 Monitor A, 6-4 D, 6-6 E, 6-12 **F**, 6-7 G, 6-14 H, 6-16 M, 6-7 N, 6-13 Q, 6-5 R, 6-11 S, 6-8 W, 6-12 X, 6-9, 6-10

OBJHEX, 3-40 RENAME, 3-36 SUBMIT, 3-24 VERS, 3-38 ISIS-II resident area, 5-1 **JSIS-II** system calls ATTRIB, 5-20 CI, 5-31 CLOSE, 5-15 11 . CO, 5-32 CONSOL, 5-25 CSTS, 5-40 **DELETE**, 5-18 **ERROR**, 5-27 EXIT, 5-30 GETATT, 5-22 GETD, 5-23 **IOCHK**, 5-42 **IOSET**, 5-44 LO, 5-35 LOAD, 5-28 **MEMCK**, 5-44 **OPEN**, 5-8 PO, 5-34 READ, 5-9 RENAME, 5-19 RESCAN, 5-14 RI, 5-33 SEEK, 5-12 SPATH, 5-16 UI, 5-36 UO, 5-38 1 UPPS, 5-41 WHOCON, 5-26 1. WRITE, 5-10 ISIS-II version numbers, 3-38 K command, 3-49 kill line command, 3-49 L command, 3-45 language translations, 1-2 æ length, 3-6 15 LIB command, 4-17 LIB commands 12.6 ADD, 4-18 , **CREATE**, 4-17 **DELETE**, 4-18 ١. EXIT, 4-19 LIST, 4-19 librarian, 4-17 libraries, use of, 4-6 library files, 4-6 line command, 3-45 ~ edit buffer, reading, 5-3 edited input files, 5-3 editing, 3-1 editing characters, 3-1 3 printer, 1-1 LINES, 4-13 LINK command, 4-7 error messages, C-4 fatal, C-4 non-fatal, C-5

1

.

ş

Ĵ	с, °С	
	**	الم المحمد ال
		READ THE CONSOLE FILE TO GET THE PARAMETER STRING
		TYPE ASM LST(CR)(LF)
		AT THIS POINT, THE CONSOLE INPUT BUFFER CONTAINS
		ASM LST(CR)(LF)
		*1
		CALL READ(1, BUFFER 128 ACTUAL\$COUNT STATUS) CALL OPEN(AFT\$IN, BUFFER, READ\$ACCESS,0, STATUS), IF STATUS > 0 THEN CALL ERROR(STATUS),
		THE FILE ASM LST IS NOW OPEN FOR INPUT
		DO WHILE ACTUAL\$COUNT < > 0, CALL READ(AFT\$IN, BUFFER, 128 ACTUAL\$COUNT STATUS), IF STATUS > 0 THEN CALL ERROR(STATUS)
		CALL WRITE(0_BUFFER, ACTUAL\$COUNT_STATUS), IF STATUS > 0 THEN CALL ERROR(STATUS), END
		CALL WRITE (0, (COPY COMPLETED' 0DH, 0AH), 16, STATUS) CALL CLOSE(AFT\$IN STATUS),
		IF STATUS > 0 THEN CALL ERROR(STATUS), '

END,

CALL EXIT,

8080/8085 Assembly Language Version of TYPE

;	Sample Pro	gram		
	5011	٥		'
	EQU	U		
CLOSE	EQU			
READ	EQU	3		
WRITE	EQU	4		
EXIT	EQU	9		
ERROR	EQU	12		,
,			•	2
	EXTRN	ISIS		1
:				
,	CSEG	BEG	INNING OF CODE SEGMENT	
BEGIN		,		۲
	I XI	SP STCKA+4	ŧ	- 16 L
	MAAL	C READ	READ THE CONSOLE	
		D DPLK	, HEAD THE GONGOLE	
	GALL	1515		
	LDA	STATUS		
	ORA	Α		
	JNZ	ERR		
;				
	MVI	C,OPEN	, OPEN THE INPUT FILE	e +6 1
	LXI	D,OBLK		
	CALL	ISIS	17 · ·	
		STATUS		

£

nonfatal errors, 3-3 nonsystem disk formatting, 3-10 null command, 6-13 object file formats, 2-3 object module, 4-4 **OBJHEX** command, 3-40 obtaining file information 5-16 **OPEN**, 5-8 operating system, 1-1 **ORDER**, 4-13 order of modules in an output file, 4-9 organization of disks, 3-5 organization of memory, 5-1 overlay, 4-19 overlay management, 4-19 P switch of COPY command, 3-30 P switch of DIR command, 3-27 page boundary, 4-24 page relocation, 4-22 paper tape 1/O commands, 6-11 paper tape punch, 1-1 paper tape reader, 1-1 parameter passing to SUBMIT, 3-24 parameters, text Editor command, 3-43 passing parameters to SUBMIT, 3-24 pause switch COPY command, 3-30 **DELETE** command, 3-34 DIR command, 3-26 peripheral devices, 1-1 peripheral interfaces, 1-1 PL/M, 1-2 PL/M calls, 5-6 PLM80, 4-1 PO. 5-34 pointer, text, 3-43 position disk file marker, 5-12 position file marker at beginning, 5-14 power up, 2-7 **PRINT**, 4-12 PRINT parameter of LINK command, 4-8 printer, 1-1 processing errors and debugging, 3-3 processing interrupts, 7-1 program development, 4-4 execution calls, 5-28 execution commands, 3-23 execution under Monitor, 3-23, 6-13 execution, non-interactive, 3-24 loading, 5-28 overlays and linked loading, 4-20 segments, 4-2 public symbols and external references, 4-5 PUBLICS, 4-13 punch, 1-1 punch output, 5-34 **PURGE**, 4-13 O command

Editor, 3-52

Monitor, 6-5

ł

O switch of ATTRIB command, 3-37 of COPY command, 3-30 of DELETE command, 3-34 query command, 6-5 ٠, query switch 1 1 of ATTRIB command, 3-37 of COPY command, 3-30 of DELETE command, 3-34 question mark (?), 3-7, 3-30 **OUIT. 3-20** quit command, 3-52 R command, 6-11 **READ**, 5-9 read command, 6-11 reader, 1-1 reader input, 5-33 reading a command line, 5-4 reading data from disk, 3-53 reading from line edit buffer, 5-3 RECORD, 3-19 recording characteristics, disk, 3-4 references, external, 4-5 references, intersegment, 4-5 references, intrasegment, 4-5 register command, 6-9, 6-10 relative addressing, 4-4 relocatable object module, 4-2 relocation, 4-4 relocation and linkage, mechanics of, 4-4 relocation types, 4-22 relocation with the assembler, 4-22 removing interrupts, 7-2 **RENAME** command, 3-36 **RENAME** system call, 5-19 renaming a disk file, 3-36 RESCAN, 5-14 reset button, 2-7 RESTART0, 4-14 R1, 5-33 rubout, 3-1, 5-4 S command Editor, 3-48 Monitor, 6-8 S switch of COPY command, 3-30 of FORMAT command, 3-13 of IDISK command, 3-11 S0 parameter of ATTRIB command, 3-37 S1 parameter of ATTRIB command, 3-37 saving your work, 3-51 sectors, 3-5 SEEK, 5-12 segments, 4-2 shared subprograms, 4-4 single density disks, 2-1 source program, 4-1 single disk drive copying, 3-28 ., SPATH, 5-16 **STACK**, 4-14 1. . stack segment, 4-3 STACKSIZE, 4-15

1

æ

;		
WBLK		
	DW	0
	DW	BUFFER
ACTUAL	DS	2
	DW	STATUS
YDI K		د کر
XBLK	DW	074700
	DW	STATUS
EBLK		
STATUS	DS	2
	DW	STATUS
,		
BUFFER	DS	128
STCKA	DS	4
-		
END	BEGIN	

£ _

universal PROM programmer, 1-1 unsatisfied external reference, 4-5 unsatisfied module, 4-5 UO, 5-38 UPP input, 5-36 output, 5-38 status, 5-41 **UPPS**, 5-41 use of different source languages, 4-4 use of ISIS-II by other programs, 5-1 use of libraries, 4-6 user aids, 3-1 using ISIS-II commands, 3-8 using the Text Editor, 3-40 utility command, 6-16 utility version numbers, 3-38

VERS command, 3-38 version numbers, 3-38 VI, 2-4 VO, 2-4 W command, Editor, 3-50 Monitor, 6-12 W0 parameter of ATTRIB command, 3-37 W1 parameter of ATTRIB command, 3-37 WHOCON, 5-26 wild card file names, 3-7, 3-30 working with program modules, 4-1 WRITE, 5-10 write command Editor, 3-52 Monitor, 6-12 write-protect attribute, 3-6

X command, 6-9, 6-10

Z command, 3-44

Q



Table E-2. ASCII Code Definition

Ĩ	Abbreviation	Meaning	Decimal Code	
	NUL SOH STX ETX EOT ENQ ACK BEL BS HT LF VT FF	NULL Character Start of Heading Start of Text End of Text End of Transmission Enquiry Acknowledge Bell Backspace Horizontal Tabulation Line Feed Vertical Tabulation Form Feed	0 1 2 3 3 4 5 0 5 6 7 8 8 9 9 9 10 11 12	8 echy 8 8 8 8 8 8 8 8 8 8 8 8
	CR SO SI DLE DC1 DC2 DC3 DC4 NAK SYN ETB CAN	Carriage Return Shift Out Shift In Data Link Escape Device Control 1 Device Control 2 Device Control 3 Device Control 4 Negative Acknowledge Synchronous Idle End of Transmission Block	13 14 15 18 17 18 19 20 21 21 22 23 24	
	EM SUB ESC FS GS RS US SP DEL	End of Medium Substitute Escape File Separator Group Separator Necord Separator Unit Separator Space Delete	24 25 26 27 28 29 30 31 31 32 127	
•				· · · · · · · · · · · · · · · · · · ·

E-2

l

CODE segment, 4-2 COLUMNS, (number), 4-12 command aborting, Editor, 3-41 categories, Monitor, 6-3 entry, Editor, 3-41 entry, Monitor, 6-1 line, reading, 5-4 parameters, Editor, 3-41 sequence definition file, 3-24 string iterations, 3-54 syntax Editor, 3-43 ISIS-11, 3-10 Monitor, 6-1 commands ATTRIB, 3 37 r COPY, 3-28 His 15 DEBUG, 3-23 **DELETE**, 3-34 DIR, 3-26 EDIT, 3-43 Editor A, 3-53 ١ B, 3-44 C, 3-45 D. 3-49 E, 3-51 F, 3-46 I, 3-47 K, 3-49 L, 3-45 M, 3-53 Q, 3-52 S, 3-48 T, 3-50 W, 3-52 Z, 3-44 tcFIXMAP, 3 14 FORMAT, 3-12 HDCOPY, 3-32 HEXOBJ, 3-39 **IDISK**, 3-10 LIB, 4-17 ADD, 4-18 11.8 CREATE, 4-18 **DELETE**, 4-18 EXIT, 4-19 LIST, 4-19 LINK, 4-7 LOCATE, 4-10 Monitor A, 6-4 11 D, 6-6 Ł E, 6-12 F, 6-7 G, 6-14 H. 6-16 M, 6-7 N, 6-13 Q, 6-5 R, 6-11 S, 6-8 W, 6-12 X, 6-9, 6-10

ISIS-II User's Guide

7 4 I

ŧ

1.4

11

3

•)

40

•

٤.

• •

د ا

,

P / M

š.

ر ۲۰ م

7201

11

117 .

11

1.

207

OBJHEX, 3-40 **RENAME**, 3-36 SUBMIT, 3-24 VERS, 3-38 common segments 4-3 compiler, 1-2 composition, system, 2-1 configuration commands, Monitor, 6-3 Configurations, supported, 2-1 CONSOL, 5-25 CONSOL and SUBMIT, 3-25 console assignment, 5-25, 5-44 changing, 6-4 current, 3-2 initial system, 3-2 input, 5-31 input status, 5-40 output, 5-35 resuming output, 3 2 stopping output, 3-2 system, 3 2 user aids, 3-1 content, disk directory, 3-6 continuation lines, 4-8, 4-11 control characters control/c, 3 41 control/e, 3-24 control/1, 3-42, 3-47 11 3 control/p, 3-1,5-4 5 control/q, 3-2 control/r, 3-1,5-4 1. control/s, 3-2 control/x, 3-1, 5-4 control/z, 3 2, 5-4 control descriptions LINK, 4-7 LOCATE, 4-11 control/c, 3-41 control/e, 3-24 control/1, 3-42, 3-47 control/p, 3-1, 5-4 control/q, 3 2 control/r, 3-1, 5-4 control/s, 3-2 control/x, 3-1, 5-4 control/z, 3-2, 5-4 conversion commands HEXOBJ, 3-39 **OBJHEX**, 3-40 converting 91 **a**0 absolute object code to hexadecimal, 3-40 hexadecimal code to absolute object code, 3-39 COPY command 3-28 COPY command switches, 3-30 copying a disk file, 3-28 copying a hard disk file, 3 32 COUNT, 3-19 CPU registers, 6-9 CREATE, 4-18 creation and mangement of files, 3-1 CRT terminal, 1-1 CSD, 3-24

5

ż

error messages Editor, C-9 1818-11, C-1 LIB, C-7 LINK, C-4 LOCATE, C-5 error processing and debugging, 3-3 ERRORS, 3-21 5 111 execute command, 6-14 executing the Editor, 3-42 execution commands, program, 3-22 execution of program under Monitor, 3-23 execution, non-interactive, 3-23 EXIT (FIXMAP), 3-20 EXIT (LIB command), 4-19 EXIT (system call), 5-30 exit command, 3-51 extension, 2-4 external references and public symbols, 4-5 F command Editor, 3-46 Monitor, 6-7 F switch of DIR command, 3-27 F0 parameter of ATTRIB command, 3-37 F1 parameter of ATTR1B command, 3-37 faster program development, 4-3 fatal errors, 3-3 file accessing, 2-5 attribute changing, 3-37 attributes, 3-6 blocks, 3-6 character coding, 3-5 control commands, 3-26 copying, 3-28 creation and management, 3-1 deletion, 3-34 extensions, 2-4 from memory, 5-9 input/output calls, 5-7 length, 3-6 marker, positioning, 5-12 name format, 2-3 name, change, 3-36, 5-19 names, wild card, 3-7 renaming, 3-36, 5-19 saving, 3-51 to memory, 5-9 types, 2-4 typing, 3-50 filename, 3-6 filename command, 3-22 filename format, 2-4 files, disk, 1-2 files, initializing for 1/O, 5-8 fill command, 6-7 find command, 3-46 flexible disk care, 2-5 start-up, 2-7 FIXMAP, 3-14 commands, 3-15 Mark, 3-16 Free, 3-17 List, 3-18

ISIS-II User's Guide

Count. 3-19 Record, 3-19 Quit, 3-20 Exit, 3-20 Errors, 3-21 FOR parameter of DIR command, 3-26 τ. Ę format attribute, 3-6 FORMAT command, 3-12 format of filename, 2-3 12 1 format of ISIS-II commands, 3-10 format, name, 2-4 formatting characters, Editor 3-42 formatting nonsystem disks, 3-9 formatting system disks, 3-10, 3-12 FORT80, 4-1 FREE, 3-17 functions of the Editor, 3-40 G command, 6-14 gap, 4-9 GETATT system call, 5-22 GETD system call, 5-23 getting started with ISIS-II, 2-1 go command, 6-14 H and L registers and memory pages, 4-21 H command, 6-16 hard disk, 2-2 hardware configuration, 1-1 HDCOPY command, 3-32 1 hexadecimal arithmatic, 6-16 code, converting to absolute object code, 3-39 command, 6-16 format, 2-3 paper tape format, A-1 to decimal conversion, B-1 HEXOBJ command, 3-39 1 how LOCATE locates segments, 4-15 Я₹. HP, 2-4 11110 HR, 2-4 .,, 1 command, 3-47 I switch of DIR command, 3-27 ر ا I/O1111 configuration commands, 6-3 device management, 2-3 interface, 2-2 operations, terminate, 5-15 10 parameter of ATTRIB command, 3-37 II parameter of ATTRIB command, 3-37 IDISK command, 3-10 ٠Ľ. In-Circuit Emulators, 1-1 2-2 - 1 initial system console, 3-2 initialization command, disk, 3-10 • • • initialization of mask register, 7-1 1. 2. 181 initializing (formatting) disks, 2-2, 3-10 initializing files for 1/O, 5-8 17 inpage relocation, 4-22 input/output calls, 5-7 insert command, 3-46 inserting text, 3-47 Intellec MDS, 1-1 H ... Intellec Monitor, 6-1

ð

ISIS-II User's Guide

\$1

H. R.

-1.

٠.,

4.4

link map, 4-8 linkage and relocation, mechanics of, 4-4 linked loading and program overlays, 4-20 LIST, 4-19 LIST (FIXMAP), 3-18 listing directory, command, 3-26 LO, 5-35 LOAD, 5-28 LOCATE command, 4-10 LOCATE control descriptions //, 4-14 /common name/, 4-14 CODE, 4-14 COLUMNS (number), 4-12 DATA, 4-14 LINES, 4-13 MAP, 4-11 MEMORY, 4-14 NAME, 4-14 **ORDER**, 4-13 **PRINT**, 4-12 PUBLICS, 4-13 **PURGE**, 4-13 RESTART0, 4-14 STACK, 4-14 STACKSIZE, 4-14 START (address), 4-14 SYMBOLS, 4-12 LOCATE errors, C-5 fatal, C-5 non-fatal, C-7 LOCATE map, 4-11 LOCATE with default order, 4-15 Locating with the default, ORDER control, and specific addresses, 4-15 LP, 2-4 M command Editor, 3-53 Monitor, 6-6 maintenance, directory calls, 5-18 management and creation of files, 3-1 management, I/O device, 2-3 management, module, 2-3 MAP parameter of link command, 4-8 MAP, LINK, 4-8 MAP, LOCATE, 4-11 MARK, 3-16 MARKER, 5-6 mechanics of relation and linkage, 4-4 **MEMCK**, 5-44 memory allocation, 4-1 command, 3-53 control commands, 6-6 from file, 5-9 organization, 5-1 pages and H and L registers, 4-21 requirements, 1-1 segment, 4-3 space, determing, 3-53 to file, 5-10 usage, 2-2 MEMORY control, 4-14 merging files, 3-28

microprocessor memory allocation, 4-1 minimum memory, 2-2 modular program development, 4-3 modular programming, 1-3 module management, 2-3 module name, 4-18 Monitor calls CI, 5-31 CO, 5-32 CSTS, 5-40 **IOCHK**, 5-42 IOSET, 5-44 LO, 5-35 MEMCHK, 5-44 PO. 5-34 RI, 5-33 UI, 5-36 UO, 5-38 UPPS, 5-41 command categories, 6-3 command entry, 6-1 commands A. 6-4 D, 6-6 E, 6-12 F, 6-7 G, 6-14 H. 6-16 M, 6-7 N, 6-13 Q, 6-5 R, 6-11 S, 6-8 W, 6-12 X, 6-9, 6-10 entry errors, 6-2 I/O configuration commands, 6-3 I/O Interface routines, 5-30 memory control commands, 6-5 program execution under, 3-23 move command, 6-7 moving data, 5-9 N command, 6-13 N switch of COPY command, 3-30 name format, 2-4 NAME parameter of LINK command, 4-8 names system devices :BB:, 2-5 :CI:, 2-4 :CO:, 2-4 :Fn:, 2-4 :HP:, 2-4 :HR:, 2-4 :LP:, 2-4 :T1:, 2-4 :TO:, 2-4 :TP:, 2-4 :TR:, 2-4

:VO:, 2-4 nesting SUBMIT files, 3-24 non-interactive program execution, 3-24

:VI:, 2-4

standard devices :BB:, 2-5 :CI:, 2-4 :CO:, 2-4 :Fn:, 2-4 :HP:, 2-4 :HR:, 2-4 :LP:, 2-4 :T1:, 2-4 :TO:, 2-4 :TP:, 2-4 :TR:, 2-4 :V1:, 2-4 :VO:, 2-4 START, 4-15 start-up procedure, 2-7 starting the Editor, 3-42 starting the system, 2-7 STKLN, 4-2 storage, 2-2 string, command iterations, 3-54 SUBMIT and CONSOL, 3-25 SUBMIT command, 3-24 SUBMIT files, preparing, 3-24 substitute command Editor, 3-48 Monitor, 6-8 summary of system calls, 5-5 switches, interrupt, 3-2 SYMBOLS, 4-12 syntax of system calls, 5-6 system attribute, 3-6 call syntax and usage, 5-6 calls ATTRIB, 5-20 CI, 5-31 CLOSE, 5-15 CO, 5-32 CONSOL, 5-25 CSTS, 5-40 **DELETE**, 5-18 **ERROR**, 5-27 EX1T, 5-30 GETATT, 5-22 GETD, 5-23 **IOCHK**, 5-42 **IOSET**, 5-44 LO, 5-35 LOAD, 5-28 **MEMCHK**, 5-44 **OPEN**, 5-8 PO, 5-34 **READ**, 5-9 **RENAME**, 5-19 RESCAN, 5-14 RI, 5-33 SEEK, 5-12 SPATH, 5-16 U1, 5-36 UO, 5-38 UPPS, 5-41 WHOCON, 5-26 WRITE, 5-10 calls, cautions, 5-7

۲Ľ

3

P

calls, summary, 5-5 composition, 2-1 console, 3-2 designated device names, 2-4 disk formatting, 3-10, 3-12 start-up, 2-7 operating, 1-1 status routines, 5-40 11.1. SYSTEM.LIB, 5-6 T command, 3-50 л. TAB character, 3-42 temporary files, 3-5 s * terminate I/O operations, 5-15 ٠٢, terminate program, 5-30 terminating a line, 5-3 terminating a session, 3-51 text commands, 3-47 Text Editor command entry, 3-41 command parameters, 3-41 command string iteration, 3-54 commands A, 3-53 B, 3-44 C, 3-45 D, 3-49 E, 3-51 F. 3-46 1, 3-47 K, 3-49 L, 3-45 M, 3-53 Q, 3-52 S, 3-48 T, 3-50 W. 3-52 Z, 3-44 errors, C-9 formatting characters, 3-42 . . functions, 3-40 activating, 3-42 saving your work, 3-51 terminating a session, 3-51 using, 3-40 text pointer, 3-43 1.0 T1, 2-4 TO, 2-4 TO parameter of COPY command, 3-30 of DIR command, 3-26 of RENAME command, 3-36 top of memory, 5-44 TP, 2-4 TR, 2-4 tracks, 3-5 . 4 transferring data, 5-7 TTY, 1-1 TYPE program, D-1 type command, 3-50 types of disk files, 1-3 typing a file, 3-50

U switch of COPY command, 3-30 UI, 5-36



i il i i hid

> 4 16 200 x 4 x

> > 1

X

,

1

.